



---

## Historic Landmarks and Preservation Districts Commission

---

### Report to the Committee

---

To: Old Louisville Architectural Review Committee  
Thru: Savannah Darr, Historic Preservation Officer  
From: Priscilla Bowman, Historic Preservation Specialist  
Date: November 2, 2022 *SD*

---

**Case No:** 22-COA-0228  
**Classification:** Committee Review

#### GENERAL INFORMATION

**Property Address:** 1330 S. 2<sup>nd</sup> Street

**Applicant:** Cassidy Cook  
High Bridge Development, LLC  
101 N. 7th Street  
Louisville, KY 40202  
(502) 861-6100  
[cassidy@highbridgedev.com](mailto:cassidy@highbridgedev.com)

**Owner:** Kevin + Mary Uhls  
1330 S. 2<sup>nd</sup> Street  
Louisville, KY 40208

**Estimated Project Cost:** \$100,000.00

#### Description of proposed exterior alteration:

The applicant seeks approval to demolish an existing detached, two-car garage at the rear of the property, to construct a new 1.5-story carriage house. The carriage house will be 26'L X 30'W and will have a two-car garage on the first level with an accessory apartment on the second level, which will be accessed via an internal stairwell. The carriage house will have a raised CMU foundation, be clad in fiber cement lap siding, and have a side gable roof clad in asphalt shingles. The first story of the carriage house will have two 9' overhead garage doors on the west elevation facing the alley and two pedestrian doors on the south façade. The second story will have a shed dormer on the west elevation with four 6/6 double-hung windows. The north and south elevations will each have one more window.

## **Communications with Applicant, Completion of Application**

The application was submitted on September 16, 2022. Staff emailed the applicant to let them know that the application had been received. The case is scheduled to be heard by the Old Louisville Architectural Review Committee (ARC) on November 9, 2022 at 5:30 pm, in person, at 444 S. 5<sup>th</sup> Street, Room 101.

## **FINDINGS**

### **Guidelines**

The following design review guidelines, approved for the Old Louisville Preservation District, are applicable to the proposed exterior alteration: **Demolition, New Construction (Residential), Garage, and Site**. The report of the Commission Staff's findings of fact and conclusions with respect to these guidelines is attached to this report.

The following additional findings are incorporated in this report:

### **Site Context/ Background**

The site is located on the west side of S. 2<sup>nd</sup> Street, 11 lots south of the intersection of W. Ormsby Avenue and S. 2<sup>nd</sup> Street. The property is zoned TNZD in a Traditional Neighborhood Form District. The site contains the 2.5-story masonry, Richardsonian Romanesque style house. The garage in the rear appears to date to the 20<sup>th</sup> century. The surrounding context includes 2- and 2.5-story masonry and stone exterior homes.

In 2011, staff approved a Certificate of Appropriateness (under case number 16123-OL) for roofing and window replacement of the existing detached garage.

### **Conclusions**

The garage removal and new construction generally meet the Old Louisville Design Guidelines for **Demolition, New Construction (Residential), Garage, and Site**. The existing detached garage is a non-contributing structure to the Old Louisville Preservation District and National Register-listed Historic District. Based on research, it does not have historic significance relating to the architectural, cultural, and/or developmental history of Old Louisville. Its demolition will not have an adverse effect on the historic integrity of the 1330 S. 2<sup>nd</sup> Street site or on the District as a whole. The proposed design of the new carriage house is subordinate in size to that of the main home. The surrounding area has a diverse array of garages and carriage houses of varying styles and sizes. The height, scale, materials, and design of the proposed carriage house reflect the architectural context of the surrounding structures (**NC3**). The proposed structure also complies with applicable Land Development Code zoning and setback requirements (**NC1**). The new carriage house will be set back from the existing alley and is surrounded by garages and carriage homes of similar design. The proposed materials are appropriate and will be used in a manner that complements the main home and nearby structures. Two, single garage doors will be installed facing the rear alley (**NC40**).

**Recommendation**

On the basis of the information furnished by the applicant, Staff recommends the application for a Certificate of Appropriateness be **approved with the following conditions:**

1. The existing noncontributing building shall not be demolished in a manner that will threaten the structural integrity of any existing historic structure.
2. The lap siding shall have a 3-4" reveal depth.
3. Window, door, and garage door details and cut sheets shall be submitted to staff for review and approval prior to the issuance of building permits.
4. The raised CMU foundation shall be a split face CMU or a stuccoed CMU.
5. All wood shall be painted or opaque stained within 12 months of construction.
6. All grade level concrete shall be of historic concrete mix.
7. The applicant shall use understated fixtures when installing any type of exterior lighting. Fixture attachment shall be done so as not to damage historic fabric. Light should be directed down and away from neighbors.
8. Half-round or Ogee gutters shall be installed.
9. Trash receptacles shall be screened and stored off the alley.
10. Storm-water management provisions shall be incorporated into the design of new construction, so that any related runoff will not adversely impact nearby historic resources.
11. If the design or materials change, the applicant shall contact staff for review and approval.



Priscilla Bowman  
Historic Preservation Specialist

11/2/2022

Date

# DEMOLITION

## Design Guideline Checklist From Economic Hardship Exemption

- + Meets Guidelines
- Does Not Meet Guidelines
- +/- Meets Guidelines with Conditions as Noted
- NA Not Applicable
- NSI Not Sufficient Information

### Introduction

Unless the city has determined that it poses an imminent threat to life or property, do not demolish any historic structure or part of a historic structure that contributes to the integrity of any historic district, or any individual landmark or part of an individual landmark.

### Demolition by Neglect

*The deteriorated condition of a historic building attributable to the owner's failure to provide proper maintenance over an extended period of time will not be considered a mitigating circumstance in evaluations of economic hardship. Hardship that is attributable to a building's being allowed to deteriorate will be considered self-imposed; restoration costs incurred to remediate such neglect will not be considered.*

	Guideline	Finding	Comment
DE1	Do not demolish existing non-contributing buildings and additions in a manner that will threaten the integrity of existing contributing structures.	+	See conditions of approval
DE2	Do take steps to assure the integrity of a wall exposed to the elements by the removal of a non-historic addition.	NA	
DE3	Do remove non-historic interior finishes such as plaster, drywall, or paneling that may be exposed as a result of the removal of non-historic additions.	NA	
DE4	Do infill non-historic openings in historic walls, exposed as a result of the removal of the non-historic finishes.	NA	
DE5	Do landscape areas that are left vacant as the result of removals of non-contributing buildings and additions. Topography should be made consistent with that of adjacent properties. The slope and grades of land left vacant after demolition should continue and be consistent with those features on adjacent properties.	NA	
DE6	Do take measures to reestablish the street wall after demolition through the use of low fences, walls, and/or vegetation.	+	Replacing existing garage with new carriage house in same location.

# NEW CONSTRUCTION

## RESIDENTIAL DESIGN GUIDELINES

- + Meets Guidelines
- Does Not Meet Guidelines
- +/- Meets Guidelines with Conditions as Noted
- NA Not Applicable
- NSI Not Sufficient Information

	Guideline	Finding	Comment
<b>NC1</b>	Make sure that new designs conform to all other municipal regulations, including the Jefferson County Development Code and Zoning District Regulations.	+	
<b>NC2</b>	Do not demolish contributing structures in a historic district to make way for new or large-scale construction. Non-contributing buildings are identified in each of the district or individual landmark designations or National Register nominations.	+	The existing detached garage is a non-contributing structure.
<b>NC3</b>	Design new construction so that the building height, directional emphasis, scale, massing, and volume reflect the architectural context established by surrounding structures.	+	The surrounding area has a diverse array of garages and carriage homes of varying styles and sizes. The height and scale of the proposed carriage house reflect the architectural context of the surrounding structures.
<b>NC4</b>	Make sure that the scale of new construction does not conflict with the historic character of the neighborhood.	+	The surrounding area has a diverse array of garages and carriage homes of varying styles and sizes.
<b>NC5</b>	Incorporate materials and design elements that complement the color, size, texture, and level of craftsmanship seen in surrounding buildings.	+	The materials and overall design are complementary of nearby structures; Hardie Board siding around structure and asphalt shingle roofing will match existing home and surrounding structures.
<b>NC6</b>	Do not use materials in new construction that are visually incompatible with surrounding historic buildings within the district. Materials to be avoided include: ornamental pierced concrete masonry screens and walls, "antiqued" brick, wrought-iron porch columns, chain-link fencing, exterior carpeting, jalousie windows, glass block, picture windows, unpainted wood, and asphalt siding.	+	See comment above
<b>NC7</b>	Design new construction to reinforce the human scale of historic districts where this is a character-defining feature.	+	
<b>NC8</b>	Design new construction in such a way that it does not disrupt important public views and vistas.	+	
<b>NC9</b>	Reinforce existing patterns of open space and enclosure, created by circulation routes, fences, walls, lawns, and allees of trees, in designs for new construction.	+	

<b>NC10</b>	Design infill construction that reinforces the spatial organization established by surrounding buildings. The character of historic streetscapes relies heavily on the visual continuity established by the repetition of similarly-designed facades.	+	Carriage house will have a similarly-designed façade of neighboring structures.
<b>NC11</b>	Design infill construction in such a way that the façade's organization closely relates to surrounding buildings. Window and door openings should be similar in size to their historic counterparts, as should the proportion of window to wall space. Cornice lines, columns, and storefronts are other important character-defining facade elements.	+	
<b>NC12</b>	Design new construction so that the building mass has a similar sense of lightness or weight as surrounding historic structures. Mass is determined by the proportion of solids (walls) to voids (window and door openings). Historic window proportions are generally two-and-one-half (height) by one (width).	+	
<b>NC13</b>	Develop designs for new construction using windows that are sympathetic to the window patterns of surrounding buildings. Use of comparable frame dimensions, proportions, and muntin configurations is encouraged.	+	
<b>NC14</b>	Develop designs for new construction using front doors that are sympathetic to the door patterns of surrounding buildings. Use of comparable frame dimensions, proportion, and panel and light configuration is encouraged.	+	Two, single-car opening garage doors proposed.
<b>NC15</b>	Design new construction so that the orientation of the main entrance is the same as the majority of other buildings on the street	+	
<b>NC16</b>	Incorporate paved walks between sidewalks and the front entrances for new construction located on streets where this is a character-defining feature.	NA	
<b>NC17</b>	Retain the character-defining features of a historic building when undertaking accessibility code-required work.	NA	
<b>NC18</b>	Investigate removable or portable ramps as options to providing barrier-free access.	NA	
<b>NC19</b>	Locate handicapped access ramps on secondary elevations wherever possible. If locating a ramp on the primary façade is required, it should be installed in a manner that does not damage historic fabric and is as unobtrusive as possible.	NA	
<b>NC20</b>	Design infill construction so that it is compatible with the average height and width of surrounding buildings.	+	
<b>NC21</b>	Design new construction to have a floor-to-floor height that is within 10 percent of adjacent historic construction where the floor-to-floor height is relatively consistent, and a character-defining feature.	+	The ground floor heights are roughly the same; the second-floor height is shorter than the main home.
<b>NC22</b>	Maintain the historic rhythm of the streetscape. The space between new construction and existing structures should fall within 20 percent of the average spacing for the block.	+	

<b>NC23</b>	Maintain historic setback patterns. In order to maintain the continuity of the streetscape, setbacks for new construction should either match that of adjacent buildings where all share the same setback or be within 20 percent of neighboring structures in areas with varied setbacks.	+	
<b>NC24</b>	Ensure that the roofs of new buildings relate to those of neighboring historic structures in pitch, complexity, and visual appearance of materials.	+	Asphalt shingled, shed dormer roof with a 4/12 pitch complements neighboring structures.
<b>NC25</b>	Follow the precedent set by adjacent buildings when designing rooflines for infill construction. Where the predominant form is flat, built-up roofs are preferred. Where the predominant form is complex and steeply pitched, that is preferred. In blocks characterized by shallow-pitched roofs and pronounced overhangs with exposed rafters, these elements should be incorporated.	+	
<b>NC26</b>	Design new construction so that the orientation of the main roof form is parallel with the majority of other roofs on the street, where roof forms are relatively consistent and a character-defining feature.	+	
<b>NC27</b>	Design new construction to emphasize the existing cornice line on each block where this is a character-defining feature.	NA	
<b>NC28</b>	Integrate mechanical systems into new construction in such a way that rooftops remain uncluttered.	+	
<b>NC29</b>	Make provisions for screening and storing trash receptacles when designing new construction.	+	See conditions of approval.
<b>NC30</b>	Use an exterior sheathing that is similar to those of other surrounding historic buildings. While use of wood siding is preferred, vinyl siding may be used for new construction, but only in areas where the predominate historic construction material is wood.	+	Hardie Board siding is similar to exterior sheathing materials of surrounding buildings.
<b>NC31</b>	Use masonry types and mortars that are similar to surrounding buildings in designs for new construction. Red brick is the most common masonry material found throughout the city's historic districts.	NA	Hardie Board siding is proposed
<b>NC32</b>	Incorporate stone or cast-stone sills and lintels into new construction designs on blocks where such elements are character-defining features.	NA	
<b>NC33</b>	Do not use modern "antiqued" brick in new construction.	+	
<b>NC34</b>	Design new construction to have a raised masonry foundation, which is compatible in proportion and height with surrounding buildings. Foundation materials may be of a warm-toned poured concrete, split-face concrete block, or stuccoed concrete block that has a uniform, textured appearance.	+	See conditions of approval
<b>NC35</b>	Incorporate front porches on blocks where they are character-defining features. Design of new porches should be compatible with the form, scale, and detailing of surrounding buildings. On blocks where porch columns are prevalent, new columns should always consist of a base, shaft, and capital, and convey the appearance of actually holding up the porch roof.	NA	

<b>NC36</b>	Design porches on newly-constructed buildings so that the floor is even with or a maximum of one step below the corresponding floor of the house, the ceiling is even with that of adjacent rooms, the floor is at least 6' deep, the rhythm of the porch bays matches the facade's pattern of solids and voids, and the porch fascia board matches the height of the window head.	NA	
<b>NC37</b>	Design new garages or other secondary structures so that they complement the scale, roof form, setback, and materials of adjacent secondary structures.	+	
<b>NC38</b>	Site new garages adjacent to alleys where present. Review the garage prototype insert that identifies styles appropriate to preservation districts when planning a garage construction project.	+	Garage will be located and facing rear alley.
<b>NC39</b>	Where no alleys exist, garages should be sited at the rear of the property behind the main house. Garage doors should not face the street, and access should be along the side yard. Landscape screening along the driveway is encouraged.	NA	
<b>NC40</b>	Use of smaller, single garage doors rather than expansive double or triple doors is preferred.	+	Two, single garage doors are proposed
<b>NC41</b>	Orient the roofline of a new garage so that it is parallel with the main house or follow the predominant pattern of existing secondary structures where such a pattern exists.	+	
<b>NC42</b>	Roof pitch should be no less than one in six. Where the roof form of the main house is character-defining, owners are encouraged to echo the form of the main house.	NA	
<b>NC43</b>	Design new construction so that access to off-street parking is off alleys or secondary streets wherever possible.	+	Parking pad to be located behind carriage house, between the carriage house and alley.
<b>NC44</b>	Incorporate storm-water management provisions into the design of new construction, so that any related runoff will not adversely impact nearby historic resources.	+	See conditions of approval.

# GARAGE

## Design Guideline Checklist

- + Meets Guidelines
- Does Not Meet Guidelines
- +/- Meets Guidelines with Conditions as Noted
- NA Not Applicable
- NSI Not Sufficient Information

Design Element	Building Feature		Approved	Comments	
<b>Location</b>		+	Rear-yard location		
		+	Align with adjacent secondary structures		
		+	Use to define and enclose rear yard		
		+	Minimize paving		
<b>Materials</b>	Walls	+	Horizontal wood siding (3" or 4" exposure)	Corner boards and trim around openings.	
		NA	Board and batten siding		
		NA	Brick		
		NA	Stucco over frame or concrete block		
		NA	Cast stone, molded concrete block		
		NA	Aluminum and vinyl siding (3" or 4" exposure)		
		+	No painted concrete block.		
		+	No un-painted concrete block.		
		NA	No T-111 plywood.		
		Roof	+	Asphalt, fiberglass, wood, vinyl, or slate shingles.	
			NA	Metal roofing	
			+	Half-round or Ogee gutters	
			NA	Approved Gable-end element	
NA	No membrane roofing on sloped roofs.				
<b>Building Forms</b>	Main Block	+	Simple, rectangular, prismatic volumes		
		NA	Ell-shaped buildings		
		NA	Slightly-projecting bays		
		NA	Cantilevered, second floors		
		+	No overly-elaborate volumes		
	Roof	+	Simple gable roofs (6-in-12 minimum slope)	Gable end vent	
		+	Hipped, shed, and flat roofs with parapets		
		NA	Intersecting gables		
		+	Overhanging eaves		

		+	Half-round gutters	Ogee gutters are acceptable
		+	No low-pitched gable roofs (less than 6-in-12 slope)	
		+	No flush eaves	
		+	No roofs without gutters	
<b>Openings</b>	Garage	+	Single-car openings	
	Doors	+	Surface area of door broken up by articulated panels or stiles and rails to reduce scale	
		+	No double and triple doors	
		+	No flush garage doors (they accentuate the large size of the openings)	
	Windows	+	Use window openings to break up wall surface	
		+	Security grills installed on the inside face of the windows	

# SITE

## Design Guideline Checklist

- + Meets Guidelines NA Not Applicable
- Does Not Meet Guidelines NSI Not Sufficient Information
- +/- Meets Guidelines with Conditions as Noted

	Guideline	Finding	Comment
<b>ST1</b>	Consider the relationships that exist between the site and structure when making exterior alterations. Changes to one will affect the other. A primary goal should be to maintain a complementary relationship.	+	
<b>ST2</b>	Retain established property line patterns and street and alley widths. Any re-platting should be consistent with original development patterns.	NA	
<b>ST3</b>	Use paving materials that are compatible with adjacent sites and architectural character.	+/-	See conditions of approval
<b>ST4</b>	Restore and reuse historic paving materials for streets and sidewalks such as brick and hexagonal pavers and limestone curbing. Maintain original curbing whenever possible. The historic relationship between the road surface and edging should be preserved. Any replacement should use historic materials. If replacement with original materials is not technically or economically feasible, a substitute material may be used if it duplicates the color, texture, and visual appearance of the original.	+/-	See conditions of approval
<b>ST5</b>	Maintain brick, stone, or poured concrete steps wherever present. If replacement is required, original materials should be used. New construction should incorporate steps on blocks where they are a character-defining feature.	NA	
<b>ST6</b>	Do not harm historic resources through road widening or underground utility repair.	NA	
<b>ST7</b>	Locate driveways, parking areas, and loading docks to the side and rear of properties. Access from alleys is preferred.	+	
<b>ST8</b>	Maintain original front yard topography, including grades, slopes, elevations, and earthen berms where present. New construction should match the grade of adjacent properties. Do not recontour front-yard berms into stepped terraces, using railroad ties, landscape timbers, or any other historically-inappropriate material for retaining walls.	NA	

<b>ST9</b>	Do not carry out excavations or regrading within or adjacent to a historic building, which could cause the foundation to shift or destroy significant archeological resources.	NA	
<b>ST10</b>	Do not install masonry walls in street-visible locations unless they are used to retain earth at changes in grade, screen service areas, or unless a historic precedent exists.	NA	
<b>ST11</b>	Use materials that match existing sections of historic fencing in material, height, and detail when carrying out limited replacement projects. If an exact match cannot be made, a simplified design is appropriate.	NA	
<b>ST12</b>	Use materials that match the existing character of the original when replacing retaining walls or curbing. If an exact match cannot be made, a simplified design is appropriate.	NA	
<b>ST13</b>	Install only historically-compatible iron fencing under 2'-5" in height where there is demonstrable historic precedent.	NA	
<b>ST14</b>	Do not install front-yard fencing where there is no historic precedent.	NA	
<b>ST15</b>	Install any rear- or side-yard privacy fencing so that it is set back from the side wall at least two feet and presents the finished side out. Any privacy fencing should be less than seven feet in height. Contact the Department of Inspections, Permits, and Licenses regarding additional restrictions on fencing at corner properties.	+	
<b>ST16</b>	Do not install chain-link, split-rail, or woven-wood fencing, or concrete block walls in areas that are visible from a public way. Opaque fencing, such as painted or stained pressure-treated wood, may be permitted with appropriate design.	NA	
<b>ST17</b>	Use understated fixtures when installing any type of exterior lighting. Fixture attachment should be done so as not to damage historic fabric. Fixtures should not become a visual focal point.	NSI	See conditions of approval
<b>ST18</b>	Do not light parking areas or architectural features in a harsh manner. Generally, an average illumination level of 1.5 to 2.0 foot-candles will be sufficient. Light should be directed down and away from neighboring properties.	NA	
<b>ST19</b>	Parking lots of a certain size should have a portion of the parking area dedicated to plantings that will soften the expanse of paving. See the Jefferson County Development Code - Requirements for Landscaping and Land Use Buffers for specific requirements.	NA	
<b>ST20</b>	Use high-pressure sodium or metal halide lights to create a soft illumination where site or streetscape lighting is desired.	NA	
<b>ST21</b>	Position fixtures, such as air conditioning units, satellite dishes, greenhouse additions, and overhead wiring, on secondary elevations where they do not detract from the character of the site. Try to minimize noise levels to adjacent properties.	NSI	See conditions of approval
<b>ST22</b>	Preserve large trees whenever possible and enhance established street tree patterns by planting additional trees along public rights-of-way. Consult the city arborist to determine what tree species are suitable for placement near overhead wires. Select and place street trees so that the plantings will not obscure historic storefronts once mature. Removal of trees within or immediately adjacent to a public right-of-way or within public open spaces requires review unless directed by the city arborist for emergency or public safety reasons.	NA	
<b>ST23</b>	Ensure that all proposed cellular towers and associated fixtures will be properly screened from view.	NA	
<b>ST24</b>	Install utility lines underground whenever possible.	NA	