

# final report


May 29, 2018

## Traffic Impact Study

*Covington by the Park  
4501 Taylorsville Lake Road  
Louisville, KY*

Prepared for

Louisville Metro Planning Commission  
Kentucky Transportation Cabinet



**DIANE B. ZIMMERMAN**  
Traffic Engineering, LLC

12803 High Meadows Pike  
Prospect, KY 40059  
502.648.1858  
dianezim@att.net



## Table of Contents

|  |    |
|--|----|
| INTRODUCTION .....                               | 2  |
| Figure 1. Site Map.....                          | 2  |
| EXISTING CONDITIONS .....                        | 2  |
| Figure 2. Existing Peak Hour Volumes .....       | 4  |
| FUTURE CONDITIONS .....                          | 4  |
| Figure 3. No Build Peak Hour Volumes.....        | 5  |
| TRIP GENERATION .....                            | 6  |
| Table 1. Peak Hour Trips Generated by Site ..... | 6  |
| Figure 4. Trip Distribution Percentages.....     | 6  |
| Figure 5. Peak Hour Trips Generated by Site..... | 7  |
| Figure 6. Build Peak Hour Volumes .....          | 8  |
| ANALYSIS .....                                   | 9  |
| Table 2. Peak Hour Level of Service.....         | 9  |
| CONCLUSIONS .....                                | 11 |
| APPENDIX .....                                   | 12 |

## INTRODUCTION

The development plan for the Covington by the Park subdivision on Taylorsville Lake Road in Louisville, KY shows 633 single family lots and four residual tracts. **Figure 1** displays a map of the site. Access to the subdivision will be from Taylorsville Lake Road at the intersection with Routt Road and a new entrance, north of Routt Road. Three stub roads are provided to adjoining properties. The purpose of this study is to examine the traffic impacts of the development upon the adjacent highway system. For this study, the impact area was defined to be the intersections of Taylorsville Lake Road with Routt Road; the intersections of Taylorsville Road with Taylorsville Lake Road, South Pope Lick Road, I 265 interchange and Stone Lake Drive.




Figure 1. Site Map

## EXISTING CONDITIONS

Taylorsville Lake Road, KY 155, is a state-maintained road with an estimated 2017 ADT of 17,500 vehicles per day between KY 1531 (Routt Road) and KY 148 (Taylorsville Road), as estimated from the 2016 count at Kentucky Transportation Cabinet at station 361. The road is a three-lane highway with eleven-foot lanes with ten-foot shoulders through the study area (provided by the Kentucky Transportation Cabinet). The speed limit is 55 mph. There are no sidewalks. The intersection with KY 1531, Routt Road, is controlled with a stop sign on Routt Road. There is a southbound right turn lane at the intersection.

The intersection with Taylorsville Road (KY 148) is controlled with a traffic signal. There is a northbound right turn lane, a southbound left turn lane, and separate turning lanes on the KY 148 approach.

The intersection with South Pope Lick Road is controlled with a stop sign on South Pope Lick Road. There are no turn lanes on any approaches.

The intersection with the I 265 ramps are both controlled with traffic signals. There are left turn lanes on all approaches. The right turn lanes on all approaches are free-flow except the southbound exit ramp.

The intersection with Stone Lakes Drive is controlled with a traffic signal. There are left turn lanes on all approaches. The westbound approach has a right turn lane.

Peak hour traffic counts for the intersections were obtained on various dates. The a.m. and p.m. peak hour varied between the intersections. **Figure 2** illustrates the existing a.m. and p.m. peak hour traffic volumes.





Figure 2. Existing Peak Hour Volumes

## FUTURE CONDITIONS

The project completion date is 2030. An annual growth rate of 1.0 percent was applied to all. This is based upon a review of historical data and the potential for additional development in the vicinity. For the volumes west of I-265, the trips generated by the developments documented in the Taylorsville Road/Urton Lane Area-wide Traffic Impact Study prepared by BTM Engineering, Inc., dated August 2009, have been included. Volumes on north South Pope Lick

Road include trip generation from the two approved subdivisions, Trestle Creek and Trestle Point. **Figure 3** displays the 2030 No Build peak hour volumes. The intersection of Taylorsville Road with South Pope Lick Road is scheduled to be improved with left turn lanes on all approaches. A traffic signal is assumed to be installed by 2030.




**Figure 3. No Build Peak Hour Volumes**

## TRIP GENERATION



The Institute of Transportation Engineers Trip Generation Manual, 10<sup>th</sup> Edition contains trip generation rates for a wide range of developments. The land uses of “Single Family Detached (210)” was reviewed and determined to be the best match. The trip generation results are listed in **Table 1**. The trips were assigned to the highway network with the percentages shown in **Figure 4**. **Figure 5** shows the trips generated by this development and distributed throughout the road network during the peak hours. **Figure 6** displays the individual turning movements for the peak hours when the development is completed.

**Table 1. Peak Hour Trips Generated by Site**

| Land Use                          | A.M. Peak Hour |     |     | P.M. Peak Hour |     |     |
|-----------------------------------|----------------|-----|-----|----------------|-----|-----|
|                                   | Trips          | In  | Out | Trips          | In  | Out |
| Single-Family Detached (633 lots) | 454            | 114 | 340 | 597            | 376 | 221 |




**Figure 4. Trip Distribution Percentages**



**Figure 5. Peak Hour Trips Generated by Site**





**Figure 6. Build Peak Hour Volumes**

## ANALYSIS

The qualitative measure of operation for a roadway facility or intersection is evaluated by assigning a “Level of Service”. Level of Service is a ranking scale from A through F, “A” is the best operating condition and “F” is the worst. Level of Service results depend upon the facility that is analyzed. In this case, the Level of Service is based upon the total delay experienced at an intersection.

To evaluate the impact of the proposed development, the vehicle delays at the intersections were determined using procedures detailed in the Highway Capacity Manual, 6<sup>th</sup> edition. Future delays and Level of Service were determined for the intersections using the HCS Streets (version 7.5) software. The delays and Level of Service are summarized in **Table 2**.

**Table 2. Peak Hour Level of Service**

| Approach                                   | A.M.                    |                         |                         | P.M.                    |                         |                         |
|--|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
|  | 2018 Existing           | 2030 No Build           | 2030 Build              | 2018 Existing           | 2030 No Build           | 2030 Build              |
| <b>Taylorsville Road at Stone Lakes Dr</b> | <b>C</b><br><b>28.7</b> | <b>E</b><br><b>68.7</b> | <b>E</b><br><b>73.3</b> | <b>C</b><br><b>26.5</b> | <b>C</b><br><b>33.6</b> | <b>D</b><br><b>35.8</b> |
| Taylorsville Road Eastbound                | C<br>20.2               | E<br>57.3               | E<br>56.6               | C<br>21.3               | C<br>24.4               | C<br>25.8               |
| Taylorsville Road Westbound                | C<br>23.9               | E<br>73.9               | F<br>85.5               | B<br>19.7               | B<br>16.6               | B<br>17.1               |
| Stone Lakes Drive Northbound               | D<br>38.7               | F<br>124.3              | F<br>124.3              | C<br>33.7               | E<br>62.5               | E<br>62.5               |
| Stone Lakes Drive Southbound               | D<br>48.8               | E<br>56.9               | E<br>57.1               | D<br>51.3               | E<br>67.9               | E<br>74.8               |
| <b>Taylorsville Road at I 265 SB ramps</b> | <b>B</b><br><b>19.3</b> | <b>C</b><br><b>29.1</b> | <b>C</b><br><b>29.6</b> | <b>C</b><br><b>23.3</b> | <b>D</b><br><b>38.1</b> | <b>D</b><br><b>44.2</b> |
| Taylorsville Road Eastbound                | A<br>7.8                | B<br>19.2               | C<br>20.2               | B<br>12.6               | C<br>23.1               | C<br>33.3               |
| Taylorsville Road Westbound                | B<br>16.9               | C<br>22.9               | C<br>23.6               | C<br>20.4               | C<br>33.7               | D<br>41.6               |
| I 265 Ramp Southbound                      | D<br>52.5               | E<br>63.9               | E<br>61.9               | D<br>42.0               | E<br>63.3               | E<br>61.3               |
| <b>Taylorsville Road at I 265 NB ramps</b> | <b>C</b><br><b>21.3</b> | <b>D</b><br><b>48.6</b> | <b>E</b><br><b>56.4</b> | <b>B</b><br><b>13.4</b> | <b>C</b><br><b>24.4</b> | <b>C</b><br><b>23.7</b> |
| Taylorsville Road Eastbound                | B<br>19.9               | E<br>64.2               | E<br>69.4               | B<br>11.3               | C<br>23.5               | C<br>27.8               |
| Taylorsville Road Westbound                | B<br>12.5               | C<br>29.3               | D<br>44.4               | A<br>6.1                | B<br>16.0               | B<br>15.4               |
| I 265 Ramp Northbound                      | D<br>40.6               | E<br>68.6               | E<br>67.2               | C<br>28.6               | C<br>29.0               | C<br>22.7               |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| Approach   | A.M.                    |                         |                          | P.M.                    |                         |                          |
|--|-------------------------|-------------------------|--------------------------|-------------------------|-------------------------|--------------------------|
|  | 2018 Existing           | 2030 No Build           | 2030 Build               | 2018 Existing           | 2030 No Build           | 2030 Build               |
| <b>Taylorsville Road at S Pope Lick Road</b>       |                         | <b>D</b><br><b>51.6</b> | <b>F</b><br><b>101.9</b> |                         | <b>D</b><br><b>51.4</b> | <b>F</b><br><b>105.9</b> |
| Taylorsville Road Eastbound                        | B<br>14.9               | C<br>25.0               | C<br>23.1                | A<br>9.1                | E<br>67.4               | F<br>155.4               |
| Taylorsville Road Westbound                        | A<br>8.3                | D<br>52.9               | F<br>129.0               | B<br>12.1               | B<br>10.0               | B<br>11.7                |
| S Pope Lick Road Northbound                        | F<br>63.4               | E<br>66.4               | E<br>66.4                | F<br>179.9              | E<br>71.4               | E<br>71.4                |
| S Pope Lick Road Southbound                        | F<br>54.8               | F<br>127.5              | F<br>125.6               | F<br>250.1              | F<br>85.0               | F<br>88.0                |
| <b>Taylorsville Road at Taylorsville Lake Road</b> | <b>C</b><br><b>32.4</b> | <b>E</b><br><b>56.9</b> | <b>F</b><br><b>121.6</b> | <b>C</b><br><b>24.7</b> | <b>D</b><br><b>39.8</b> | <b>F</b><br><b>87.1</b>  |
| Taylorsville Road (KY 148) Westbound               | B<br>18.4               | D<br>49.7               | D<br>49.8                | C<br>20.5               | E<br>58.8               | E<br>68.8                |
| Taylorsville Lake Road Northbound                  | C<br>31.9               | E<br>64.6               | F<br>162.2               | B<br>18.8               | C<br>21.6               | C<br>25.7                |
| Taylorsville Road Southbound                       | D<br>53.1               | D<br>36.6               | C<br>30.4                | D<br>37.3               | D<br>37.0               | F<br>121.5               |
| <b>Taylorsville Road at Entrance</b>               |                         |                         |                          |                         |                         |                          |
| Entrance Westbound                                 |                         |                         | F<br>271.9               |                         |                         | C<br>17.2                |
| Taylorsville Lake Road Southbound                  |                         |                         | B<br>13.8                |                         |                         | A<br>9.9                 |
| <b>Taylorsville Road at Routt Road</b>             |                         |                         | <b>F</b><br><b>83.5</b>  |                         |                         | <b>D</b><br><b>39.0</b>  |
| Routt Road Eastbound                               | F<br>505.9              | F<br>898.3              | E<br>56.3                | F<br>119.0              | F<br>282.0              | D<br>41.5                |
| Entrance Westbound                                 |                         |                         | E<br>72.9                |                         |                         | E<br>57.1                |
| Taylorsville Road Northbound (left)                | A<br>7.7                | A<br>7.8                | F<br>112.6               | B<br>12.6               | B<br>14.0               | B<br>13.9                |
| Taylorsville Road Southbound (left)                |                         |                         | B<br>17.9                |                         |                         | D<br>44.2                |

Key: Level of Service, Delay in seconds per vehicle

Both entrances were evaluated for turn lanes using the Kentucky Transportation Cabinet Highway Design Guidance Manual dated March, 2017. Using the volumes in Figure 6, a left turn lane will be required at both entrances. Due to the poor operating conditions at Routt Road a traffic signal has been assumed to be installed at the intersection of Routt Road. This intersection will need to be monitored to determine when the signal warrant is satisfied.

## **CONCLUSIONS**

Based upon the volume of traffic generated by the development and the amount of traffic forecasted for the year 2030, there will be an impact to the existing highway network. Left turn lanes will be required at the entrances. The No-Build condition indicates inadequate capacity in the corridor. The Kentucky Transportation Cabinet is currently evaluating several alternates to providing additional capacity in the corridor. One option to achieve acceptable Levels of Service is KY 155 widening to include two lanes in each direction from I 265 (Gene Snyder) through the intersection with Routt Road, with a traffic signal installed at the intersection with Routt Road.

## **APPENDIX**

Traffic Counts

**Louisville Metro Government**  
 Department of Public Works  
 Traffic Engineering & Operations

File Name : Taylorsville Rd & Stone Lakes Dr  
 Site Code :  
 Start Date : 1/19/2016  
 Page No : 3

| Start Time   | Stone Lakes Dr<br>From North |      |      |         |            | Taylorsville Rd<br>From East |      |      |         |            | Stone Lakes Dr<br>From South |      |      |         |            | Taylorsville Rd<br>From West |      |      |         |            | Int. Total |
|--|------------------------------|------|------|---------|------------|------------------------------|------|------|---------|------------|------------------------------|------|------|---------|------------|------------------------------|------|------|---------|------------|------------|
|  | Right                        | Thru | Left | U-Turns | App. Total | Right                        | Thru | Left | U-Turns | App. Total | Right                        | Thru | Left | U-Turns | App. Total | Right                        | Thru | Left | U-Turns | App. Total |            |
| Peak Hour Analysis From 07:00 AM to 09:45 AM - Peak 1 of 1 |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |            |
| Peak Hour for Entire Intersection Begins at 07:00 AM       |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |            |
| 07:00 AM   | 10                           | 1    | 41   | 0       | 52         | 60                           | 159  | 5    | 0       | 224        | 25                           | 4    | 25   | 0       | 54         | 1                            | 117  | 20   | 0       | 138        | 468        |
| 07:15 AM   | 46                           | 6    | 47   | 0       | 99         | 90                           | 151  | 2    | 0       | 243        | 14                           | 11   | 14   | 0       | 39         | 2                            | 90   | 59   | 0       | 151        | 532        |
| 07:30 AM   | 68                           | 9    | 54   | 0       | 131        | 122                          | 175  | 7    | 0       | 304        | 16                           | 38   | 12   | 0       | 66         | 9                            | 144  | 77   | 0       | 230        | 731        |
| 07:45 AM   | 60                           | 10   | 64   | 0       | 134        | 61                           | 201  | 1    | 0       | 263        | 12                           | 8    | 18   | 0       | 38         | 1                            | 123  | 22   | 0       | 146        | 581        |
| Total Volume   | 184                          | 26   | 206  | 0       | 416        | 333                          | 686  | 15   | 0       | 1034       | 67                           | 61   | 69   | 0       | 197        | 13                           | 474  | 178  | 0       | 665        | 2312       |
| % App. Total   | 44.2                         | 6.2  | 49.5 | 0       |            | 32.2                         | 66.3 | 1.5  | 0       |            | 34                           | 31   | 35   | 0       |            | 2                            | 71.3 | 26.8 | 0       |            |            |
| PHF  | .676                         | .650 | .805 | .000    | .776       | .682                         | .853 | .536 | .000    | .850       | .670                         | .401 | .690 | .000    | .746       | .361                         | .823 | .578 | .000    | .723       | .791       |
| Peak Hour Analysis From 10:00 AM to 01:45 PM - Peak 1 of 1 |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |            |
| Peak Hour for Entire Intersection Begins at 01:00 PM       |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |            |
| 01:00 PM   | 5                            | 2    | 45   | 0       | 52         | 49                           | 107  | 6    | 0       | 162        | 7                            | 2    | 6    | 0       | 15         | 5                            | 86   | 4    | 0       | 95         | 324        |
| 01:15 PM   | 5                            | 1    | 48   | 0       | 54         | 43                           | 93   | 5    | 0       | 141        | 5                            | 3    | 2    | 0       | 10         | 3                            | 85   | 6    | 0       | 94         | 299        |
| 01:30 PM   | 6                            | 3    | 52   | 0       | 61         | 58                           | 85   | 4    | 0       | 147        | 8                            | 2    | 4    | 0       | 14         | 6                            | 88   | 7    | 0       | 101        | 323        |
| 01:45 PM   | 10                           | 0    | 45   | 0       | 55         | 49                           | 98   | 6    | 0       | 153        | 7                            | 2    | 6    | 0       | 15         | 3                            | 130  | 12   | 0       | 145        | 368        |
| Total Volume   | 26                           | 6    | 190  | 0       | 222        | 199                          | 383  | 21   | 0       | 603        | 27                           | 9    | 18   | 0       | 54         | 17                           | 389  | 29   | 0       | 435        | 1314       |
| % App. Total   | 11.7                         | 2.7  | 85.6 | 0       |            | 33                           | 63.5 | 3.5  | 0       |            | 50                           | 16.7 | 33.3 | 0       |            | 3.9                          | 89.4 | 6.7  | 0       |            |            |
| PHF  | .650                         | .500 | .913 | .000    | .910       | .858                         | .895 | .875 | .000    | .931       | .844                         | .750 | .750 | .000    | .900       | .708                         | .748 | .604 | .000    | .750       | .893       |
| Peak Hour Analysis From 02:00 PM to 06:45 PM - Peak 1 of 1 |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |            |
| Peak Hour for Entire Intersection Begins at 04:30 PM       |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |                              |      |      |         |            |            |
| 04:30 PM   | 17                           | 8    | 91   | 0       | 116        | 77                           | 150  | 11   | 0       | 238        | 6                            | 1    | 11   | 0       | 18         | 8                            | 242  | 10   | 0       | 260        | 632        |
| 04:45 PM   | 23                           | 9    | 85   | 0       | 117        | 83                           | 137  | 6    | 0       | 226        | 9                            | 4    | 12   | 0       | 25         | 5                            | 248  | 13   | 0       | 266        | 634        |
| 05:00 PM   | 22                           | 8    | 94   | 0       | 124        | 67                           | 149  | 6    | 0       | 222        | 3                            | 5    | 7    | 0       | 15         | 15                           | 282  | 10   | 0       | 307        | 668        |
| 05:15 PM   | 16                           | 5    | 82   | 0       | 103        | 81                           | 130  | 8    | 0       | 219        | 8                            | 10   | 7    | 0       | 25         | 11                           | 292  | 8    | 0       | 311        | 658        |
| Total Volume   | 78                           | 30   | 352  | 0       | 460        | 308                          | 566  | 31   | 0       | 905        | 26                           | 20   | 37   | 0       | 83         | 39                           | 1064 | 41   | 0       | 1144       | 2592       |
| % App. Total   | 17                           | 6.5  | 76.5 | 0       |            | 34                           | 62.5 | 3.4  | 0       |            | 31.3                         | 24.1 | 44.6 | 0       |            | 3.4                          | 93   | 3.6  | 0       |            |            |
| PHF  | .848                         | .833 | .936 | .000    | .927       | .928                         | .943 | .705 | .000    | .951       | .722                         | .500 | .771 | .000    | .830       | .650                         | .911 | .788 | .000    | .920       | .970       |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

8/22/2017

Taylorsville Road at I 265 Interchange All Movements

| Start Time     | KY 155 Westbound |            | I265 Off Ramp Northbound |            | KY 155 Eastbound |             |          | I265 SB Off Ramp Southbound |            | KY 155 Westbound |            | KY 155 Eastbound |            | Interchange |
|----------------|------------------|------------|--------------------------|------------|------------------|-------------|----------|-----------------------------|------------|------------------|------------|------------------|------------|-------------|
|                | Thru             | Right      | Left                     | Right      | Left             | Thru        | U-Turn   | Left                        | Right      | Left             | Thru       | Thru             | Right      |             |
| 6:45:00        | 167              | 176        | 107                      | 38         | 108              | 62          | 1        | 32                          | 44         | 67               | 203        | 139              | 56         | 759         |
| 7:00:00        | 154              | 180        | 114                      | 41         | 108              | 63          | 0        | 25                          | 56         | 64               | 212        | 143              | 53         | 766         |
| 7:15:00        | 192              | 158        | 111                      | 55         | 86               | 76          | 1        | 40                          | 59         | 76               | 225        | 120              | 78         | 813         |
| 7:30:00        | 172              | 150        | 118                      | 55         | 106              | 85          | 0        | 33                          | 75         | 48               | 246        | 166              | 69         | 838         |
| 7:45:00        | 177              | 137        | 107                      | 55         | 90               | 93          | 0        | 54                          | 53         | 62               | 203        | 121              | 63         | 767         |
| 8:00:00        | 152              | 114        | 88                       | 46         | 80               | 62          | 0        | 29                          | 65         | 62               | 195        | 115              | 58         | 667         |
| 8:15:00        | 176              | 132        | 105                      | 42         | 78               | 81          | 0        | 47                          | 54         | 63               | 213        | 115              | 62         | 733         |
| 8:30:00        | 113              | 135        | 85                       | 32         | 82               | 77          | 0        | 48                          | 56         | 45               | 162        | 110              | 61         | 640         |
| 8:45:00        | 117              | 121        | 67                       | 28         | 83               | 82          | 0        | 35                          | 50         | 43               | 140        | 122              | 48         | 588         |
| 16:00:00       | 80               | 52         | 53                       | 45         | 58               | 267         | 0        | 147                         | 117        | 34               | 96         | 174              | 106        | 774         |
| 16:15:00       | 79               | 57         | 57                       | 50         | 69               | 265         | 0        | 132                         | 119        | 34               | 118        | 202              | 116        | 812         |
| 16:30:00       | 104              | 69         | 69                       | 45         | 70               | 234         | 0        | 130                         | 98         | 46               | 127        | 175              | 107        | 797         |
| 16:45:00       | 96               | 52         | 69                       | 80         | 68               | 256         | 1        | 102                         | 76         | 46               | 116        | 217              | 127        | 819         |
| 17:00:00       | 113              | 58         | 50                       | 78         | 64               | 230         | 0        | 75                          | 67         | 51               | 111        | 213              | 110        | 764         |
| 17:15:00       | 113              | 56         | 79                       | 72         | 57               | 208         | 0        | 82                          | 66         | 54               | 141        | 179              | 129        | 776         |
| 17:30:00       | 95               | 42         | 90                       | 74         | 47               | 203         | 0        | 72                          | 87         | 30               | 156        | 182              | 111        | 753         |
| 17:45:00       | 66               | 44         | 56                       | 62         | 42               | 229         | 0        | 93                          | 88         | 27               | 102        | 168              | 109        | 686         |
| 7:00:00        | 154              | 180        | 114                      | 41         | 108              | 63          | 0        | 25                          | 56         | 64               | 212        | 143              | 53         | 766         |
| 7:15:00        | 192              | 158        | 111                      | 55         | 86               | 76          | 1        | 40                          | 59         | 76               | 225        | 120              | 78         | 813         |
| 7:30:00        | 172              | 150        | 118                      | 55         | 106              | 85          | 0        | 33                          | 75         | 48               | 246        | 166              | 69         | 838         |
| 7:45:00        | 177              | 137        | 107                      | 55         | 90               | 93          | 0        | 54                          | 53         | 62               | 203        | 121              | 63         | 767         |
| <b>AM Peak</b> | <b>695</b>       | <b>625</b> | <b>450</b>               | <b>206</b> | <b>390</b>       | <b>317</b>  | <b>1</b> | <b>152</b>                  | <b>243</b> | <b>250</b>       | <b>886</b> | <b>550</b>       | <b>263</b> | <b>3184</b> |
| 16:00:00       | 80               | 52         | 53                       | 45         | 58               | 267         | 0        | 147                         | 117        | 34               | 96         | 174              | 106        | 774         |
| 16:15:00       | 79               | 57         | 57                       | 50         | 69               | 265         | 0        | 132                         | 119        | 34               | 118        | 202              | 116        | 812         |
| 16:30:00       | 104              | 69         | 69                       | 45         | 70               | 234         | 0        | 130                         | 98         | 46               | 127        | 175              | 107        | 797         |
| 16:45:00       | 96               | 52         | 69                       | 80         | 68               | 256         | 1        | 102                         | 76         | 46               | 116        | 217              | 127        | 819         |
| <b>PM Peak</b> | <b>359</b>       | <b>230</b> | <b>248</b>               | <b>220</b> | <b>265</b>       | <b>1022</b> | <b>1</b> | <b>511</b>                  | <b>410</b> | <b>160</b>       | <b>457</b> | <b>768</b>       | <b>456</b> | <b>3202</b> |

**Study Name**    **KY 155 at Pope Lick Road**  
**Start Date**    **09/06/2017**  
**Start Time**    **12:00 AM**  
**Site Code**      **Pope Lick Road**  
**Project**        **5-808.00 KY 155 @ Pope Lick Road**

**Type**            **Road**  
**Classification** **Totals**

| Start Time | Pope Lick Road Southbound |      |       | KY 155 Westbound |      |       | Pope Lick Road Northbound |      |       | KY 155 Eastbound |      |       | Total |
|------------|---------------------------|------|-------|------------------|------|-------|---------------------------|------|-------|------------------|------|-------|-------|
|            | Left                      | Thru | Right | Left             | Thru | Right | Left                      | Thru | Right | Left             | Thru | Right |       |
| 7:00 AM    | 2                         | 0    | 10    | 0                | 314  | 36    | 3                         | 0    | 1     | 8                | 61   | 9     | 444   |
| 7:15 AM    | 2                         | 0    | 6     | 0                | 301  | 48    | 0                         | 0    | 0     | 24               | 100  | 11    | 492   |
| 7:30 AM    | 0                         | 0    | 6     | 0                | 301  | 69    | 0                         | 1    | 4     | 20               | 106  | 8     | 515   |
| 7:45 AM    | 2                         | 0    | 16    | 0                | 274  | 74    | 1                         | 0    | 1     | 24               | 93   | 14    | 499   |
| 8:00 AM    | 1                         | 0    | 6     | 1                | 282  | 51    | 2                         | 0    | 1     | 15               | 83   | 9     | 451   |
| 8:15 AM    | 1                         | 1    | 5     | 0                | 222  | 46    | 2                         | 1    | 0     | 1                | 79   | 12    | 370   |
| 8:30 AM    | 2                         | 0    | 0     | 1                | 233  | 41    | 5                         | 2    | 0     | 7                | 87   | 8     | 386   |
| 8:45 AM    | 4                         | 1    | 2     | 1                | 203  | 31    | 6                         | 1    | 1     | 3                | 116  | 22    | 391   |
| 4:00 PM    | 7                         | 1    | 12    | 2                | 139  | 9     | 5                         | 1    | 1     | 5                | 277  | 21    | 480   |
| 4:15 PM    | 7                         | 2    | 8     | 0                | 125  | 3     | 4                         | 0    | 3     | 7                | 302  | 18    | 479   |
| 4:30 PM    | 4                         | 2    | 13    | 1                | 182  | 7     | 2                         | 0    | 2     | 4                | 308  | 11    | 536   |
| 4:45 PM    | 17                        | 0    | 12    | 0                | 143  | 3     | 7                         | 0    | 2     | 5                | 294  | 20    | 503   |
| 5:00 PM    | 10                        | 1    | 12    | 0                | 164  | 10    | 3                         | 0    | 1     | 0                | 286  | 18    | 505   |
| 5:15 PM    | 9                         | 0    | 11    | 1                | 181  | 9     | 7                         | 0    | 1     | 4                | 304  | 23    | 550   |
| 5:30 PM    | 9                         | 1    | 9     | 0                | 171  | 9     | 5                         | 2    | 3     | 6                | 288  | 31    | 534   |
| 5:45 PM    | 8                         | 1    | 7     | 3                | 137  | 7     | 4                         | 0    | 2     | 3                | 293  | 47    | 512   |
| 7:15 AM    | 2                         | 0    | 6     | 0                | 301  | 48    | 0                         | 0    | 0     | 24               | 100  | 11    | 492   |
| 7:30 AM    | 0                         | 0    | 6     | 0                | 301  | 69    | 0                         | 1    | 4     | 20               | 106  | 8     | 515   |
| 7:45 AM    | 2                         | 0    | 16    | 0                | 274  | 74    | 1                         | 0    | 1     | 24               | 93   | 14    | 499   |
| 8:00 AM    | 1                         | 0    | 6     | 1                | 282  | 51    | 2                         | 0    | 1     | 15               | 83   | 9     | 451   |
| AM Peak    | 5                         | 0    | 34    | 1                | 1158 | 242   | 3                         | 1    | 6     | 83               | 382  | 42    | 1957  |
| 5:00 PM    | 10                        | 1    | 12    | 0                | 164  | 10    | 3                         | 0    | 1     | 0                | 286  | 18    | 505   |
| 5:15 PM    | 9                         | 0    | 11    | 1                | 181  | 9     | 7                         | 0    | 1     | 4                | 304  | 23    | 550   |
| 5:30 PM    | 9                         | 1    | 9     | 0                | 171  | 9     | 5                         | 2    | 3     | 6                | 288  | 31    | 534   |
| 5:45 PM    | 8                         | 1    | 7     | 3                | 137  | 7     | 4                         | 0    | 2     | 3                | 293  | 47    | 512   |
| PM Peak    | 36                        | 3    | 39    | 4                | 653  | 35    | 19                        | 2    | 7     | 13               | 1171 | 119   | 2101  |



Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study




11.16.16 pm  
 11.22.16 am

| Interval<br>Start Time | <i>Taylorsville Lake Road</i> |             |            |      | <i>Taylorsville Road</i> |      |            |      | <i>Taylorsville Road</i> |             |       |      | Total |
|------------------------|-------------------------------|-------------|------------|------|--------------------------|------|------------|------|--------------------------|-------------|-------|------|-------|
|                        | From South                    |             |            |      | From East                |      |            |      | From West                |             |       |      |       |
|                        | Left                          | Thru        | Right      | Peds | Left                     | Thru | Right      | Peds | Left                     | Thru        | Right | Peds |       |
| 7:00                   |                               | 286         | 12         |      | 5                        |      | 57         |      | 30                       | 41          |       |      | 431   |
| 7:15                   |                               | 287         | 9          |      | 3                        |      | 65         |      | 36                       | 42          |       |      | 442   |
| 7:30                   |                               | 267         | 15         |      | 3                        |      | 58         |      | 19                       | 32          |       |      | 394   |
| 7:45                   |                               | 256         | 16         |      | 6                        |      | 57         |      | 45                       | 46          |       |      | 426   |
| 8:00                   |                               | 252         | 12         |      | 9                        |      | 50         |      | 45                       | 65          |       |      | 433   |
| 8:15                   |                               | 242         | 17         |      | 4                        |      | 47         |      | 34                       | 44          |       |      | 388   |
| 8:30                   |                               | 210         | 14         |      | 5                        |      | 43         |      | 25                       | 43          |       |      | 340   |
| 8:45                   |                               | 186         | 11         |      | 5                        |      | 45         |      | 29                       | 46          |       |      | 322   |
| <b>AM TOTALS</b>       |                               | <b>1986</b> | <b>106</b> |      | <b>40</b>                |      | <b>422</b> |      | <b>263</b>               | <b>359</b>  |       |      | 3176  |
| 16:00                  |                               | 97          | 8          |      | 22                       |      | 41         |      | 57                       | 218         |       |      | 443   |
| 16:15                  |                               | 98          | 8          |      | 31                       |      | 44         |      | 54                       | 233         |       |      | 468   |
| 16:30                  |                               | 118         | 8          |      | 29                       |      | 58         |      | 43                       | 251         |       |      | 507   |
| 16:45                  |                               | 112         | 7          |      | 96                       |      | 67         |      | 49                       | 225         |       |      | 556   |
| 17:00                  |                               | 116         | 8          |      | 91                       |      | 79         |      | 57                       | 270         |       |      | 621   |
| 17:15                  |                               | 103         | 8          |      | 79                       |      | 55         |      | 61                       | 256         |       |      | 562   |
| 17:30                  |                               | 112         | 8          |      | 103                      |      | 62         |      | 48                       | 253         |       |      | 586   |
| 17:45                  |                               | 133         | 11         |      | 65                       |      | 38         |      | 36                       | 211         |       |      | 494   |
| <b>PM TOTALS</b>       |                               | <b>889</b>  | <b>66</b>  |      | <b>516</b>               |      | <b>444</b> |      | <b>405</b>               | <b>1917</b> |       |      | 4237  |
| 7:15                   |                               | 287         | 9          |      | 3                        |      | 65         |      | 36                       | 42          |       |      | 442   |
| 7:30                   |                               | 267         | 15         |      | 3                        |      | 58         |      | 19                       | 32          |       |      | 394   |
| 7:45                   |                               | 256         | 16         |      | 6                        |      | 57         |      | 45                       | 46          |       |      | 426   |
| 8:00                   |                               | 252         | 12         |      | 9                        |      | 50         |      | 45                       | 65          |       |      | 433   |
| <b>AM PEAK</b>         |                               | <b>1062</b> | <b>52</b>  |      | <b>21</b>                |      | <b>230</b> |      | <b>145</b>               | <b>185</b>  |       |      | 1695  |
| 16:45                  |                               | 112         | 7          |      | 96                       |      | 67         |      | 49                       | 225         |       |      | 556   |
| 17:00                  |                               | 116         | 8          |      | 91                       |      | 79         |      | 57                       | 270         |       |      | 621   |
| 17:15                  |                               | 103         | 8          |      | 79                       |      | 55         |      | 61                       | 256         |       |      | 562   |
| 17:30                  |                               | 112         | 8          |      | 103                      |      | 62         |      | 48                       | 253         |       |      | 586   |
| <b>PM PEAK</b>         |                               | <b>443</b>  | <b>31</b>  |      | <b>369</b>               |      | <b>263</b> |      | <b>215</b>               | <b>1004</b> |       |      | 2325  |


2/14/2018

| Interval<br>Start Time | <i>Taylorsville Lake Rd</i> |             |            | <i>Taylorsville Lake Rd</i> |             |       | <i>Routt Rd</i> |      |          | Total |
|------------------------|-----------------------------|-------------|------------|-----------------------------|-------------|-------|-----------------|------|----------|-------|
|                        | From North                  |             |            | From South                  |             |       | From West       |      |          |       |
|                        | Left                        | Thru        | Right      | Left                        | Thru        | Right | Left            | Thru | Right    |       |
| 7:00                   |                             | 27          | 2          | 1                           | 220         |       | 52              |      | 0        | 302   |
| 7:15                   |                             | 40          | 4          | 0                           | 243         |       | 84              |      | 0        | 371   |
| 7:30                   |                             | 55          | 6          | 1                           | 290         |       | 77              |      | 0        | 429   |
| 7:45                   |                             | 49          | 7          | 1                           | 239         |       | 70              |      | 2        | 368   |
| 8:00                   |                             | 53          | 9          | 0                           | 214         |       | 60              |      | 0        | 336   |
| 8:15                   |                             | 59          | 10         | 0                           | 237         |       | 55              |      | 1        | 362   |
| 8:30                   |                             | 52          | 12         | 0                           | 188         |       | 44              |      | 0        | 296   |
| 8:45                   |                             | 57          | 8          | 1                           | 166         |       | 37              |      | 0        | 269   |
| <b>AM TOTALS</b>       |                             | <b>392</b>  | <b>58</b>  | <b>4</b>                    | <b>1797</b> |       | <b>479</b>      |      | <b>3</b> | 2733  |
| 16:00                  |                             | 172         | 45         | 1                           | 53          |       | 19              |      | 0        | 290   |
| 16:15                  |                             | 215         | 76         | 0                           | 73          |       | 22              |      | 2        | 388   |
| 16:30                  |                             | 272         | 67         | 0                           | 111         |       | 34              |      | 1        | 485   |
| 16:45                  |                             | 232         | 68         | 2                           | 92          |       | 9               |      | 1        | 404   |
| 17:00                  |                             | 245         | 63         | 0                           | 77          |       | 21              |      | 0        | 406   |
| 17:15                  |                             | 250         | 66         | 0                           | 85          |       | 34              |      | 0        | 435   |
| 17:30                  |                             | 255         | 78         | 1                           | 92          |       | 21              |      | 1        | 448   |
| 17:45                  |                             | 234         | 75         | 1                           | 54          |       | 24              |      | 0        | 388   |
| <b>PM TOTALS</b>       |                             | <b>1875</b> | <b>538</b> | <b>5</b>                    | <b>637</b>  |       | <b>184</b>      |      | <b>5</b> | 3244  |
| 7:15                   |                             | 40          | 4          | 0                           | 243         |       | 84              |      | 0        | 371   |
| 7:30                   |                             | 55          | 6          | 1                           | 290         |       | 77              |      | 0        | 429   |
| 7:45                   |                             | 49          | 7          | 1                           | 239         |       | 70              |      | 2        | 368   |
| 8:00                   |                             | 53          | 9          | 0                           | 214         |       | 60              |      | 0        | 336   |
| <b>AM PEAK</b>         |                             | <b>197</b>  | <b>26</b>  | <b>2</b>                    | <b>986</b>  |       | <b>291</b>      |      | <b>2</b> | 1504  |
| 16:30                  |                             | 272         | 67         | 0                           | 111         |       | 34              |      | 1        | 485   |
| 16:45                  |                             | 232         | 68         | 2                           | 92          |       | 9               |      | 1        | 404   |
| 17:00                  |                             | 245         | 63         | 0                           | 77          |       | 21              |      | 0        | 406   |
| 17:15                  |                             | 250         | 66         | 0                           | 85          |       | 34              |      | 0        | 435   |
| <b>PM PEAK</b>         |                             | <b>999</b>  | <b>264</b> | <b>2</b>                    | <b>365</b>  |       | <b>98</b>       |      | <b>2</b> | 1730  |

HCS Reports


















| HCS7 Signalized Intersection Results Summary    |  |                 |               |  |       |                                 |         |   |     |       |       |   |      |  |  |   |  |  |
|---|--|-----------------|---------------|--|-------|---------------------------------|---------|---|-----|-------|-------|---|------|--|--|---|--|--|
| <b>General Information</b>                      |  |                 |               |  |       | <b>Intersection Information</b> |         |   |     |       |       |  |      |  |  |   |  |  |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |  |       | Duration, h                     | 0.25    |   |     |       |       |   |      |  |  |   |  |  |
| Analyst   | DBZ                                    | Analysis Date   | 3/8/2018      |  |       | Area Type                       | Other   |   |     |       |       |   |      |  |  |   |  |  |
| Jurisdiction                                    |  | Time Period     | AM Peak       |  |       | PHF                             | 0.79    |   |     |       |       |   |      |  |  |   |  |  |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2018   |       | Analysis Period                 | 1> 7:00 |   |     |       |       |   |      |  |  |   |  |  |
| Intersection                                    | Stone Lakes Drive                      |                 | File Name     | AM 18.xus  |       |                                 |         |   |     |       |       |   |      |  |  |   |  |  |
| Project Description                             | Covington by the Park                  |                 |               |  |       |                                 |         |   |     |       |       |   |      |  |  |   |  |  |
| <b>Demand Information</b>                       |  |                 |               | EB   |       |                                 | WB      |   |     | NB    |       |   | SB   |  |  |   |  |  |
| Approach Movement                               | L                                      | T               | R             | L  | T     | R                               | L       | T   | R   | L     | T     | R   |      |  |  |   |  |  |
| Demand (v), veh/h                               | 178                                    | 474             | 13            | 15   | 686   | 333                             | 69      | 61  | 67  | 206   | 26    | 184   |      |  |  |   |  |  |
| <b>Signal Information</b>                       |  |                 |               |  |       |                                 |         |  |     |       |       |   |      |  |  |   |  |  |
| Cycle, s  | 120.0                                  | Reference Phase | 2             |  |       |                                 |         |   |     |       |       |   |      |  |  |   |  |  |
| Offset, s                                       | 0                                      | Reference Point | End           |  |       |                                 |         |   |     |       |       |   |      |  |  |   |  |  |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On            |  |       |                                 |         |   |     |       |       |   |      |  |  |   |  |  |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | Off           |  |       |                                 |         |   |     |       |       |   |      |  |  |   |  |  |
|   |  |                 | Green         | 2.6  | 0.8   | 57.8                            | 34.3    | 0.0   | 0.0 |       |       |   |      |  |  |   |  |  |
|   |  |                 | Yellow        | 3.5  | 3.5   | 4.3                             | 3.6     | 0.0   | 0.0 |       |       |   |      |  |  |   |  |  |
|   |  |                 | Red           | 3.0  | 3.0   | 1.5                             | 2.1     | 0.0   | 0.0 |       |       |   |      |  |  |   |  |  |
| <b>Timer Results</b>                            |  |                 |               | EBL  | EBT   | WBL                             | WBT     | NBL   | NBT | SBL   | SBT   |   |      |  |  |   |  |  |
| Assigned Phase                                  | 5                                      |                 |               | 2  |       |                                 | 1       |   |     | 6     |       |   |      |  |  |   |  |  |
| Case Number                                     | 1.1                                    |                 |               | 4.0  |       |                                 | 1.1     |   |     | 3.0   |       |   |      |  |  |   |  |  |
| Phase Duration, s                               | 16.4                                   |                 |               | 70.9   |       |                                 | 9.1     |   |     | 63.6  |       |   |      |  |  |   |  |  |
| Change Period, (Y+R <sub>c</sub> ), s           | 6.5                                    |                 |               | 5.8  |       |                                 | 6.5     |   |     | 5.8   |       |   |      |  |  |   |  |  |
| Max Allow Headway (MAH), s                      | 5.0                                    |                 |               | 0.0  |       |                                 | 5.0     |   |     | 0.0   |       |   |      |  |  |   |  |  |
| Queue Clearance Time (g <sub>s</sub> ), s       | 9.2                                    |                 |               |  |       |                                 | 2.6     |   |     |       |       |   |      |  |  |   |  |  |
| Green Extension Time (g <sub>e</sub> ), s       | 0.7                                    |                 |               | 0.0  |       |                                 | 0.0     |   |     | 0.0   |       |   |      |  |  |   |  |  |
| Phase Call Probability                          | 1.00                                   |                 |               |  |       |                                 | 0.44    |   |     |       |       |   |      |  |  |   |  |  |
| Max Out Probability                             | 0.12                                   |                 |               |  |       |                                 | 0.00    |   |     |       |       |   |      |  |  |   |  |  |
| <b>Movement Group Results</b>                   |  |                 |               | EB   |       |                                 | WB      |   |     | NB    |       |   | SB   |  |  |   |  |  |
| Approach Movement                               | L                                      | T               | R             | L  | T     | R                               | L       | T   | R   | L     | T     | R   |      |  |  |   |  |  |
| Assigned Movement                               | 5                                      | 2               | 12            | 1  | 6     | 16                              | 3       | 8   | 18  | 7     | 4     | 14  |      |  |  |   |  |  |
| Adjusted Flow Rate (v), veh/h                   | 225                                    | 310             | 307           | 17   | 793   | 385                             | 87      | 162   |     | 261   | 266   |   |      |  |  |   |  |  |
| Adjusted Saturation Flow Rate (s), veh/h/ln     | 1795                                   | 1856            | 1838          | 1795   | 1841  | 1598                            | 1131    | 1696  |     | 1234  | 1628  |   |      |  |  |   |  |  |
| Queue Service Time (g <sub>s</sub> ), s         | 7.2                                    | 11.0            | 11.0          | 0.6  | 43.8  | 8.6                             | 8.5     | 9.0   |     | 25.1  | 16.7  |   |      |  |  |   |  |  |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s | 7.2                                    | 11.0            | 11.0          | 0.6  | 43.8  | 8.6                             | 25.2    | 9.0   |     | 34.1  | 16.7  |   |      |  |  |   |  |  |
| Green Ratio (g/C)                               | 0.58                                   | 0.54            | 0.54          | 0.50   | 0.48  | 0.48                            | 0.29    | 0.29  |     | 0.29  | 0.29  |   |      |  |  |   |  |  |
| Capacity (c), veh/h                             | 289                                    | 1006            | 996           | 452  | 886   | 769                             | 235     | 485   |     | 330   | 465   |   |      |  |  |   |  |  |
| Volume-to-Capacity Ratio (X)                    | 0.780                                  | 0.308           | 0.308         | 0.038  | 0.896 | 0.501                           | 0.371   | 0.334   |     | 0.789 | 0.571 |   |      |  |  |   |  |  |
| Back of Queue (Q), ft/ln (90 th percentile)     | 149.8                                  | 186.8           | 181.6         | 10.6   | 560.2 | 107.1                           | 109     | 157.1   |     | 310.8 | 252.5 |   |      |  |  |   |  |  |
| Back of Queue (Q), veh/ln (90 th percentile)    | 5.9                                    | 7.3             | 7.3           | 0.4  | 21.7  | 4.3                             | 4.4     | 6.1   |     | 12.3  | 10.0  |   |      |  |  |   |  |  |
| Queue Storage Ratio (RQ) (90 th percentile)     | 0.86                                   | 0.37            | 0.37          | 0.06   | 0.56  | 0.21                            | 0.56    | 0.79  |     | 0.89  | 0.72  |   |      |  |  |   |  |  |
| Uniform Delay (d <sub>1</sub> ), s/veh          | 24.5                                   | 15.1            | 15.1          | 15.2   | 19.3  | 6.2                             | 46.4    | 33.3  |     | 46.4  | 36.6  |   |      |  |  |   |  |  |
| Incremental Delay (d <sub>2</sub> ), s/veh      | 7.5                                    | 0.8             | 0.8           | 0.0  | 12.3  | 2.1                             | 1.4     | 0.6   |     | 12.7  | 2.1   |   |      |  |  |   |  |  |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    | 0.0                                    | 0.0             | 0.0           | 0.0  | 0.0   | 0.0                             | 0.0     | 0.0   |     | 0.0   | 0.0   |   |      |  |  |   |  |  |
| Control Delay (d), s/veh                        | 31.9                                   | 15.9            | 15.9          | 15.3   | 31.6  | 8.3                             | 47.8    | 33.8  |     | 59.1  | 38.6  |   |      |  |  |   |  |  |
| Level of Service (LOS)                          | C                                      | B               | B             | B  | C     | A                               | D       | C   |     | E     | D     |   |      |  |  |   |  |  |
| Approach Delay, s/veh / LOS                     | 20.2                                   |                 | C             | 23.9   |       | C                               | 38.7    |   | D   | 48.8  |       | D   |      |  |  |   |  |  |
| Intersection Delay, s/veh / LOS                 | 28.7                                   |                 |               |  |       |                                 | C       |   |     |       |       |   |      |  |  |   |  |  |
| <b>Multimodal Results</b>                       |  |                 |               | EB   |       |                                 | WB      |   |     | NB    |       |   | SB   |  |  |   |  |  |
| Pedestrian LOS Score / LOS                      | 1.90                                   |                 |               | B  |       |                                 | 1.91    |   |     | B     |       |   | 2.13 |  |  | B |  |  |
| Bicycle LOS Score / LOS                         | 1.18                                   |                 |               | A  |       |                                 | 2.65    |   |     | C     |       |   | 0.90 |  |  | A |  |  |

### HCS7 Signalized Intersection Results Summary

| General Information                                    |  |                 |     | Intersection Information |               |       |       |  |       |       |       |         |       |       |     |
|--|--|-----------------|-----|--------------------------|---------------|-------|-------|---|-------|-------|-------|---------|-------|-------|-----|
| Agency   | Diane B. Zimmerman Traffic Engineering |                 |     | Duration, h              | 0.25          |       |       |   |       |       |       |         |       |       |     |
| Analyst  | DBZ                                    |                 |     | Analysis Date            | 3/8/2018      |       |       |   |       |       |       |         |       |       |     |
| Jurisdiction   |  |                 |     | Area Type                | Other         |       |       |   |       |       |       |         |       |       |     |
| Urban Street   | Taylorsville Road                      |                 |     | Time Period              | AM Peak       |       |       |   |       |       |       |         |       |       |     |
| Intersection   | Stone Lakes Drive                      |                 |     | PHF                      | 0.79          |       |       |   |       |       |       |         |       |       |     |
| Project Description                                    | Covington by the Park                  |                 |     | Analysis Year            | 2030 No Build |       |       |   |       |       |       |         |       |       |     |
|  | File Name                              |                 |     | AM 30 NB.xus             |               |       |       | Analysis Period   |       |       |       | 1> 7:00 |       |       |     |
| Demand Information                                     |  |                 |     | EB                       |               |       | WB    |   |       | NB    |       |         | SB    |       |     |
| Approach Movement                                      |  |                 |     | L                        | T             | R     | L     | T   | R     | L     | T     | R       | L     | T     | R   |
| Demand ( <i>v</i> ), veh/h                             |  |                 |     | 251                      | 534           | 15    | 17    | 773   | 626   | 78    | 73    | 75      | 410   | 32    | 243 |
| Signal Information                                     |  |                 |     |                          |               |       |       |   |       |       |       |         |       |       |     |
| Cycle, s   | 120.0                                  | Reference Phase | 2   |                          |               |       |       |   |       |       |       |         |       |       |     |
| Offset, s  | 0                                      | Reference Point | End |                          |               |       |       |   |       |       |       |         |       |       |     |
| Uncoordinated  | No                                     | Simult. Gap E/W | On  | Green                    | 2.9           | 4.1   | 49.2  | 24.3  | 9.3   | 0.0   |       |         |       |       |     |
| Force Mode   | Fixed                                  | Simult. Gap N/S | Off | Yellow                   | 3.5           | 3.5   | 4.3   | 3.6   | 3.6   | 0.0   |       |         |       |       |     |
|  |  |                 |     | Red                      | 3.0           | 3.0   | 1.5   | 2.1   | 2.1   | 0.0   |       |         |       |       |     |
| Timer Results  |  |                 |     | EBL                      | EBT           | WBL   | WBT   | NBL   | NBT   | SBL   | SBT   |         |       |       |     |
| Assigned Phase   |  |                 |     | 5                        | 2             | 1     | 6     |   | 8     |       | 4     |         |       |       |     |
| Case Number  |  |                 |     | 1.1                      | 4.0           | 1.1   | 3.0   |   | 10.0  |       | 10.0  |         |       |       |     |
| Phase Duration, s                                      |  |                 |     | 20.0                     | 65.6          | 9.4   | 55.0  |   | 15.0  |       | 30.0  |         |       |       |     |
| Change Period, ( <i>Y+R<sub>c</sub></i> ), s           |  |                 |     | 6.5                      | 5.8           | 6.5   | 5.8   |   | 5.7   |       | 5.7   |         |       |       |     |
| Max Allow Headway ( <i>MAH</i> ), s                    |  |                 |     | 5.0                      | 0.0           | 5.0   | 0.0   |   | 5.0   |       | 5.1   |         |       |       |     |
| Queue Clearance Time ( <i>g<sub>s</sub></i> ), s       |  |                 |     | 16.5                     |               | 2.8   |       |   | 12.3  |       | 24.5  |         |       |       |     |
| Green Extension Time ( <i>g<sub>e</sub></i> ), s       |  |                 |     | 0.0                      | 0.0           | 0.0   | 0.0   |   | 0.0   |       | 0.0   |         |       |       |     |
| Phase Call Probability                                 |  |                 |     | 1.00                     |               | 0.48  |       |   | 1.00  |       | 1.00  |         |       |       |     |
| Max Out Probability                                    |  |                 |     | 1.00                     |               | 0.00  |       |   | 1.00  |       | 1.00  |         |       |       |     |
| Movement Group Results                                 |  |                 |     | EB                       |               |       | WB    |   |       | NB    |       |         | SB    |       |     |
| Approach Movement                                      |  |                 |     | L                        | T             | R     | L     | T   | R     | L     | T     | R       | L     | T     | R   |
| Assigned Movement                                      |  |                 |     | 5                        | 2             | 12    | 1     | 6   | 16    | 3     | 8     | 18      | 7     | 4     | 14  |
| Adjusted Flow Rate ( <i>v</i> ), veh/h                 |  |                 |     | 318                      | 349           | 346   | 20    | 890   | 548   | 99    | 149   |         | 519   | 310   |     |
| Adjusted Saturation Flow Rate ( <i>s</i> ), veh/h/ln   |  |                 |     | 1795                     | 1856          | 1837  | 1795  | 1841  | 1598  | 1810  | 1736  |         | 1743  | 1630  |     |
| Queue Service Time ( <i>g<sub>s</sub></i> ), s         |  |                 |     | 14.5                     | 13.9          | 14.0  | 0.8   | 50.2  | 26.5  | 6.3   | 10.3  |         | 16.6  | 22.5  |     |
| Cycle Queue Clearance Time ( <i>g<sub>c</sub></i> ), s |  |                 |     | 14.5                     | 13.9          | 14.0  | 0.8   | 50.2  | 26.5  | 6.3   | 10.3  |         | 16.6  | 22.5  |     |
| Green Ratio ( <i>g/C</i> )                             |  |                 |     | 0.56                     | 0.50          | 0.50  | 0.43  | 0.42  | 0.42  | 0.09  | 0.09  |         | 0.20  | 0.20  |     |
| Capacity ( <i>c</i> ), veh/h                           |  |                 |     | 277                      | 925           | 916   | 379   | 770   | 655   | 155   | 135   |         | 735   | 344   |     |
| Volume-to-Capacity Ratio ( <i>X</i> )                  |  |                 |     | 1.147                    | 0.377         | 0.378 | 0.052 | 1.155   | 0.836 | 0.636 | 1.110 |         | 0.706 | 0.902 |     |
| Back of Queue ( <i>Q</i> ), ft/ln ( 90 th percentile)  |  |                 |     | 418.8                    | 232.4         | 225.3 | 14.1  | 1188.9  | 204.8 | 137.8 | 325.7 |         | 270.5 | 391.8 |     |
| Back of Queue ( <i>Q</i> ), veh/ln ( 90 th percentile) |  |                 |     | 16.6                     | 9.1           | 9.0   | 0.6   | 46.1  | 8.1   | 5.5   | 12.7  |         | 10.7  | 15.5  |     |
| Queue Storage Ratio ( <i>RQ</i> ) ( 90 th percentile)  |  |                 |     | 2.39                     | 0.46          | 0.46  | 0.07  | 1.19  | 0.41  | 0.71  | 1.63  |         | 0.77  | 1.12  |     |
| Uniform Delay ( <i>d<sub>1</sub></i> ), s/veh          |  |                 |     | 39.6                     | 18.6          | 18.6  | 19.7  | 27.6  | 11.1  | 53.0  | 55.0  |         | 43.9  | 46.7  |     |
| Incremental Delay ( <i>d<sub>2</sub></i> ), s/veh      |  |                 |     | 99.9                     | 1.2           | 1.2   | 0.1   | 80.6  | 8.9   | 9.5   | 110.1 |         | 3.4   | 26.2  |     |
| Initial Queue Delay ( <i>d<sub>3</sub></i> ), s/veh    |  |                 |     | 0.0                      | 0.0           | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |         | 0.0   | 0.0   |     |
| Control Delay ( <i>d</i> ), s/veh                      |  |                 |     | 139.5                    | 19.8          | 19.8  | 19.7  | 108.2   | 20.1  | 62.5  | 165.2 |         | 47.3  | 72.9  |     |
| Level of Service (LOS)                                 |  |                 |     | F                        | B             | B     | B     | F   | C     | E     | F     |         | D     | E     |     |
| Approach Delay, s/veh / LOS                            |  |                 |     | 57.3                     |               | E     | 73.9  |   | E     | 124.3 |       | F       | 56.9  |       | E   |
| Intersection Delay, s/veh / LOS                        |  |                 |     | 68.7                     |               |       |       |   |       | E     |       |         |       |       |     |
| Multimodal Results                                     |  |                 |     | EB                       |               |       | WB    |   |       | NB    |       |         | SB    |       |     |
| Pedestrian LOS Score / LOS                             |  |                 |     | 1.95                     |               | B     | 2.15  |   | B     | 2.54  |       | C       | 2.15  |       | B   |
| Bicycle LOS Score / LOS                                |  |                 |     | 1.32                     |               | A     | 3.13  |   | C     | 0.90  |       | A       | 1.86  |       | B   |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

**HCS7 Signalized Intersection Results Summary**

| General Information                              |  |                 |              | Intersection Information  |         |       |       |  |       |       |   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
|--|--|-----------------|--------------|---|---------|-------|-------|---|-------|-------|---|--|-------|-------|---|---|--|--|--|--|--|--|---|--|--|--|
| Agency   | Diane B. Zimmerman Traffic Engineering |                 |              | Duration, h   | 0.25    |       |       |   |       |       |   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Analyst  | DBZ                                    | Analysis Date   | Mar 25, 2018 | Area Type   | Other   |       |       |   |       |       |   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Jurisdiction                                     |  | Time Period     | AM Peak      | PHF   | 0.79    |       |       |   |       |       |   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Urban Street                                     | Taylorsville Road                      | Analysis Year   | 2030 Build   | Analysis Period   | 1> 7:00 |       |       |   |       |       |   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Intersection                                     | Stone Lakes Drive                      | File Name       | AM 30 B.xus  |   |         |       |       |   |       |       |   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Project Description                              | Covington by the Park                  |                 |              |   |         |       |       |   |       |       |   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Demand Information                               |  |                 |              | EB  |         |       | WB    |   |       | NB    |   |  | SB    |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Approach Movement                                |  |                 |              | L   | T       | R     | L     | T   | R     | L     | T   | R  | L     | T     | R   |   |  |  |  |  |  |  |   |  |  |  |
| Demand ( v ), veh/h                              |  |                 |              | 251   | 553     | 15    | 17    | 829   | 655   | 78    | 73  | 75   | 418   | 32    | 243   |   |  |  |  |  |  |  |   |  |  |  |
| Signal Information                               |  |                 |              |   |         |       |       |   |       |       |   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Cycle, s   | 120.0                                  | Reference Phase | 2            |  |         |       |       |    |       |       |   |  |       |       |   |  |  |  |  |  |  |  |   |  |  |  |
| Offset, s  | 0                                      | Reference Point | End          | Green   | 2.8     | 4.2   | 49.2  | 24.3  | 9.3   | 0.0   |  |  |       |       |  |   |  |  |  |  |  |  |  |  |  |  |
| Uncoordinated                                    | No                                     | Simult. Gap E/W | On           | Yellow  | 3.5     | 3.5   | 4.3   | 3.6   | 3.6   | 0.0   |  |  |       |       |  |   |  |  |  |  |  |  |  |  |  |  |
| Force Mode                                       | Fixed                                  | Simult. Gap N/S | Off          | Red   | 3.0     | 3.0   | 1.5   | 2.1   | 2.1   | 0.0   |  |  |       |       |  |   |  |  |  |  |  |  |  |  |  |  |
| Timer Results                                    |  |                 |              | EBL   | EBT     | WBL   | WBT   | NBL   | NBT   | SBL   | SBT   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Assigned Phase                                   |  |                 |              | 5   | 2       | 1     | 6     |   | 8     |       | 4   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Case Number                                      |  |                 |              | 1.1   | 4.0     | 1.1   | 3.0   |   | 10.0  |       | 10.0  |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Phase Duration, s                                |  |                 |              | 20.0  | 65.7    | 9.3   | 55.0  |   | 15.0  |       | 30.0  |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Change Period, ( Y+R <sub>c</sub> ), s           |  |                 |              | 6.5   | 5.8     | 6.5   | 5.8   |   | 5.7   |       | 5.7   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Max Allow Headway ( MAH ), s                     |  |                 |              | 5.0   | 0.0     | 5.0   | 0.0   |   | 5.0   |       | 5.1   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Queue Clearance Time ( g <sub>s</sub> ), s       |  |                 |              | 16.5  |         | 2.7   |       |   | 12.3  |       | 24.5  |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Green Extension Time ( g <sub>e</sub> ), s       |  |                 |              | 0.0   | 0.0     | 0.0   | 0.0   |   | 0.0   |       | 0.0   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Phase Call Probability                           |  |                 |              | 1.00  |         | 0.47  |       |   | 1.00  |       | 1.00  |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Max Out Probability                              |  |                 |              | 1.00  |         | 0.00  |       |   | 1.00  |       | 1.00  |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Movement Group Results                           |  |                 |              | EB  |         |       | WB    |   |       | NB    |   |  | SB    |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Approach Movement                                |  |                 |              | L   | T       | R     | L     | T   | R     | L     | T   | R  | L     | T     | R   |   |  |  |  |  |  |  |   |  |  |  |
| Assigned Movement                                |  |                 |              | 5   | 2       | 12    | 1     | 6   | 16    | 3     | 8   | 18   | 7     | 4     | 14  |   |  |  |  |  |  |  |   |  |  |  |
| Adjusted Flow Rate ( v ), veh/h                  |  |                 |              | 318   | 361     | 358   | 19    | 924   | 563   | 99    | 149   |  | 529   | 310   |   |   |  |  |  |  |  |  |   |  |  |  |
| Adjusted Saturation Flow Rate ( s ), veh/h/ln    |  |                 |              | 1795  | 1856    | 1838  | 1795  | 1841  | 1598  | 1810  | 1736  |  | 1743  | 1630  |   |   |  |  |  |  |  |  |   |  |  |  |
| Queue Service Time ( g <sub>s</sub> ), s         |  |                 |              | 14.5  | 14.5    | 14.5  | 0.7   | 50.2  | 28.5  | 6.3   | 10.3  |  | 16.9  | 22.5  |   |   |  |  |  |  |  |  |   |  |  |  |
| Cycle Queue Clearance Time ( g <sub>c</sub> ), s |  |                 |              | 14.5  | 14.5    | 14.5  | 0.7   | 50.2  | 28.5  | 6.3   | 10.3  |  | 16.9  | 22.5  |   |   |  |  |  |  |  |  |   |  |  |  |
| Green Ratio ( g/C )                              |  |                 |              | 0.56  | 0.50    | 0.50  | 0.43  | 0.42  | 0.42  | 0.09  | 0.09  |  | 0.20  | 0.20  |   |   |  |  |  |  |  |  |   |  |  |  |
| Capacity ( c ), veh/h                            |  |                 |              | 277   | 926     | 917   | 369   | 770   | 655   | 155   | 135   |  | 735   | 344   |   |   |  |  |  |  |  |  |   |  |  |  |
| Volume-to-Capacity Ratio ( X )                   |  |                 |              | 1.147   | 0.390   | 0.390 | 0.051 | 1.201   | 0.860 | 0.636 | 1.110   |  | 0.720 | 0.902 |   |   |  |  |  |  |  |  |   |  |  |  |
| Back of Queue ( Q ), ft/ln ( 90 th percentile)   |  |                 |              | 418.8   | 240.8   | 233.6 | 13.6  | 1329.6  | 212   | 137.8 | 325.7   |  | 276.5 | 391.8 |   |   |  |  |  |  |  |  |   |  |  |  |
| Back of Queue ( Q ), veh/ln ( 90 th percentile)  |  |                 |              | 16.6  | 9.4     | 9.3   | 0.5   | 51.5  | 8.4   | 5.5   | 12.7  |  | 11.0  | 15.5  |   |   |  |  |  |  |  |  |   |  |  |  |
| Queue Storage Ratio ( RQ ) ( 90 th percentile)   |  |                 |              | 2.39  | 0.48    | 0.48  | 0.07  | 1.33  | 0.42  | 0.71  | 1.63  |  | 0.79  | 1.12  |   |   |  |  |  |  |  |  |   |  |  |  |
| Uniform Delay ( d <sub>1</sub> ), s/veh          |  |                 |              | 39.6  | 18.7    | 18.7  | 19.7  | 26.8  | 11.1  | 53.0  | 55.0  |  | 44.1  | 46.7  |   |   |  |  |  |  |  |  |   |  |  |  |
| Incremental Delay ( d <sub>2</sub> ), s/veh      |  |                 |              | 99.9  | 1.2     | 1.2   | 0.1   | 99.2  | 10.2  | 9.5   | 110.1   |  | 3.7   | 26.2  |   |   |  |  |  |  |  |  |   |  |  |  |
| Initial Queue Delay ( d <sub>3</sub> ), s/veh    |  |                 |              | 0.0   | 0.0     | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |  | 0.0   | 0.0   |   |   |  |  |  |  |  |  |   |  |  |  |
| Control Delay ( d ), s/veh                       |  |                 |              | 139.5   | 19.9    | 19.9  | 19.8  | 126.0   | 21.3  | 62.5  | 165.2   |  | 47.8  | 72.9  |   |   |  |  |  |  |  |  |   |  |  |  |
| Level of Service ( LOS )                         |  |                 |              | F   | B       | B     | B     | F   | C     | E     | F   |  | D     | E     |   |   |  |  |  |  |  |  |   |  |  |  |
| Approach Delay, s/veh / LOS                      |  |                 |              | 56.6  |         | E     | 85.5  |   | F     | 124.3 |   | F  | 57.1  |       | E   |   |  |  |  |  |  |  |   |  |  |  |
| Intersection Delay, s/veh / LOS                  |  |                 |              | 73.3  |         |       |       |   |       | E     |   |  |       |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Multimodal Results                               |  |                 |              | EB  |         |       | WB    |   |       | NB    |   |  | SB    |       |   |   |  |  |  |  |  |  |   |  |  |  |
| Pedestrian LOS Score / LOS                       |  |                 |              | 1.95  |         | B     | 2.15  |   | B     | 2.54  |   | C  | 2.15  |       | B   |   |  |  |  |  |  |  |   |  |  |  |
| Bicycle LOS Score / LOS                          |  |                 |              | 1.34  |         | A     | 3.31  |   | C     | 0.90  |   | A  | 1.87  |       | B   |   |  |  |  |  |  |  |   |  |  |  |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |           |       |                 |                                 |       |       |       |       |    |       |       |    |
|---|--|-----------------|---------------|-----------|-------|-----------------|---------------------------------|-------|-------|-------|-------|----|-------|-------|----|
| <b>General Information</b>                      |  |                 |               |           |       |                 | <b>Intersection Information</b> |       |       |       |       |    |       |       |    |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |           |       |                 | Duration, h                     | 0.25  |       |       |       |    |       |       |    |
| Analyst   | DBZ                                    | Analysis Date   | 3/8/2018      |           |       | Area Type       | Other                           |       |       |       |       |    |       |       |    |
| Jurisdiction                                    |  | Time Period     | PM Peak       |           |       | PHF             | 0.97                            |       |       |       |       |    |       |       |    |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2018      |       | Analysis Period | 1> 4:00                         |       |       |       |       |    |       |       |    |
| Intersection                                    | Stone Lakes Drive                      |                 | File Name     | PM 18.xus |       |                 |                                 |       |       |       |       |    |       |       |    |
| Project Description                             | Covington by the Park                  |                 |               |           |       |                 |                                 |       |       |       |       |    |       |       |    |
| <b>Demand Information</b>                       |  |                 |               | EB        |       |                 | WB                              |       |       | NB    |       |    | SB    |       |    |
| Approach Movement                               |  |                 |               | L         | T     | R               | L                               | T     | R     | L     | T     | R  | L     | T     | R  |
| Demand (v), veh/h                               |  |                 |               | 41        | 1064  | 39              | 31                              | 566   | 308   | 37    | 20    | 26 | 352   | 30    | 78 |
| <b>Signal Information</b>                       |  |                 |               |           |       |                 |                                 |       |       |       |       |    |       |       |    |
| Cycle, s  | 120.0                                  | Reference Phase | 2             | Green     | 3.9   | 0.7             | 63.2                            | 34.3  | 0.0   | 0.0   |       |    |       |       |    |
| Offset, s                                       | 0                                      | Reference Point | End           | Yellow    | 3.5   | 0.0             | 4.3                             | 3.6   | 0.0   | 0.0   |       |    |       |       |    |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On            | Red       | 3.0   | 0.0             | 1.5                             | 2.1   | 0.0   | 0.0   |       |    |       |       |    |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | Off           |           |       |                 |                                 |       |       |       |       |    |       |       |    |
| <b>Timer Results</b>                            |  |                 |               | EBL       | EBT   | WBL             | WBT                             | NBL   | NBT   | SBL   | SBT   |    |       |       |    |
| Assigned Phase                                  |  |                 |               | 5         | 2     | 1               | 6                               |       | 8     |       | 4     |    |       |       |    |
| Case Number                                     |  |                 |               | 1.1       | 4.0   | 1.1             | 3.0                             |       | 6.0   |       | 6.0   |    |       |       |    |
| Phase Duration, s                               |  |                 |               | 11.0      | 69.6  | 10.4            | 69.0                            |       | 40.0  |       | 40.0  |    |       |       |    |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               | 6.5       | 5.8   | 6.5             | 5.8                             |       | 5.7   |       | 5.7   |    |       |       |    |
| Max Allow Headway (MAH), s                      |  |                 |               | 5.0       | 0.0   | 5.0             | 0.0                             |       | 5.1   |       | 5.1   |    |       |       |    |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               | 3.3       |       | 2.9             |                                 |       | 10.9  |       | 35.9  |    |       |       |    |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               | 0.0       | 0.0   | 0.0             | 0.0                             |       | 0.4   |       | 0.0   |    |       |       |    |
| Phase Call Probability                          |  |                 |               | 0.76      |       | 0.64            |                                 |       | 1.00  |       | 1.00  |    |       |       |    |
| Max Out Probability                             |  |                 |               | 0.80      |       | 0.53            |                                 |       | 0.00  |       | 1.00  |    |       |       |    |
| <b>Movement Group Results</b>                   |  |                 |               | EB        |       |                 | WB                              |       |       | NB    |       |    | SB    |       |    |
| Approach Movement                               |  |                 |               | L         | T     | R               | L                               | T     | R     | L     | T     | R  | L     | T     | R  |
| Assigned Movement                               |  |                 |               | 5         | 2     | 12              | 1                               | 6     | 16    | 3     | 8     | 18 | 7     | 4     | 14 |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               | 42        | 572   | 565             | 31                              | 563   | 306   | 38    | 47    |    | 363   | 111   |    |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               | 1795      | 1856  | 1832            | 1795                            | 1841  | 1598  | 1302  | 1684  |    | 1369  | 1668  |    |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               | 1.3       | 25.0  | 25.0            | 0.9                             | 27.3  | 8.2   | 2.8   | 2.5   |    | 31.5  | 6.1   |    |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               | 1.3       | 25.0  | 25.0            | 0.9                             | 27.3  | 8.2   | 8.9   | 2.5   |    | 33.9  | 6.1   |    |
| Green Ratio (g/C)                               |  |                 |               | 0.56      | 0.53  | 0.53            | 0.56                            | 0.53  | 0.53  | 0.29  | 0.29  |    | 0.29  | 0.29  |    |
| Capacity (c), veh/h                             |  |                 |               | 383       | 987   | 975             | 271                             | 969   | 841   | 366   | 481   |    | 434   | 477   |    |
| Volume-to-Capacity Ratio (X)                    |  |                 |               | 0.110     | 0.579 | 0.580           | 0.114                           | 0.581 | 0.364 | 0.104 | 0.099 |    | 0.835 | 0.233 |    |
| Back of Queue (Q), ft/ln (90 th percentile)     |  |                 |               | 22.3      | 378.9 | 366.8           | 16.3                            | 425.4 | 113.1 | 39.6  | 46.4  |    | 409.5 | 111.8 |    |
| Back of Queue (Q), veh/ln (90 th percentile)    |  |                 |               | 0.9       | 14.8  | 14.7            | 0.6                             | 16.5  | 4.5   | 1.6   | 1.8   |    | 16.3  | 4.4   |    |
| Queue Storage Ratio (RQ) (90 th percentile)     |  |                 |               | 0.13      | 0.76  | 0.75            | 0.09                            | 0.43  | 0.23  | 0.20  | 0.23  |    | 1.17  | 0.32  |    |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               | 14.9      | 19.0  | 19.0            | 14.7                            | 23.1  | 8.5   | 36.2  | 31.5  |    | 43.1  | 32.8  |    |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               | 0.2       | 2.5   | 2.5             | 0.2                             | 2.3   | 1.1   | 0.2   | 0.1   |    | 13.7  | 0.4   |    |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               | 0.0       | 0.0   | 0.0             | 0.0                             | 0.0   | 0.0   | 0.0   | 0.0   |    | 0.0   | 0.0   |    |
| Control Delay (d), s/veh                        |  |                 |               | 15.1      | 21.5  | 21.5            | 14.9                            | 25.4  | 9.6   | 36.4  | 31.6  |    | 56.8  | 33.1  |    |
| Level of Service (LOS)                          |  |                 |               | B         | C     | C               | B                               | C     | A     | D     | C     |    | E     | C     |    |
| Approach Delay, s/veh / LOS                     |  |                 |               | 21.3      |       | C               | 19.7                            |       | B     | 33.7  |       | C  | 51.3  |       | D  |
| Intersection Delay, s/veh / LOS                 |  |                 |               | 26.5      |       |                 |                                 |       | C     |       |       |    |       |       |    |
| <b>Multimodal Results</b>                       |  |                 |               | EB        |       |                 | WB                              |       |       | NB    |       |    | SB    |       |    |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.90      |       | B               | 1.90                            |       | B     | 2.29  |       | B  | 2.13  |       | B  |
| Bicycle LOS Score / LOS                         |  |                 |               | 1.46      |       | A               | 2.03                            |       | B     | 0.63  |       | A  | 1.27  |       | A  |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary     |  |                 |               |        |       |                 |                                 |       |       |       |       |    |       |       |     |
|--|--|-----------------|---------------|--------|-------|-----------------|---------------------------------|-------|-------|-------|-------|----|-------|-------|-----|
| <b>General Information</b>                       |  |                 |               |        |       |                 | <b>Intersection Information</b> |       |       |       |       |    |       |       |     |
| Agency   | Diane B. Zimmerman Traffic Engineering |                 |               |        |       |                 | Duration, h                     | 0.25  |       |       |       |    |       |       |     |
| Analyst  | DBZ                                    | Analysis Date   | Mar 25, 2018  |        |       | Area Type       | Other                           |       |       |       |       |    |       |       |     |
| Jurisdiction                                     |  | Time Period     | PM Peak       |        |       | PHF             | 0.97                            |       |       |       |       |    |       |       |     |
| Urban Street                                     | Taylorsville Road                      | Analysis Year   | 2030 No Build |        |       | Analysis Period | 1> 4:00                         |       |       |       |       |    |       |       |     |
| Intersection                                     | Stone Lakes Drive                      | File Name       | PM 30 NB.xus  |        |       |                 |                                 |       |       |       |       |    |       |       |     |
| Project Description                              | Covington by the Park                  |                 |               |        |       |                 |                                 |       |       |       |       |    |       |       |     |
| <b>Demand Information</b>                        |  |                 |               | EB     |       |                 | WB                              |       |       | NB    |       |    | SB    |       |     |
| Approach Movement                                |  |                 |               | L      | T     | R               | L                               | T     | R     | L     | T     | R  | L     | T     | R   |
| Demand ( v ), veh/h                              |  |                 |               | 109    | 1199  | 44              | 35                              | 638   | 648   | 42    | 27    | 29 | 693   | 38    | 147 |
| <b>Signal Information</b>                        |  |                 |               |        |       |                 |                                 |       |       |       |       |    |       |       |     |
| Cycle, s   | 120.0                                  | Reference Phase | 2             |        |       |                 |                                 |       |       |       |       |    |       |       |     |
| Offset, s  | 0                                      | Reference Point | End           |        |       |                 |                                 |       |       |       |       |    |       |       |     |
| Uncoordinated                                    | No                                     | Simult. Gap E/W | On            | Green  | 4.1   | 1.8             | 60.5                            | 24.3  | 5.7   | 0.0   |       |    |       |       |     |
| Force Mode                                       | Fixed                                  | Simult. Gap N/S | Off           | Yellow | 3.5   | 0.0             | 4.3                             | 3.6   | 3.6   | 0.0   |       |    |       |       |     |
|  |  |                 |               | Red    | 3.0   | 0.0             | 1.5                             | 2.1   | 2.1   | 0.0   |       |    |       |       |     |
| <b>Timer Results</b>                             |  |                 |               | EBL    | EBT   | WBL             | WBT                             | NBL   | NBT   | SBL   | SBT   |    |       |       |     |
| Assigned Phase                                   |  |                 |               | 5      | 2     | 1               | 6                               |       | 8     |       | 4     |    |       |       |     |
| Case Number                                      |  |                 |               | 1.1    | 4.0   | 1.1             | 3.0                             |       | 10.0  |       | 10.0  |    |       |       |     |
| Phase Duration, s                                |  |                 |               | 12.4   | 68.0  | 10.6            | 66.3                            |       | 11.4  |       | 30.0  |    |       |       |     |
| Change Period, ( Y+R <sub>c</sub> ), s           |  |                 |               | 6.5    | 5.8   | 6.5             | 5.8                             |       | 5.7   |       | 5.7   |    |       |       |     |
| Max Allow Headway ( MAH ), s                     |  |                 |               | 5.0    | 0.0   | 5.0             | 0.0                             |       | 5.0   |       | 5.0   |    |       |       |     |
| Queue Clearance Time ( g <sub>s</sub> ), s       |  |                 |               | 5.6    |       | 3.1             |                                 |       | 4.8   |       | 26.4  |    |       |       |     |
| Green Extension Time ( g <sub>e</sub> ), s       |  |                 |               | 0.2    | 0.0   | 0.0             | 0.0                             |       | 0.1   |       | 0.0   |    |       |       |     |
| Phase Call Probability                           |  |                 |               | 0.98   |       | 0.68            |                                 |       | 0.94  |       | 1.00  |    |       |       |     |
| Max Out Probability                              |  |                 |               | 0.33   |       | 0.01            |                                 |       | 1.00  |       | 1.00  |    |       |       |     |
| <b>Movement Group Results</b>                    |  |                 |               | EB     |       |                 | WB                              |       |       | NB    |       |    | SB    |       |     |
| Approach Movement                                |  |                 |               | L      | T     | R               | L                               | T     | R     | L     | T     | R  | L     | T     | R   |
| Assigned Movement                                |  |                 |               | 5      | 2     | 12              | 1                               | 6     | 16    | 3     | 8     | 18 | 7     | 4     | 14  |
| Adjusted Flow Rate ( v ), veh/h                  |  |                 |               | 112    | 644   | 637             | 34                              | 629   | 491   | 43    | 42    |    | 714   | 160   |     |
| Adjusted Saturation Flow Rate ( s ), veh/h/ln    |  |                 |               | 1795   | 1856  | 1832            | 1795                            | 1841  | 1598  | 1810  | 1748  |    | 1743  | 1660  |     |
| Queue Service Time ( g <sub>s</sub> ), s         |  |                 |               | 3.6    | 30.7  | 30.8            | 1.1                             | 28.9  | 15.1  | 2.8   | 2.8   |    | 24.4  | 10.2  |     |
| Cycle Queue Clearance Time ( g <sub>c</sub> ), s |  |                 |               | 3.6    | 30.7  | 30.8            | 1.1                             | 28.9  | 15.1  | 2.8   | 2.8   |    | 24.4  | 10.2  |     |
| Green Ratio ( g/C )                              |  |                 |               | 0.55   | 0.52  | 0.52            | 0.54                            | 0.50  | 0.50  | 0.05  | 0.05  |    | 0.20  | 0.20  |     |
| Capacity ( c ), veh/h                            |  |                 |               | 359    | 963   | 950             | 228                             | 928   | 805   | 85    | 82    |    | 735   | 336   |     |
| Volume-to-Capacity Ratio ( X )                   |  |                 |               | 0.313  | 0.669 | 0.670           | 0.151                           | 0.677 | 0.609 | 0.508 | 0.513 |    | 0.972 | 0.475 |     |
| Back of Queue ( Q ), ft/ln ( 90 th percentile)   |  |                 |               | 64.8   | 460.1 | 445.8           | 19.5                            | 379.8 | 138.6 | 63.2  | 63.6  |    | 441.6 | 172.4 |     |
| Back of Queue ( Q ), veh/ln ( 90 th percentile)  |  |                 |               | 2.6    | 18.0  | 17.8            | 0.8                             | 14.7  | 5.5   | 2.5   | 2.5   |    | 17.5  | 6.8   |     |
| Queue Storage Ratio ( RQ ) ( 90 th percentile)   |  |                 |               | 0.37   | 0.92  | 0.91            | 0.10                            | 0.38  | 0.28  | 0.32  | 0.32  |    | 1.26  | 0.49  |     |
| Uniform Delay ( d <sub>1</sub> ), s/veh          |  |                 |               | 16.9   | 21.3  | 21.3            | 17.3                            | 19.3  | 7.9   | 55.8  | 55.8  |    | 47.0  | 42.2  |     |
| Incremental Delay ( d <sub>2</sub> ), s/veh      |  |                 |               | 0.7    | 3.7   | 3.8             | 0.3                             | 2.4   | 2.1   | 6.5   | 6.9   |    | 26.4  | 1.5   |     |
| Initial Queue Delay ( d <sub>3</sub> ), s/veh    |  |                 |               | 0.0    | 0.0   | 0.0             | 0.0                             | 0.0   | 0.0   | 0.0   | 0.0   |    | 0.0   | 0.0   |     |
| Control Delay ( d ), s/veh                       |  |                 |               | 17.6   | 25.0  | 25.1            | 17.6                            | 21.7  | 10.0  | 62.3  | 62.7  |    | 73.4  | 43.7  |     |
| Level of Service (LOS)                           |  |                 |               | B      | C     | C               | B                               | C     | B     | E     | E     |    | E     | D     |     |
| Approach Delay, s/veh / LOS                      |  |                 |               | 24.4   |       | C               | 16.6                            |       | B     | 62.5  |       | E  | 67.9  |       | E   |
| Intersection Delay, s/veh / LOS                  |  |                 |               | 33.6   |       |                 |                                 |       |       | C     |       |    |       |       |     |
| <b>Multimodal Results</b>                        |  |                 |               | EB     |       |                 | WB                              |       |       | NB    |       |    | SB    |       |     |
| Pedestrian LOS Score / LOS                       |  |                 |               | 1.92   |       | B               | 2.14                            |       | B     | 2.54  |       | C  | 2.15  |       | B   |
| Bicycle LOS Score / LOS                          |  |                 |               | 1.64   |       | B               | 2.48                            |       | B     | 0.63  |       | A  | 1.93  |       | B   |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |              |        |       |                                 |         |       |       |       |       |    |       |       |     |
|---|--|-----------------|--------------|--------|-------|---------------------------------|---------|-------|-------|-------|-------|----|-------|-------|-----|
| <b>General Information</b>                      |  |                 |              |        |       | <b>Intersection Information</b> |         |       |       |       |       |    |       |       |     |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |              |        |       | Duration, h                     | 0.25    |       |       |       |       |    |       |       |     |
| Analyst   | DBZ                                    | Analysis Date   | Mar 25, 2018 |        |       | Area Type                       | Other   |       |       |       |       |    |       |       |     |
| Jurisdiction                                    |  | Time Period     | PM Peak      |        |       | PHF                             | 0.97    |       |       |       |       |    |       |       |     |
| Urban Street                                    | Taylorsville Road                      | Analysis Year   | 2030 Build   |        |       | Analysis Period                 | 1> 4:00 |       |       |       |       |    |       |       |     |
| Intersection                                    | Stone Lakes Drive                      | File Name       | PM 30 B.xus  |        |       |                                 |         |       |       |       |       |    |       |       |     |
| Project Description                             | Covington by the Park                  |                 |              |        |       |                                 |         |       |       |       |       |    |       |       |     |
| <b>Demand Information</b>                       |  |                 |              | EB     |       |                                 | WB      |       |       | NB    |       |    | SB    |       |     |
| Approach Movement                               |  |                 |              | L      | T     | R                               | L       | T     | R     | L     | T     | R  | L     | T     | R   |
| Demand (v), veh/h                               |  |                 |              | 109    | 1270  | 44                              | 35      | 674   | 668   | 42    | 27    | 29 | 716   | 38    | 147 |
| <b>Signal Information</b>                       |  |                 |              |        |       |                                 |         |       |       |       |       |    |       |       |     |
| Cycle, s  | 120.0                                  | Reference Phase | 2            |        |       |                                 |         |       |       |       |       |    |       |       |     |
| Offset, s                                       | 0                                      | Reference Point | End          |        |       |                                 |         |       |       |       |       |    |       |       |     |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On           | Green  | 4.1   | 1.8                             | 60.5    | 24.3  | 5.7   | 0.0   |       |    |       |       |     |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | Off          | Yellow | 3.5   | 0.0                             | 4.3     | 3.6   | 3.6   | 0.0   |       |    |       |       |     |
|   |  |                 |              | Red    | 3.0   | 0.0                             | 1.5     | 2.1   | 2.1   | 0.0   |       |    |       |       |     |
| <b>Timer Results</b>                            |  |                 |              | EBL    | EBT   | WBL                             | WBT     | NBL   | NBT   | SBL   | SBT   |    |       |       |     |
| Assigned Phase                                  |  |                 |              | 5      | 2     | 1                               | 6       |       | 8     |       | 4     |    |       |       |     |
| Case Number                                     |  |                 |              | 1.1    | 4.0   | 1.1                             | 3.0     |       | 10.0  |       | 10.0  |    |       |       |     |
| Phase Duration, s                               |  |                 |              | 12.4   | 68.0  | 10.6                            | 66.3    |       | 11.4  |       | 30.0  |    |       |       |     |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |              | 6.5    | 5.8   | 6.5                             | 5.8     |       | 5.7   |       | 5.7   |    |       |       |     |
| Max Allow Headway (MAH), s                      |  |                 |              | 5.0    | 0.0   | 5.0                             | 0.0     |       | 5.0   |       | 5.0   |    |       |       |     |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |              | 5.6    |       | 3.1                             |         |       | 4.8   |       | 27.3  |    |       |       |     |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |              | 0.2    | 0.0   | 0.0                             | 0.0     |       | 0.1   |       | 0.0   |    |       |       |     |
| Phase Call Probability                          |  |                 |              | 0.98   |       | 0.68                            |         |       | 0.94  |       | 1.00  |    |       |       |     |
| Max Out Probability                             |  |                 |              | 0.33   |       | 0.01                            |         |       | 1.00  |       | 1.00  |    |       |       |     |
| <b>Movement Group Results</b>                   |  |                 |              | EB     |       |                                 | WB      |       |       | NB    |       |    | SB    |       |     |
| Approach Movement                               |  |                 |              | L      | T     | R                               | L       | T     | R     | L     | T     | R  | L     | T     | R   |
| Assigned Movement                               |  |                 |              | 5      | 2     | 12                              | 1       | 6     | 16    | 3     | 8     | 18 | 7     | 4     | 14  |
| Adjusted Flow Rate (v), veh/h                   |  |                 |              | 112    | 681   | 674                             | 35      | 666   | 512   | 43    | 42    |    | 738   | 160   |     |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |              | 1795   | 1856  | 1833                            | 1795    | 1841  | 1598  | 1810  | 1748  |    | 1743  | 1660  |     |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |              | 3.6    | 33.5  | 33.6                            | 1.1     | 31.5  | 16.2  | 2.8   | 2.8   |    | 25.3  | 10.2  |     |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |              | 3.6    | 33.5  | 33.6                            | 1.1     | 31.5  | 16.2  | 2.8   | 2.8   |    | 25.3  | 10.2  |     |
| Green Ratio (g/C)                               |  |                 |              | 0.55   | 0.52  | 0.52                            | 0.54    | 0.50  | 0.50  | 0.05  | 0.05  |    | 0.20  | 0.20  |     |
| Capacity (c), veh/h                             |  |                 |              | 335    | 962   | 951                             | 212     | 928   | 805   | 85    | 82    |    | 735   | 336   |     |
| Volume-to-Capacity Ratio (X)                    |  |                 |              | 0.336  | 0.707 | 0.709                           | 0.164   | 0.718 | 0.636 | 0.508 | 0.513 |    | 1.004 | 0.475 |     |
| Back of Queue (Q), ft/ln (90 th percentile)     |  |                 |              | 65.1   | 498.3 | 483.9                           | 19.6    | 407.4 | 142.9 | 63.2  | 63.6  |    | 477.3 | 172.4 |     |
| Back of Queue (Q), veh/ln (90 th percentile)    |  |                 |              | 2.6    | 19.5  | 19.4                            | 0.8     | 15.8  | 5.7   | 2.5   | 2.5   |    | 18.9  | 6.8   |     |
| Queue Storage Ratio (RQ) (90 th percentile)     |  |                 |              | 0.37   | 1.00  | 0.99                            | 0.10    | 0.41  | 0.29  | 0.32  | 0.32  |    | 1.36  | 0.49  |     |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |              | 17.6   | 22.0  | 22.0                            | 18.2    | 19.5  | 7.9   | 55.8  | 55.8  |    | 47.4  | 42.2  |     |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |              | 0.8    | 4.4   | 4.5                             | 0.3     | 2.9   | 2.3   | 6.5   | 6.9   |    | 34.2  | 1.5   |     |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |              | 0.0    | 0.0   | 0.0                             | 0.0     | 0.0   | 0.0   | 0.0   | 0.0   |    | 0.0   | 0.0   |     |
| Control Delay (d), s/veh                        |  |                 |              | 18.5   | 26.3  | 26.4                            | 18.5    | 22.4  | 10.2  | 62.3  | 62.7  |    | 81.6  | 43.7  |     |
| Level of Service (LOS)                          |  |                 |              | B      | C     | C                               | B       | C     | B     | E     | E     |    | F     | D     |     |
| Approach Delay, s/veh / LOS                     |  |                 |              | 25.8   |       | C                               | 17.1    |       | B     | 62.5  |       | E  | 74.8  |       | E   |
| Intersection Delay, s/veh / LOS                 |  |                 |              | 35.8   |       |                                 |         |       | D     |       |       |    |       |       |     |
| <b>Multimodal Results</b>                       |  |                 |              | EB     |       |                                 | WB      |       |       | NB    |       |    | SB    |       |     |
| Pedestrian LOS Score / LOS                      |  |                 |              | 1.92   |       | B                               | 2.14    |       | B     | 2.54  |       | C  | 2.15  |       | B   |
| Bicycle LOS Score / LOS                         |  |                 |              | 1.70   |       | B                               | 2.57    |       | C     | 0.63  |       | A  | 1.97  |       | B   |



Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |           |       |                                 |         |       |      |     |     |       |    |       |     |
|---|--|-----------------|---------------|-----------|-------|---------------------------------|---------|-------|------|-----|-----|-------|----|-------|-----|
| <b>General Information</b>                      |  |                 |               |           |       | <b>Intersection Information</b> |         |       |      |     |     |       |    |       |     |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |           |       | Duration, h                     | 0.25    |       |      |     |     |       |    |       |     |
| Analyst   | DBZ                                    | Analysis Date   | 3/8/2018      |           |       | Area Type                       | Other   |       |      |     |     |       |    |       |     |
| Jurisdiction                                    |  | Time Period     | AM Peak       |           |       | PHF                             | 0.95    |       |      |     |     |       |    |       |     |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2018      |       | Analysis Period                 | 1> 7:00 |       |      |     |     |       |    |       |     |
| Intersection                                    | I 265 SB Ramps                         |                 | File Name     | AM 18.xus |       |                                 |         |       |      |     |     |       |    |       |     |
| Project Description                             | Covington by the Park                  |                 |               |           |       |                                 |         |       |      |     |     |       |    |       |     |
| <b>Demand Information</b>                       |  |                 |               | EB        |       |                                 | WB      |       |      | NB  |     |       | SB |       |     |
| Approach Movement                               |  |                 |               | L         | T     | R                               | L       | T     | R    | L   | T   | R     | L  | T     | R   |
| Demand (v), veh/h                               |  |                 |               |           | 550   | 263                             | 250     | 886   |      |     |     | 152   |    |       | 243 |
| <b>Signal Information</b>                       |  |                 |               |           |       |                                 |         |       |      |     |     |       |    |       |     |
| Cycle, s  | 120.0                                  | Reference Phase | 2             |           |       |                                 |         |       |      |     |     |       |    |       |     |
| Offset, s                                       | 0                                      | Reference Point | End           |           |       |                                 |         |       |      |     |     |       |    |       |     |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On            | Green     | 10.0  | 68.6                            | 23.2    | 0.0   | 0.0  | 0.0 |     |       |    |       |     |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            | Yellow    | 3.5   | 4.3                             | 3.5     | 0.0   | 0.0  | 0.0 |     |       |    |       |     |
|   |  |                 |               | Red       | 2.8   | 1.6                             | 2.5     | 0.0   | 0.0  | 0.0 |     |       |    |       |     |
| <b>Timer Results</b>                            |  |                 |               | EBL       | EBT   | WBL                             | WBT     | NBL   | NBT  | SBL | SBT |       |    |       |     |
| Assigned Phase                                  |  |                 |               |           | 2     | 1                               | 6       |       |      |     |     | 4     |    |       |     |
| Case Number                                     |  |                 |               |           | 7.3   | 1.0                             | 4.0     |       |      |     |     | 9.0   |    |       |     |
| Phase Duration, s                               |  |                 |               |           | 74.5  | 16.3                            | 90.8    |       |      |     |     | 29.2  |    |       |     |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               |           | 5.9   | 6.3                             | 5.9     |       |      |     |     | 6.0   |    |       |     |
| Max Allow Headway (MAH), s                      |  |                 |               |           | 0.0   | 4.0                             | 0.0     |       |      |     |     | 5.2   |    |       |     |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               |           |       | 8.9                             |         |       |      |     |     | 21.3  |    |       |     |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               |           | 0.0   | 0.8                             | 0.0     |       |      |     |     | 2.0   |    |       |     |
| Phase Call Probability                          |  |                 |               |           |       | 1.00                            |         |       |      |     |     | 1.00  |    |       |     |
| Max Out Probability                             |  |                 |               |           |       | 0.00                            |         |       |      |     |     | 0.09  |    |       |     |
| <b>Movement Group Results</b>                   |  |                 |               | EB        |       |                                 | WB      |       |      | NB  |     |       | SB |       |     |
| Approach Movement                               |  |                 |               | L         | T     | R                               | L       | T     | R    | L   | T   | R     | L  | T     | R   |
| Assigned Movement                               |  |                 |               |           | 2     | 12                              | 1       | 6     |      |     |     | 7     |    | 14    |     |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               |           | 640   | 306                             | 265     | 940   |      |     |     | 160   |    | 256   |     |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               |           | 1742  |                                 | 1781    | 1806  |      |     |     | 1702  |    | 1541  |     |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               |           | 10.1  |                                 | 6.9     | 23.7  |      |     |     | 4.8   |    | 19.3  |     |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               |           | 10.1  |                                 | 6.9     | 23.7  |      |     |     | 4.8   |    | 19.3  |     |
| Green Ratio (g/C)                               |  |                 |               |           | 0.57  |                                 | 0.67    | 0.61  |      |     |     | 0.19  |    | 0.19  |     |
| Capacity (c), veh/h                             |  |                 |               |           | 1991  |                                 | 593     | 2215  |      |     |     | 659   |    | 298   |     |
| Volume-to-Capacity Ratio (X)                    |  |                 |               |           | 0.321 |                                 | 0.447   | 0.424 |      |     |     | 0.243 |    | 0.857 |     |
| Back of Queue (Q), ft/ln (90 th percentile)     |  |                 |               |           | 147.2 |                                 | 102.8   | 363.7 |      |     |     | 92    |    | 301.8 |     |
| Back of Queue (Q), veh/ln (90 th percentile)    |  |                 |               |           | 5.8   |                                 | 4.0     | 14.4  |      |     |     | 3.6   |    | 11.9  |     |
| Queue Storage Ratio (RQ) (90 th percentile)     |  |                 |               |           | 0.29  |                                 | 0.37    | 0.52  |      |     |     | 0.26  |    | 0.86  |     |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               |           | 11.2  |                                 | 8.6     | 18.7  |      |     |     | 40.9  |    | 46.8  |     |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               |           | 0.4   |                                 | 0.4     | 0.4   |      |     |     | 0.3   |    | 12.9  |     |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               |           | 0.0   |                                 | 0.0     | 0.0   |      |     |     | 0.0   |    | 0.0   |     |
| Control Delay (d), s/veh                        |  |                 |               |           | 11.6  | 0.0                             | 9.0     | 19.2  |      |     |     | 41.2  |    | 59.6  |     |
| Level of Service (LOS)                          |  |                 |               |           | B     | A                               | A       | B     |      |     |     | D     |    | E     |     |
| Approach Delay, s/veh / LOS                     |  |                 |               | 7.8       |       | A                               | 16.9    | B     | 0.0  |     |     | 52.5  |    | D     |     |
| Intersection Delay, s/veh / LOS                 |  |                 |               | 19.3      |       |                                 |         | B     |      |     |     |       |    |       |     |
| <b>Multimodal Results</b>                       |  |                 |               | EB        |       |                                 | WB      |       |      | NB  |     |       | SB |       |     |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.38      |       | A                               | 1.86    | B     | 2.32 |     | B   | 2.33  |    | B     |     |
| Bicycle LOS Score / LOS                         |  |                 |               | 1.19      |       | A                               | 1.47    | A     |      |     |     |       | F  |       |     |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |               |       |                                 |         |       |     |      |      |       |      |       |     |
|---|--|-----------------|---------------|---------------|-------|---------------------------------|---------|-------|-----|------|------|-------|------|-------|-----|
| <b>General Information</b>                      |  |                 |               |               |       | <b>Intersection Information</b> |         |       |     |      |      |       |      |       |     |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |               |       | Duration, h                     | 0.25    |       |     |      |      |       |      |       |     |
| Analyst   | DBZ                                    | Analysis Date   | 3/8/2018      |               |       | Area Type                       | Other   |       |     |      |      |       |      |       |     |
| Jurisdiction                                    |  | Time Period     | AM Peak       |               |       | PHF                             | 0.95    |       |     |      |      |       |      |       |     |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2030 No Build |       | Analysis Period                 | 1> 7:00 |       |     |      |      |       |      |       |     |
| Intersection                                    | I 265 SB Ramps                         |                 | File Name     | AM 30 NB.xus  |       |                                 |         |       |     |      |      |       |      |       |     |
| Project Description                             | Covington by the Park                  |                 |               |               |       |                                 |         |       |     |      |      |       |      |       |     |
| <b>Demand Information</b>                       |  |                 |               | EB            |       |                                 | WB      |       |     | NB   |      |       | SB   |       |     |
| Approach Movement                               |  |                 |               | L             | T     | R                               | L       | T     | R   | L    | T    | R     | L    | T     | R   |
| Demand (v), veh/h                               |  |                 |               |               | 775   | 347                             | 317     | 1179  |     |      |      | 193   |      |       | 416 |
| <b>Signal Information</b>                       |  |                 |               |               |       |                                 |         |       |     |      |      |       |      |       |     |
| Cycle, s  | 120.0                                  | Reference Phase | 2             |               |       |                                 |         |       |     |      |      |       |      |       |     |
| Offset, s                                       | 0                                      | Reference Point | End           |               |       |                                 |         |       |     |      |      |       |      |       |     |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On            | Green         | 13.5  | 54.3                            | 34.0    | 0.0   | 0.0 | 0.0  |      |       |      |       |     |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            | Yellow        | 3.5   | 4.3                             | 3.5     | 0.0   | 0.0 | 0.0  |      |       |      |       |     |
|   |  |                 |               | Red           | 2.8   | 1.6                             | 2.5     | 0.0   | 0.0 | 0.0  |      |       |      |       |     |
| <b>Timer Results</b>                            |  |                 |               | EBL           | EBT   | WBL                             | WBT     | NBL   | NBT | SBL  | SBT  |       |      |       |     |
| Assigned Phase                                  |  |                 |               |               | 2     | 1                               | 6       |       |     |      |      | 4     |      |       |     |
| Case Number                                     |  |                 |               |               | 7.3   | 1.0                             | 4.0     |       |     |      |      | 9.0   |      |       |     |
| Phase Duration, s                               |  |                 |               |               | 60.2  | 19.8                            | 80.0    |       |     |      |      | 40.0  |      |       |     |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               |               | 5.9   | 6.3                             | 5.9     |       |     |      |      | 6.0   |      |       |     |
| Max Allow Headway (MAH), s                      |  |                 |               |               | 0.0   | 4.0                             | 0.0     |       |     |      |      | 5.2   |      |       |     |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               |               |       | 13.0                            |         |       |     |      | 34.8 |       |      |       |     |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               |               | 0.0   | 0.6                             | 0.0     |       |     |      | 0.0  |       |      |       |     |
| Phase Call Probability                          |  |                 |               |               |       | 1.00                            |         |       |     |      | 1.00 |       |      |       |     |
| Max Out Probability                             |  |                 |               |               |       | 0.39                            |         |       |     |      | 1.00 |       |      |       |     |
| <b>Movement Group Results</b>                   |  |                 |               | EB            |       |                                 | WB      |       |     | NB   |      |       | SB   |       |     |
| Approach Movement                               |  |                 |               | L             | T     | R                               | L       | T     | R   | L    | T    | R     | L    | T     | R   |
| Assigned Movement                               |  |                 |               |               | 2     | 12                              | 1       | 6     |     |      |      | 7     |      | 14    |     |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               |               | 891   | 399                             | 325     | 1209  |     |      |      | 203   |      | 438   |     |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               |               | 1774  |                                 | 1781    | 1846  |     |      |      | 1702  |      | 1587  |     |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               |               | 23.2  |                                 | 11.0    | 30.5  |     |      |      | 5.5   |      | 32.8  |     |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               |               | 23.2  |                                 | 11.0    | 30.5  |     |      |      | 5.5   |      | 32.8  |     |
| Green Ratio (g/C)                               |  |                 |               |               | 0.45  |                                 | 0.58    | 0.62  |     |      |      | 0.28  |      | 0.28  |     |
| Capacity (c), veh/h                             |  |                 |               |               | 1604  |                                 | 422     | 2280  |     |      |      | 965   |      | 450   |     |
| Volume-to-Capacity Ratio (X)                    |  |                 |               |               | 0.555 |                                 | 0.770   | 0.530 |     |      |      | 0.211 |      | 0.974 |     |
| Back of Queue (Q), ft/ln (90 th percentile)     |  |                 |               |               | 341.9 |                                 | 136.6   | 397.4 |     |      |      | 102.8 |      | 558.4 |     |
| Back of Queue (Q), veh/ln (90 th percentile)    |  |                 |               |               | 13.6  |                                 | 5.4     | 15.8  |     |      |      | 4.0   |      | 22.0  |     |
| Queue Storage Ratio (RQ) (90 th percentile)     |  |                 |               |               | 0.68  |                                 | 0.50    | 0.57  |     |      |      | 0.29  |      | 1.60  |     |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               |               | 26.7  |                                 | 19.0    | 23.6  |     |      |      | 32.8  |      | 42.6  |     |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               |               | 1.1   |                                 | 0.9     | 0.1   |     |      |      | 0.2   |      | 35.7  |     |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               |               | 0.0   |                                 | 0.0     | 0.0   |     |      |      | 0.0   |      | 0.0   |     |
| Control Delay (d), s/veh                        |  |                 |               |               | 27.8  | 0.0                             | 20.0    | 23.7  |     |      |      | 32.9  |      | 78.3  |     |
| Level of Service (LOS)                          |  |                 |               |               | C     | A                               | B       | C     |     |      |      | C     |      | E     |     |
| Approach Delay, s/veh / LOS                     |  |                 |               | 19.2          |       | B                               | 22.9    |       | C   | 0.0  |      |       | 63.9 |       | E   |
| Intersection Delay, s/veh / LOS                 |  |                 |               | 29.1          |       |                                 |         | C     |     |      |      |       |      |       |     |
| <b>Multimodal Results</b>                       |  |                 |               | EB            |       |                                 | WB      |       |     | NB   |      |       | SB   |       |     |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.40          |       | A                               | 1.88    |       | B   | 2.32 |      | B     | 2.33 |       | B   |
| Bicycle LOS Score / LOS                         |  |                 |               | 1.46          |       | A                               | 1.79    |       | B   |      |      |       |      | F     |     |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |             |       |                 |                                 |       |      |     |      |       |     |       |     |
|---|--|-----------------|---------------|-------------|-------|-----------------|---------------------------------|-------|------|-----|------|-------|-----|-------|-----|
| <b>General Information</b>                      |  |                 |               |             |       |                 | <b>Intersection Information</b> |       |      |     |      |       |     |       |     |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |             |       |                 | Duration, h                     | 0.25  |      |     |      |       |     |       |     |
| Analyst   | DBZ                                    | Analysis Date   | Mar 25, 2018  |             |       | Area Type       | Other                           |       |      |     |      |       |     |       |     |
| Jurisdiction                                    |  | Time Period     | AM Peak       |             |       | PHF             | 0.95                            |       |      |     |      |       |     |       |     |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2030 Build  |       | Analysis Period | 1> 7:00                         |       |      |     |      |       |     |       |     |
| Intersection                                    | I 265 SB Ramps                         |                 | File Name     | AM 30 B.xus |       |                 |                                 |       |      |     |      |       |     |       |     |
| Project Description                             | Covington by the Park                  |                 |               |             |       |                 |                                 |       |      |     |      |       |     |       |     |
| <b>Demand Information</b>                       |  |                 |               | EB          |       |                 | WB                              |       |      | NB  |      | SB    |     |       |     |
| Approach Movement                               |  |                 |               | L           | T     | R               | L                               | T     | R    | L   | T    | R     | L   | T     | R   |
| Demand (v), veh/h                               |  |                 |               |             | 802   | 347             | 368                             | 1264  |      |     |      |       | 239 |       | 416 |
| <b>Signal Information</b>                       |  |                 |               |             |       |                 |                                 |       |      |     |      |       |     |       |     |
| Cycle, s  | 120.0                                  | Reference Phase | 2             |             |       |                 |                                 |       |      |     |      |       |     |       |     |
| Offset, s                                       | 0                                      | Reference Point | End           |             |       |                 |                                 |       |      |     |      |       |     |       |     |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On            | Green       | 15.1  | 52.7            | 34.0                            | 0.0   | 0.0  | 0.0 |      |       |     |       |     |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            | Yellow      | 3.5   | 4.3             | 3.5                             | 0.0   | 0.0  | 0.0 |      |       |     |       |     |
|   |  |                 |               | Red         | 2.8   | 1.6             | 2.5                             | 0.0   | 0.0  | 0.0 |      |       |     |       |     |
| <b>Timer Results</b>                            |  |                 |               | EBL         | EBT   | WBL             | WBT                             | NBL   | NBT  | SBL | SBT  |       |     |       |     |
| Assigned Phase                                  |  |                 |               |             | 2     | 1               | 6                               |       |      |     |      | 4     |     |       |     |
| Case Number                                     |  |                 |               |             | 7.3   | 1.0             | 4.0                             |       |      |     |      | 9.0   |     |       |     |
| Phase Duration, s                               |  |                 |               |             | 58.6  | 21.4            | 80.0                            |       |      |     |      | 40.0  |     |       |     |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               |             | 5.9   | 6.3             | 5.9                             |       |      |     |      | 6.0   |     |       |     |
| Max Allow Headway (MAH), s                      |  |                 |               |             | 0.0   | 4.0             | 0.0                             |       |      |     |      | 5.2   |     |       |     |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               |             |       | 14.5            |                                 |       |      |     | 34.8 |       |     |       |     |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               |             | 0.0   | 0.5             | 0.0                             |       |      |     | 0.0  |       |     |       |     |
| Phase Call Probability                          |  |                 |               |             |       | 1.00            |                                 |       |      |     | 1.00 |       |     |       |     |
| Max Out Probability                             |  |                 |               |             |       | 0.94            |                                 |       |      |     | 1.00 |       |     |       |     |
| <b>Movement Group Results</b>                   |  |                 |               | EB          |       |                 | WB                              |       |      | NB  |      | SB    |     |       |     |
| Approach Movement                               |  |                 |               | L           | T     | R               | L                               | T     | R    | L   | T    | R     | L   | T     | R   |
| Assigned Movement                               |  |                 |               |             | 2     | 12              | 1                               | 6     |      |     |      | 7     |     | 14    |     |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               |             | 924   | 400             | 366                             | 1259  |      |     |      | 252   |     | 438   |     |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               |             | 1783  |                 | 1781                            | 1854  |      |     |      | 1702  |     | 1587  |     |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               |             | 24.5  |                 | 12.5                            | 31.7  |      |     |      | 6.9   |     | 32.8  |     |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               |             | 24.5  |                 | 12.5                            | 31.7  |      |     |      | 6.9   |     | 32.8  |     |
| Green Ratio (g/C)                               |  |                 |               |             | 0.44  |                 | 0.58                            | 0.62  |      |     |      | 0.28  |     | 0.28  |     |
| Capacity (c), veh/h                             |  |                 |               |             | 1566  |                 | 426                             | 2290  |      |     |      | 965   |     | 450   |     |
| Volume-to-Capacity Ratio (X)                    |  |                 |               |             | 0.590 |                 | 0.860                           | 0.550 |      |     |      | 0.261 |     | 0.974 |     |
| Back of Queue (Q), ft/ln (90 th percentile)     |  |                 |               |             | 357.6 |                 | 155.2                           | 403.7 |      |     |      | 126.9 |     | 558.4 |     |
| Back of Queue (Q), veh/ln (90 th percentile)    |  |                 |               |             | 14.2  |                 | 6.1                             | 16.0  |      |     |      | 4.9   |     | 22.0  |     |
| Queue Storage Ratio (RQ) (90 th percentile)     |  |                 |               |             | 0.72  |                 | 0.56                            | 0.58  |      |     |      | 0.36  |     | 1.60  |     |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               |             | 27.6  |                 | 21.3                            | 23.8  |      |     |      | 33.3  |     | 42.6  |     |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               |             | 1.3   |                 | 1.4                             | 0.1   |      |     |      | 0.2   |     | 35.7  |     |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               |             | 0.0   |                 | 0.0                             | 0.0   |      |     |      | 0.0   |     | 0.0   |     |
| Control Delay (d), s/veh                        |  |                 |               |             | 28.9  | 0.0             | 22.7                            | 23.9  |      |     |      | 33.5  |     | 78.3  |     |
| Level of Service (LOS)                          |  |                 |               |             | C     | A               | C                               | C     |      |     |      | C     |     | E     |     |
| Approach Delay, s/veh / LOS                     |  |                 |               | 20.2        | C     |                 | 23.6                            | C     | 0.0  |     |      | 61.9  |     | E     |     |
| Intersection Delay, s/veh / LOS                 |  |                 |               | 29.6        |       |                 |                                 | C     |      |     |      |       |     |       |     |
| <b>Multimodal Results</b>                       |  |                 |               | EB          |       |                 | WB                              |       |      | NB  |      | SB    |     |       |     |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.40        | A     |                 | 1.88                            | B     | 2.32 | B   |      | 2.33  |     | B     |     |
| Bicycle LOS Score / LOS                         |  |                 |               | 1.49        | A     |                 | 1.90                            | B     |      |     |      |       |     | F     |     |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |           |       |                 |                                 |       |     |      |     |      |       |   |       |
|---|--|-----------------|---------------|-----------|-------|-----------------|---------------------------------|-------|-----|------|-----|------|-------|---|-------|
| <b>General Information</b>                      |  |                 |               |           |       |                 | <b>Intersection Information</b> |       |     |      |     |      |       |   |       |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |           |       |                 | Duration, h                     | 0.25  |     |      |     |      |       |   |       |
| Analyst   | DBZ                                    | Analysis Date   | 3/8/2018      |           |       | Area Type       | Other                           |       |     |      |     |      |       |   |       |
| Jurisdiction                                    |  | Time Period     | PM Peak       |           |       | PHF             | 0.96                            |       |     |      |     |      |       |   |       |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2018      |       | Analysis Period | 1> 4:00                         |       |     |      |     |      |       |   |       |
| Intersection                                    | I 265 SB Ramps                         |                 | File Name     | PM 18.xus |       |                 |                                 |       |     |      |     |      |       |   |       |
| Project Description                             | Covington by the Park                  |                 |               |           |       |                 |                                 |       |     |      |     |      |       |   |       |
| <b>Demand Information</b>                       |  |                 |               | EB        |       |                 | WB                              |       |     | NB   |     | SB   |       |   |       |
| Approach Movement                               |  |                 |               | L         | T     | R               | L                               | T     | R   | L    | T   | R    | L     | T | R     |
| Demand (v), veh/h                               |  |                 |               |           | 768   | 456             | 160                             | 457   |     |      |     |      | 511   |   | 410   |
| <b>Signal Information</b>                       |  |                 |               |           |       |                 |                                 |       |     |      |     |      |       |   |       |
| Cycle, s  | 120.0                                  | Reference Phase | 2             |           |       |                 |                                 |       |     |      |     |      |       |   |       |
| Offset, s                                       | 0                                      | Reference Point | End           |           |       |                 |                                 |       |     |      |     |      |       |   |       |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On            | Green     | 10.0  | 55.0            | 36.8                            | 0.0   | 0.0 | 0.0  |     |      |       |   |       |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            | Yellow    | 3.5   | 4.3             | 3.5                             | 0.0   | 0.0 | 0.0  |     |      |       |   |       |
|   |  |                 |               | Red       | 2.8   | 1.6             | 2.5                             | 0.0   | 0.0 | 0.0  |     |      |       |   |       |
| <b>Timer Results</b>                            |  |                 |               | EBL       | EBT   | WBL             | WBT                             | NBL   | NBT | SBL  | SBT |      |       |   |       |
| Assigned Phase                                  |  |                 |               |           | 2     | 1               | 6                               |       |     |      |     | 4    |       |   |       |
| Case Number                                     |  |                 |               |           | 7.3   | 1.0             | 4.0                             |       |     |      |     | 9.0  |       |   |       |
| Phase Duration, s                               |  |                 |               |           | 60.9  | 16.3            | 77.2                            |       |     |      |     | 42.8 |       |   |       |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               |           | 5.9   | 6.3             | 5.9                             |       |     |      |     | 6.0  |       |   |       |
| Max Allow Headway (MAH), s                      |  |                 |               |           | 0.0   | 4.0             | 0.0                             |       |     |      |     | 5.1  |       |   |       |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               |           |       | 7.3             |                                 |       |     |      |     | 32.1 |       |   |       |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               |           | 0.0   | 0.4             | 0.0                             |       |     |      |     | 4.8  |       |   |       |
| Phase Call Probability                          |  |                 |               |           |       | 1.00            |                                 |       |     |      |     | 1.00 |       |   |       |
| Max Out Probability                             |  |                 |               |           |       | 0.00            |                                 |       |     |      |     | 0.41 |       |   |       |
| <b>Movement Group Results</b>                   |  |                 |               | EB        |       |                 | WB                              |       |     | NB   |     | SB   |       |   |       |
| Approach Movement                               |  |                 |               | L         | T     | R               | L                               | T     | R   | L    | T   | R    | L     | T | R     |
| Assigned Movement                               |  |                 |               |           | 2     | 12              | 1                               | 6     |     |      |     |      | 7     |   | 14    |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               |           | 933   | 554             | 166                             | 473   |     |      |     |      | 532   |   | 427   |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               |           | 1811  |                 | 1795                            | 1726  |     |      |     |      | 1743  |   | 1609  |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               |           | 20.1  |                 | 5.3                             | 12.2  |     |      |     |      | 15.0  |   | 30.1  |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               |           | 20.1  |                 | 5.3                             | 12.2  |     |      |     |      | 15.0  |   | 30.1  |
| Green Ratio (g/C)                               |  |                 |               |           | 0.46  |                 | 0.56                            | 0.59  |     |      |     |      | 0.31  |   | 0.31  |
| Capacity (c), veh/h                             |  |                 |               |           | 1660  |                 | 385                             | 2050  |     |      |     |      | 1070  |   | 494   |
| Volume-to-Capacity Ratio (X)                    |  |                 |               |           | 0.562 |                 | 0.430                           | 0.231 |     |      |     |      | 0.497 |   | 0.865 |
| Back of Queue (Q), ft/ln (90 th percentile)     |  |                 |               |           | 262   |                 | 104.2                           | 205.6 |     |      |     |      | 236.9 |   | 440.5 |
| Back of Queue (Q), veh/ln (90 th percentile)    |  |                 |               |           | 10.4  |                 | 4.1                             | 8.1   |     |      |     |      | 9.4   |   | 17.6  |
| Queue Storage Ratio (RQ) (90 th percentile)     |  |                 |               |           | 0.52  |                 | 0.38                            | 0.29  |     |      |     |      | 0.68  |   | 1.26  |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               |           | 19.0  |                 | 17.2                            | 21.0  |     |      |     |      | 34.0  |   | 39.2  |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               |           | 1.0   |                 | 0.7                             | 0.2   |     |      |     |      | 0.5   |   | 12.0  |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               |           | 0.0   |                 | 0.0                             | 0.0   |     |      |     |      | 0.0   |   | 0.0   |
| Control Delay (d), s/veh                        |  |                 |               |           | 20.0  | 0.0             | 17.8                            | 21.3  |     |      |     |      | 34.5  |   | 51.3  |
| Level of Service (LOS)                          |  |                 |               |           | C     | A               | B                               | C     |     |      |     |      | C     |   | D     |
| Approach Delay, s/veh / LOS                     |  |                 |               | 12.6      |       | B               | 20.4                            |       | C   | 0.0  |     |      | 42.0  |   | D     |
| Intersection Delay, s/veh / LOS                 |  |                 |               | 23.3      |       |                 |                                 | C     |     |      |     |      |       |   |       |
| <b>Multimodal Results</b>                       |  |                 |               | EB        |       |                 | WB                              |       |     | NB   |     | SB   |       |   |       |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.40      |       | A               | 1.89                            |       | B   | 2.32 |     | B    | 2.33  |   | B     |
| Bicycle LOS Score / LOS                         |  |                 |               | 1.54      |       | B               | 1.02                            |       | A   |      |     |      |       | F |       |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |               |       |                 |                                 |       |     |      |     |      |       |   |       |
|---|--|-----------------|---------------|---------------|-------|-----------------|---------------------------------|-------|-----|------|-----|------|-------|---|-------|
| <b>General Information</b>                      |  |                 |               |               |       |                 | <b>Intersection Information</b> |       |     |      |     |      |       |   |       |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |               |       |                 | Duration, h                     | 0.25  |     |      |     |      |       |   |       |
| Analyst   | DBZ                                    | Analysis Date   | Mar 25, 2018  |               |       | Area Type       | Other                           |       |     |      |     |      |       |   |       |
| Jurisdiction                                    |  | Time Period     | PM Peak       |               |       | PHF             | 0.96                            |       |     |      |     |      |       |   |       |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2030 No Build |       | Analysis Period | 1> 4:00                         |       |     |      |     |      |       |   |       |
| Intersection                                    | I 265 SB Ramps                         |                 | File Name     | PM 30 NB.xus  |       |                 |                                 |       |     |      |     |      |       |   |       |
| Project Description                             | Covington by the Park                  |                 |               |               |       |                 |                                 |       |     |      |     |      |       |   |       |
| <b>Demand Information</b>                       |  |                 |               | EB            |       |                 | WB                              |       |     | NB   |     |      | SB    |   |       |
| Approach Movement                               |  |                 |               | L             | T     | R               | L                               | T     | R   | L    | T   | R    | L     | T | R     |
| Demand (v), veh/h                               |  |                 |               |               | 1185  | 599             | 203                             | 682   |     |      |     |      | 648   |   | 634   |
| <b>Signal Information</b>                       |  |                 |               |               |       |                 |                                 |       |     |      |     |      |       |   |       |
| Cycle, s  | 120.0                                  | Reference Phase | 2             |               |       |                 |                                 |       |     |      |     |      |       |   |       |
| Offset, s                                       | 0                                      | Reference Point | End           |               |       |                 |                                 |       |     |      |     |      |       |   |       |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On            | Green         | 10.1  | 47.7            | 44.0                            | 0.0   | 0.0 | 0.0  |     |      |       |   |       |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            | Yellow        | 3.5   | 4.3             | 3.5                             | 0.0   | 0.0 | 0.0  |     |      |       |   |       |
|   |  |                 |               | Red           | 2.8   | 1.6             | 2.5                             | 0.0   | 0.0 | 0.0  |     |      |       |   |       |
| <b>Timer Results</b>                            |  |                 |               | EBL           | EBT   | WBL             | WBT                             | NBL   | NBT | SBL  | SBT |      |       |   |       |
| Assigned Phase                                  |  |                 |               |               | 2     | 1               | 6                               |       |     |      |     | 4    |       |   |       |
| Case Number                                     |  |                 |               |               | 7.3   | 1.0             | 4.0                             |       |     |      |     | 9.0  |       |   |       |
| Phase Duration, s                               |  |                 |               |               | 53.6  | 16.4            | 70.0                            |       |     |      |     | 50.0 |       |   |       |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               |               | 5.9   | 6.3             | 5.9                             |       |     |      |     | 6.0  |       |   |       |
| Max Allow Headway (MAH), s                      |  |                 |               |               | 0.0   | 4.0             | 0.0                             |       |     |      |     | 5.1  |       |   |       |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               |               |       | 9.8             |                                 |       |     |      |     | 46.0 |       |   |       |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               |               | 0.0   | 0.2             | 0.0                             |       |     |      |     | 0.0  |       |   |       |
| Phase Call Probability                          |  |                 |               |               |       | 1.00            |                                 |       |     |      |     | 1.00 |       |   |       |
| Max Out Probability                             |  |                 |               |               |       | 1.00            |                                 |       |     |      |     | 1.00 |       |   |       |
| <b>Movement Group Results</b>                   |  |                 |               | EB            |       |                 | WB                              |       |     | NB   |     |      | SB    |   |       |
| Approach Movement                               |  |                 |               | L             | T     | R               | L                               | T     | R   | L    | T   | R    | L     | T | R     |
| Assigned Movement                               |  |                 |               |               | 2     | 12              | 1                               | 6     |     |      |     |      | 7     |   | 14    |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               |               | 1315  | 665             | 214                             | 718   |     |      |     |      | 675   |   | 660   |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               |               | 1916  |                 | 1795                            | 1760  |     |      |     |      | 1743  |   | 1672  |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               |               | 37.3  |                 | 7.8                             | 20.8  |     |      |     |      | 18.2  |   | 44.0  |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               |               | 37.3  |                 | 7.8                             | 20.8  |     |      |     |      | 18.2  |   | 44.0  |
| Green Ratio (g/C)                               |  |                 |               |               | 0.40  |                 | 0.50                            | 0.53  |     |      |     |      | 0.37  |   | 0.37  |
| Capacity (c), veh/h                             |  |                 |               |               | 1524  |                 | 247                             | 1880  |     |      |     |      | 1278  |   | 613   |
| Volume-to-Capacity Ratio (X)                    |  |                 |               |               | 0.863 |                 | 0.865                           | 0.382 |     |      |     |      | 0.528 |   | 1.077 |
| Back of Queue (Q), ft/ln (90 th percentile)     |  |                 |               |               | 513.1 |                 | 179.2                           | 337   |     |      |     |      | 275.4 |   | 885.3 |
| Back of Queue (Q), veh/ln (90 th percentile)    |  |                 |               |               | 20.4  |                 | 7.1                             | 13.3  |     |      |     |      | 10.9  |   | 35.4  |
| Queue Storage Ratio (RQ) (90 th percentile)     |  |                 |               |               | 1.03  |                 | 0.65                            | 0.48  |     |      |     |      | 0.79  |   | 2.53  |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               |               | 31.0  |                 | 29.0                            | 29.8  |     |      |     |      | 29.8  |   | 38.0  |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               |               | 3.7   |                 | 16.1                            | 0.5   |     |      |     |      | 0.5   |   | 58.9  |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               |               | 0.0   |                 | 0.0                             | 0.0   |     |      |     |      | 0.0   |   | 0.0   |
| Control Delay (d), s/veh                        |  |                 |               |               | 34.8  | 0.0             | 45.1                            | 30.3  |     |      |     |      | 30.4  |   | 96.9  |
| Level of Service (LOS)                          |  |                 |               |               | C     | A               | D                               | C     |     |      |     |      | C     |   | F     |
| Approach Delay, s/veh / LOS                     |  |                 |               | 23.1          |       | C               | 33.7                            |       | C   | 0.0  |     |      | 63.3  |   | E     |
| Intersection Delay, s/veh / LOS                 |  |                 |               | 38.1          |       |                 |                                 | D     |     |      |     |      |       |   |       |
| <b>Multimodal Results</b>                       |  |                 |               | EB            |       |                 | WB                              |       |     | NB   |     |      | SB    |   |       |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.40          |       | A               | 1.90                            |       | B   | 2.32 |     | B    | 2.33  |   | B     |
| Bicycle LOS Score / LOS                         |  |                 |               | 2.02          |       | B               | 1.25                            |       | A   |      |     |      |       | F |       |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |             |       |                                 |         |       |      |     |     |       |    |       |     |
|---|--|-----------------|---------------|-------------|-------|---------------------------------|---------|-------|------|-----|-----|-------|----|-------|-----|
| <b>General Information</b>                      |  |                 |               |             |       | <b>Intersection Information</b> |         |       |      |     |     |       |    |       |     |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |             |       | Duration, h                     | 0.25    |       |      |     |     |       |    |       |     |
| Analyst   | DBZ                                    | Analysis Date   | Mar 25, 2018  |             |       | Area Type                       | Other   |       |      |     |     |       |    |       |     |
| Jurisdiction                                    |  | Time Period     | PM Peak       |             |       | PHF                             | 0.96    |       |      |     |     |       |    |       |     |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2030 Build  |       | Analysis Period                 | 1> 4:00 |       |      |     |     |       |    |       |     |
| Intersection                                    | I 265 SB Ramps                         |                 | File Name     | PM 30 B.xus |       |                                 |         |       |      |     |     |       |    |       |     |
| Project Description                             | Covington by the Park                  |                 |               |             |       |                                 |         |       |      |     |     |       |    |       |     |
| <b>Demand Information</b>                       |  |                 |               | EB          |       |                                 | WB      |       |      | NB  |     |       | SB |       |     |
| Approach Movement                               |  |                 |               | L           | T     | R                               | L       | T     | R    | L   | T   | R     | L  | T     | R   |
| Demand (v), veh/h                               |  |                 |               |             | 1279  | 599                             | 236     | 738   |      |     |     | 798   |    |       | 634 |
| <b>Signal Information</b>                       |  |                 |               |             |       |                                 |         |       |      |     |     |       |    |       |     |
| Cycle, s  | 120.0                                  | Reference Phase | 2             |             |       |                                 |         |       |      |     |     |       |    |       |     |
| Offset, s                                       | 0                                      | Reference Point | End           |             |       |                                 |         |       |      |     |     |       |    |       |     |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On            | Green       | 13.7  | 44.1                            | 44.0    | 0.0   | 0.0  | 0.0 |     |       |    |       |     |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            | Yellow      | 3.5   | 4.3                             | 3.5     | 0.0   | 0.0  | 0.0 |     |       |    |       |     |
|   |  |                 |               | Red         | 2.8   | 1.6                             | 2.5     | 0.0   | 0.0  | 0.0 |     |       |    |       |     |
| <b>Timer Results</b>                            |  |                 |               | EBL         | EBT   | WBL                             | WBT     | NBL   | NBT  | SBL | SBT |       |    |       |     |
| Assigned Phase                                  |  |                 |               |             | 2     | 1                               | 6       |       |      |     |     | 4     |    |       |     |
| Case Number                                     |  |                 |               |             | 7.3   | 1.0                             | 4.0     |       |      |     |     | 9.0   |    |       |     |
| Phase Duration, s                               |  |                 |               |             | 50.0  | 20.0                            | 70.0    |       |      |     |     | 50.0  |    |       |     |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               |             | 5.9   | 6.3                             | 5.9     |       |      |     |     | 6.0   |    |       |     |
| Max Allow Headway (MAH), s                      |  |                 |               |             | 0.0   | 4.0                             | 0.0     |       |      |     |     | 5.1   |    |       |     |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               |             |       | 14.5                            |         |       |      |     |     | 46.0  |    |       |     |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               |             | 0.0   | 0.0                             | 0.0     |       |      |     |     | 0.0   |    |       |     |
| Phase Call Probability                          |  |                 |               |             |       | 1.00                            |         |       |      |     |     | 1.00  |    |       |     |
| Max Out Probability                             |  |                 |               |             |       | 1.00                            |         |       |      |     |     | 1.00  |    |       |     |
| <b>Movement Group Results</b>                   |  |                 |               | EB          |       |                                 | WB      |       |      | NB  |     |       | SB |       |     |
| Approach Movement                               |  |                 |               | L           | T     | R                               | L       | T     | R    | L   | T   | R     | L  | T     | R   |
| Assigned Movement                               |  |                 |               |             | 2     | 12                              | 1       | 6     |      |     |     | 7     |    | 14    |     |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               |             | 1413  | 662                             | 248     | 777   |      |     |     | 831   |    | 660   |     |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               |             | 1933  |                                 | 1795    | 1768  |      |     |     | 1743  |    | 1672  |     |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               |             | 43.7  |                                 | 12.5    | 22.5  |      |     |     | 23.8  |    | 44.0  |     |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               |             | 43.7  |                                 | 12.5    | 22.5  |      |     |     | 23.8  |    | 44.0  |     |
| Green Ratio (g/C)                               |  |                 |               |             | 0.37  |                                 | 0.50    | 0.53  |      |     |     | 0.37  |    | 0.37  |     |
| Capacity (c), veh/h                             |  |                 |               |             | 1420  |                                 | 266     | 1889  |      |     |     | 1278  |    | 613   |     |
| Volume-to-Capacity Ratio (X)                    |  |                 |               |             | 0.995 |                                 | 0.933   | 0.411 |      |     |     | 0.650 |    | 1.077 |     |
| Back of Queue (Q), ft/ln (90 th percentile)     |  |                 |               |             | 634.4 |                                 | 362.8   | 361.4 |      |     |     | 348.2 |    | 885.3 |     |
| Back of Queue (Q), veh/ln (90 th percentile)    |  |                 |               |             | 25.2  |                                 | 14.4    | 14.2  |      |     |     | 13.8  |    | 35.4  |     |
| Queue Storage Ratio (RQ) (90 th percentile)     |  |                 |               |             | 1.27  |                                 | 1.32    | 0.52  |      |     |     | 0.99  |    | 2.53  |     |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               |             | 33.6  |                                 | 42.9    | 30.3  |      |     |     | 31.6  |    | 38.0  |     |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               |             | 15.3  |                                 | 32.5    | 0.5   |      |     |     | 1.3   |    | 58.9  |     |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               |             | 0.0   |                                 | 0.0     | 0.0   |      |     |     | 0.0   |    | 0.0   |     |
| Control Delay (d), s/veh                        |  |                 |               |             | 48.8  | 0.0                             | 75.4    | 30.8  |      |     |     | 32.9  |    | 96.9  |     |
| Level of Service (LOS)                          |  |                 |               |             | D     | A                               | E       | C     |      |     |     | C     |    | F     |     |
| Approach Delay, s/veh / LOS                     |  |                 |               | 33.3        |       | C                               | 41.6    | D     | 0.0  |     |     | 61.3  |    | E     |     |
| Intersection Delay, s/veh / LOS                 |  |                 |               | 44.2        |       |                                 |         | D     |      |     |     |       |    |       |     |
| <b>Multimodal Results</b>                       |  |                 |               | EB          |       |                                 | WB      |       |      | NB  |     |       | SB |       |     |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.41        |       | A                               | 1.90    | B     | 2.32 |     | B   | 2.33  |    | B     |     |
| Bicycle LOS Score / LOS                         |  |                 |               | 2.10        |       | B                               | 1.32    | A     |      |     |     |       | F  |       |     |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary     |  |                 |               |           |       |                 |                                 |      |      |      |     |    |  |
|--|--|-----------------|---------------|-----------|-------|-----------------|---------------------------------|------|------|------|-----|----|--|
| <b>General Information</b>                       |  |                 |               |           |       |                 | <b>Intersection Information</b> |      |      |      |     |    |  |
| Agency   | Diane B. Zimmerman Traffic Engineering |                 |               |           |       |                 | Duration, h                     | 0.25 |      |      |     |    |  |
| Analyst  | DBZ                                    | Analysis Date   | 3/8/2018      |           |       | Area Type       | Other                           |      |      |      |     |    |  |
| Jurisdiction                                     |  | Time Period     | AM Peak       |           |       | PHF             | 0.95                            |      |      |      |     |    |  |
| Urban Street                                     | Taylorsville Road                      |                 | Analysis Year | 2018      |       | Analysis Period | 1> 7:00                         |      |      |      |     |    |  |
| Intersection                                     | I 265 NB Ramps                         |                 | File Name     | AM 18.xus |       |                 |                                 |      |      |      |     |    |  |
| Project Description                              | Covington by the Park                  |                 |               |           |       |                 |                                 |      |      |      |     |    |  |
| <b>Demand Information</b>                        |  |                 |               | EB        |       |                 | WB                              |      |      | NB   |     | SB |  |
| Approach Movement                                | L                                      | T               | R             | L         | T     | R               | L                               | T    | R    | L    | T   | R  |  |
| Demand ( v ), veh/h                              | 390                                    | 317             |               |           | 695   | 625             | 450                             |      | 206  |      |     |    |  |
| <b>Signal Information</b>                        |  |                 |               |           |       |                 |                                 |      |      |      |     |    |  |
| Cycle, s   | 120.0                                  | Reference Phase | 2             |           |       |                 |                                 |      |      |      |     |    |  |
| Offset, s  | 0                                      | Reference Point | End           | Green     | 16.9  | 54.3            | 33.8                            | 0.0  | 0.0  | 0.0  |     |    |  |
| Uncoordinated                                    | No                                     | Simult. Gap E/W | On            | Yellow    | 3.5   | 3.5             | 3.5                             | 0.0  | 0.0  | 0.0  |     |    |  |
| Force Mode                                       | Fixed                                  | Simult. Gap N/S | On            | Red       | 1.5   | 1.5             | 1.5                             | 0.0  | 0.0  | 0.0  |     |    |  |
| <b>Timer Results</b>                             |  |                 |               | EBL       | EBT   | WBL             | WBT                             | NBL  | NBT  | SBL  | SBT |    |  |
| Assigned Phase                                   | 5                                      |                 | 2             |           |       |                 | 6                               |      | 8    |      |     |    |  |
| Case Number                                      | 1.0                                    |                 | 4.0           |           |       |                 | 7.3                             |      | 9.0  |      |     |    |  |
| Phase Duration, s                                | 21.9                                   |                 | 81.2          |           |       |                 | 59.3                            |      | 38.8 |      |     |    |  |
| Change Period, ( Y+R <sub>c</sub> ), s           | 5.0                                    |                 | 5.0           |           |       |                 | 5.0                             |      | 5.0  |      |     |    |  |
| Max Allow Headway ( MAH ), s                     | 4.0                                    |                 | 0.0           |           |       |                 | 0.0                             |      | 4.1  |      |     |    |  |
| Queue Clearance Time ( g <sub>s</sub> ), s       | 15.4                                   |                 |               |           |       |                 |                                 |      | 32.5 |      |     |    |  |
| Green Extension Time ( g <sub>e</sub> ), s       | 1.5                                    |                 | 0.0           |           |       |                 | 0.0                             |      | 1.2  |      |     |    |  |
| Phase Call Probability                           | 1.00                                   |                 |               |           |       |                 |                                 |      | 1.00 |      |     |    |  |
| Max Out Probability                              | 0.00                                   |                 |               |           |       |                 |                                 |      | 0.90 |      |     |    |  |
| <b>Movement Group Results</b>                    |  |                 |               | EB        |       |                 | WB                              |      |      | NB   |     | SB |  |
| Approach Movement                                | L                                      | T               | R             | L         | T     | R               | L                               | T    | R    | L    | T   | R  |  |
| Assigned Movement                                | 5                                      | 2               |               |           | 6     | 16              | 3                               |      | 18   |      |     |    |  |
| Adjusted Flow Rate ( v ), veh/h                  | 441                                    | 359             |               |           | 732   | 658             | 474                             |      | 217  |      |     |    |  |
| Adjusted Saturation Flow Rate ( s ), veh/h/ln    | 1795                                   | 1697            |               |           | 1724  |                 | 1795                            |      |      |      |     |    |  |
| Queue Service Time ( g <sub>s</sub> ), s         | 13.4                                   | 7.8             |               |           | 17.7  |                 | 30.5                            |      |      |      |     |    |  |
| Cycle Queue Clearance Time ( g <sub>c</sub> ), s | 13.4                                   | 7.8             |               |           | 17.7  |                 | 30.5                            |      |      |      |     |    |  |
| Green Ratio ( g/C )                              | 0.61                                   | 0.64            |               |           | 0.45  |                 | 0.28                            |      |      |      |     |    |  |
| Capacity ( c ), veh/h                            | 536                                    | 2156            |               |           | 1561  |                 | 520                             |      |      |      |     |    |  |
| Volume-to-Capacity Ratio ( X )                   | 0.823                                  | 0.166           |               |           | 0.469 |                 | 0.911                           |      |      |      |     |    |  |
| Back of Queue ( Q ), ft/ln ( 90 th percentile)   | 267.9                                  | 130.7           |               |           | 262.6 |                 | 519.1                           |      |      |      |     |    |  |
| Back of Queue ( Q ), veh/ln ( 90 th percentile)  | 10.6                                   | 5.1             |               |           | 10.4  |                 | 20.6                            |      |      |      |     |    |  |
| Queue Storage Ratio ( RQ ) ( 90 th percentile)   | 1.34                                   | 0.19            |               |           | 0.53  |                 | 1.04                            |      |      |      |     |    |  |
| Uniform Delay ( d <sub>1</sub> ), s/veh          | 19.8                                   | 14.8            |               |           | 22.8  |                 | 41.1                            |      |      |      |     |    |  |
| Incremental Delay ( d <sub>2</sub> ), s/veh      | 4.1                                    | 0.2             |               |           | 1.0   |                 | 18.0                            |      |      |      |     |    |  |
| Initial Queue Delay ( d <sub>3</sub> ), s/veh    | 0.0                                    | 0.0             |               |           | 0.0   |                 | 0.0                             |      |      |      |     |    |  |
| Control Delay ( d ), s/veh                       | 23.8                                   | 14.9            |               |           | 23.8  | 0.0             | 59.1                            |      | 0.0  |      |     |    |  |
| Level of Service (LOS)                           | C                                      | B               |               |           | C     | A               | E                               |      | A    |      |     |    |  |
| Approach Delay, s/veh / LOS                      | 19.9                                   |                 | B             | 12.5      |       | B               | 40.6                            |      | D    | 0.0  |     |    |  |
| Intersection Delay, s/veh / LOS                  | 21.3                                   |                 |               |           |       |                 | C                               |      |      |      |     |    |  |
| <b>Multimodal Results</b>                        |  |                 |               | EB        |       |                 | WB                              |      |      | NB   |     | SB |  |
| Pedestrian LOS Score / LOS                       | 1.66                                   |                 | B             | 1.40      |       | A               | 2.33                            |      | B    | 2.32 |     | B  |  |
| Bicycle LOS Score / LOS                          | 1.10                                   |                 | A             | 1.63      |       | B               |                                 |      | F    |      |     |    |  |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |               |       |                 |                                 |      |       |      |     |    |   |   |   |
|---|--|-----------------|---------------|---------------|-------|-----------------|---------------------------------|------|-------|------|-----|----|---|---|---|
| <b>General Information</b>                      |  |                 |               |               |       |                 | <b>Intersection Information</b> |      |       |      |     |    |   |   |   |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |               |       |                 | Duration, h                     | 0.25 |       |      |     |    |   |   |   |
| Analyst   | DBZ                                    | Analysis Date   | 3/8/2018      |               |       | Area Type       | Other                           |      |       |      |     |    |   |   |   |
| Jurisdiction                                    |  | Time Period     | AM Peak       |               |       | PHF             | 0.95                            |      |       |      |     |    |   |   |   |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2030 No Build |       | Analysis Period | 1> 7:00                         |      |       |      |     |    |   |   |   |
| Intersection                                    | I 265 NB Ramps                         |                 | File Name     | AM 30 NB.xus  |       |                 |                                 |      |       |      |     |    |   |   |   |
| Project Description                             | Covington by the Park                  |                 |               |               |       |                 |                                 |      |       |      |     |    |   |   |   |
| <b>Demand Information</b>                       |  |                 |               | EB            |       |                 | WB                              |      |       | NB   |     | SB |   |   |   |
| Approach Movement                               |  |                 |               | L             | T     | R               | L                               | T    | R     | L    | T   | R  | L | T | R |
| Demand (v), veh/h                               |  |                 |               | 540           | 428   |                 | 917                             | 793  | 579   | 261  |     |    |   |   |   |
| <b>Signal Information</b>                       |  |                 |               |               |       |                 |                                 |      |       |      |     |    |   |   |   |
| Cycle, s  | 120.0                                  | Reference Phase | 2             |               |       |                 |                                 |      |       |      |     |    |   |   |   |
| Offset, s                                       | 0                                      | Reference Point | End           | Green         | 32.0  | 36.0            | 37.0                            | 0.0  | 0.0   | 0.0  |     |    |   |   |   |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On            | Yellow        | 3.5   | 3.5             | 3.5                             | 0.0  | 0.0   | 0.0  |     |    |   |   |   |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            | Red           | 1.5   | 1.5             | 1.5                             | 0.0  | 0.0   | 0.0  |     |    |   |   |   |
| <b>Timer Results</b>                            |  |                 |               | EBL           | EBT   | WBL             | WBT                             | NBL  | NBT   | SBL  | SBT |    |   |   |   |
| Assigned Phase                                  |  |                 |               | 5             | 2     |                 | 6                               |      | 8     |      |     |    |   |   |   |
| Case Number                                     |  |                 |               | 1.0           | 4.0   |                 | 7.3                             |      | 9.0   |      |     |    |   |   |   |
| Phase Duration, s                               |  |                 |               | 37.0          | 78.0  |                 | 41.0                            |      | 42.0  |      |     |    |   |   |   |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               | 5.0           | 5.0   |                 | 5.0                             |      | 5.0   |      |     |    |   |   |   |
| Max Allow Headway (MAH), s                      |  |                 |               | 4.0           | 0.0   |                 | 0.0                             |      | 4.1   |      |     |    |   |   |   |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               | 35.0          |       |                 |                                 |      | 40.0  |      |     |    |   |   |   |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               | 0.0           | 0.0   |                 | 0.0                             |      | 0.0   |      |     |    |   |   |   |
| Phase Call Probability                          |  |                 |               | 1.00          |       |                 |                                 |      | 1.00  |      |     |    |   |   |   |
| Max Out Probability                             |  |                 |               | 1.00          |       |                 |                                 |      | 1.00  |      |     |    |   |   |   |
| <b>Movement Group Results</b>                   |  |                 |               | EB            |       |                 | WB                              |      |       | NB   |     | SB |   |   |   |
| Approach Movement                               |  |                 |               | L             | T     | R               | L                               | T    | R     | L    | T   | R  | L | T | R |
| Assigned Movement                               |  |                 |               | 5             | 2     |                 | 6                               | 16   | 3     |      | 18  |    |   |   |   |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               | 610           | 484   |                 | 965                             | 835  | 609   |      | 275 |    |   |   |   |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               | 1795          | 1714  |                 | 1750                            |      | 1795  |      |     |    |   |   |   |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               | 33.0          | 12.3  |                 | 32.0                            |      | 38.0  |      |     |    |   |   |   |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               | 33.0          | 12.3  |                 | 32.0                            |      | 38.0  |      |     |    |   |   |   |
| Green Ratio (g/C)                               |  |                 |               | 0.60          | 0.50  |                 | 0.30                            |      | 0.31  |      |     |    |   |   |   |
| Capacity (c), veh/h                             |  |                 |               | 578           | 1730  |                 | 1050                            |      | 569   |      |     |    |   |   |   |
| Volume-to-Capacity Ratio (X)                    |  |                 |               | 1.055         | 0.280 |                 | 0.919                           |      | 1.072 |      |     |    |   |   |   |
| Back of Queue (Q), ft/ln (90 th percentile)     |  |                 |               | 871.7         | 202.6 |                 | 509.2                           |      | 834.7 |      |     |    |   |   |   |
| Back of Queue (Q), veh/ln (90 th percentile)    |  |                 |               | 34.6          | 7.9   |                 | 20.2                            |      | 33.1  |      |     |    |   |   |   |
| Queue Storage Ratio (RQ) (90 th percentile)     |  |                 |               | 4.36          | 0.29  |                 | 1.02                            |      | 1.67  |      |     |    |   |   |   |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               | 49.1          | 19.4  |                 | 40.6                            |      | 41.0  |      |     |    |   |   |   |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               | 50.3          | 0.3   |                 | 14.0                            |      | 58.5  |      |     |    |   |   |   |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               | 0.0           | 0.0   |                 | 0.0                             |      | 0.0   |      |     |    |   |   |   |
| Control Delay (d), s/veh                        |  |                 |               | 99.4          | 19.8  |                 | 54.6                            | 0.0  | 99.5  |      | 0.0 |    |   |   |   |
| Level of Service (LOS)                          |  |                 |               | F             | B     |                 | D                               | A    | F     |      | A   |    |   |   |   |
| Approach Delay, s/veh / LOS                     |  |                 |               | 64.2          | E     | 29.3            | C                               | 68.6 | E     | 0.0  |     |    |   |   |   |
| Intersection Delay, s/veh / LOS                 |  |                 |               | 48.6          |       |                 | D                               |      |       |      |     |    |   |   |   |
| <b>Multimodal Results</b>                       |  |                 |               | EB            |       |                 | WB                              |      |       | NB   |     | SB |   |   |   |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.66          | B     | 1.42            | A                               | 2.33 | B     | 2.32 | B   |    |   |   |   |
| Bicycle LOS Score / LOS                         |  |                 |               | 1.33          | A     | 1.97            | B                               | F    |       |      |     |    |   |   |   |



Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |             |       |                                 |         |       |      |       |     |     |      |   |   |
|---|--|-----------------|---------------|-------------|-------|---------------------------------|---------|-------|------|-------|-----|-----|------|---|---|
| <b>General Information</b>                      |  |                 |               |             |       | <b>Intersection Information</b> |         |       |      |       |     |     |      |   |   |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |             |       | Duration, h                     | 0.25    |       |      |       |     |     |      |   |   |
| Analyst   | DBZ                                    | Analysis Date   | Mar 25, 2018  |             |       | Area Type                       | Other   |       |      |       |     |     |      |   |   |
| Jurisdiction                                    |  | Time Period     | AM Peak       |             |       | PHF                             | 0.95    |       |      |       |     |     |      |   |   |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2030 Build  |       | Analysis Period                 | 1> 7:00 |       |      |       |     |     |      |   |   |
| Intersection                                    | I 265 NB Ramps                         |                 | File Name     | AM 30 B.xus |       |                                 |         |       |      |       |     |     |      |   |   |
| Project Description                             | Covington by the Park                  |                 |               |             |       |                                 |         |       |      |       |     |     |      |   |   |
| <b>Demand Information</b>                       |  |                 |               | EB          |       |                                 | WB      |       |      | NB    |     |     | SB   |   |   |
| Approach Movement                               |  |                 |               | L           | T     | R                               | L       | T     | R    | L     | T   | R   | L    | T | R |
| Demand (v), veh/h                               |  |                 |               | 540         | 501   |                                 |         | 1053  | 929  | 579   |     | 278 |      |   |   |
| <b>Signal Information</b>                       |  |                 |               |             |       |                                 |         |       |      |       |     |     |      |   |   |
| Cycle, s  | 120.0                                  | Reference Phase | 2             |             |       |                                 |         |       |      |       |     |     |      |   |   |
| Offset, s                                       | 0                                      | Reference Point | End           | Green       | 32.0  | 36.0                            | 37.0    | 0.0   | 0.0  | 0.0   |     |     |      |   |   |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On            | Yellow      | 3.5   | 3.5                             | 3.5     | 0.0   | 0.0  | 0.0   |     |     |      |   |   |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            | Red         | 1.5   | 1.5                             | 1.5     | 0.0   | 0.0  | 0.0   |     |     |      |   |   |
| <b>Timer Results</b>                            |  |                 |               | EBL         | EBT   | WBL                             | WBT     | NBL   | NBT  | SBL   | SBT |     |      |   |   |
| Assigned Phase                                  |  |                 |               | 5           | 2     |                                 | 6       |       | 8    |       |     |     |      |   |   |
| Case Number                                     |  |                 |               | 1.0         | 4.0   |                                 | 7.3     |       | 9.0  |       |     |     |      |   |   |
| Phase Duration, s                               |  |                 |               | 37.0        | 78.0  |                                 | 41.0    |       | 42.0 |       |     |     |      |   |   |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               | 5.0         | 5.0   |                                 | 5.0     |       | 5.0  |       |     |     |      |   |   |
| Max Allow Headway (MAH), s                      |  |                 |               | 4.0         | 0.0   |                                 | 0.0     |       | 4.1  |       |     |     |      |   |   |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               | 35.0        |       |                                 |         |       | 40.0 |       |     |     |      |   |   |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               | 0.0         | 0.0   |                                 | 0.0     |       | 0.0  |       |     |     |      |   |   |
| Phase Call Probability                          |  |                 |               | 1.00        |       |                                 |         |       | 1.00 |       |     |     |      |   |   |
| Max Out Probability                             |  |                 |               | 1.00        |       |                                 |         |       | 1.00 |       |     |     |      |   |   |
| <b>Movement Group Results</b>                   |  |                 |               | EB          |       |                                 | WB      |       |      | NB    |     |     | SB   |   |   |
| Approach Movement                               |  |                 |               | L           | T     | R                               | L       | T     | R    | L     | T   | R   | L    | T | R |
| Assigned Movement                               |  |                 |               | 5           | 2     |                                 |         | 6     | 16   | 3     |     | 18  |      |   |   |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               | 610         | 566   |                                 |         | 1108  | 978  | 609   |     | 293 |      |   |   |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               | 1795        | 1725  |                                 |         | 1761  |      | 1795  |     |     |      |   |   |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               | 33.0        | 14.3  |                                 |         | 36.0  |      | 38.0  |     |     |      |   |   |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               | 33.0        | 14.3  |                                 |         | 36.0  |      | 38.0  |     |     |      |   |   |
| Green Ratio (g/C)                               |  |                 |               | 0.60        | 0.61  |                                 |         | 0.30  |      | 0.31  |     |     |      |   |   |
| Capacity (c), veh/h                             |  |                 |               | 558         | 2098  |                                 |         | 1056  |      | 569   |     |     |      |   |   |
| Volume-to-Capacity Ratio (X)                    |  |                 |               | 1.093       | 0.270 |                                 |         | 1.049 |      | 1.072 |     |     |      |   |   |
| Back of Queue (Q), ft/ln (90 th percentile)     |  |                 |               | 918.4       | 237.5 |                                 |         | 698.2 |      | 834.7 |     |     |      |   |   |
| Back of Queue (Q), veh/ln (90 th percentile)    |  |                 |               | 36.4        | 9.3   |                                 |         | 27.7  |      | 33.1  |     |     |      |   |   |
| Queue Storage Ratio (RQ) (90 th percentile)     |  |                 |               | 4.59        | 0.34  |                                 |         | 1.40  |      | 1.67  |     |     |      |   |   |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               | 51.6        | 20.3  |                                 |         | 42.0  |      | 41.0  |     |     |      |   |   |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               | 63.0        | 0.3   |                                 |         | 41.5  |      | 58.5  |     |     |      |   |   |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               | 0.0         | 0.0   |                                 |         | 0.0   |      | 0.0   |     |     |      |   |   |
| Control Delay (d), s/veh                        |  |                 |               | 114.6       | 20.6  |                                 |         | 83.5  | 0.0  | 99.5  |     | 0.0 |      |   |   |
| Level of Service (LOS)                          |  |                 |               | F           | C     |                                 |         | F     | A    | F     |     | A   |      |   |   |
| Approach Delay, s/veh / LOS                     |  |                 |               | 69.4        |       | E                               | 44.4    |       | D    | 67.2  |     | E   | 0.0  |   |   |
| Intersection Delay, s/veh / LOS                 |  |                 |               | 56.4        |       |                                 |         |       | E    |       |     |     |      |   |   |
| <b>Multimodal Results</b>                       |  |                 |               | EB          |       |                                 | WB      |       |      | NB    |     |     | SB   |   |   |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.66        | B     |                                 | 1.42    | A     |      | 2.33  | B   |     | 2.32 | B |   |
| Bicycle LOS Score / LOS                         |  |                 |               | 1.39        | A     |                                 | 2.21    | B     |      | F     |     |     |      |   |   |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary     |  |                 |               |           |       |                 |                                 |       |      |       |     |     |      |     |   |
|--|--|-----------------|---------------|-----------|-------|-----------------|---------------------------------|-------|------|-------|-----|-----|------|-----|---|
| <b>General Information</b>                       |  |                 |               |           |       |                 | <b>Intersection Information</b> |       |      |       |     |     |      |     |   |
| Agency   | Diane B. Zimmerman Traffic Engineering |                 |               |           |       |                 | Duration, h                     | 0.25  |      |       |     |     |      |     |   |
| Analyst  | DBZ                                    | Analysis Date   | 3/8/2018      |           |       | Area Type       | Other                           |       |      |       |     |     |      |     |   |
| Jurisdiction                                     |  | Time Period     | PM Peak       |           |       | PHF             | 0.95                            |       |      |       |     |     |      |     |   |
| Urban Street                                     | Taylorsville Road                      |                 | Analysis Year | 2018      |       | Analysis Period | 1> 4:00                         |       |      |       |     |     |      |     |   |
| Intersection                                     | I 265 NB Ramps                         |                 | File Name     | PM 18.xus |       |                 |                                 |       |      |       |     |     |      |     |   |
| Project Description                              | Covington by the Park                  |                 |               |           |       |                 |                                 |       |      |       |     |     |      |     |   |
| <b>Demand Information</b>                        |  |                 |               | EB        |       |                 | WB                              |       |      | NB    |     | SB  |      |     |   |
| Approach Movement                                |  |                 |               | L         | T     | R               | L                               | T     | R    | L     | T   | R   | L    | T   | R |
| Demand ( v ), veh/h                              |  |                 |               | 265       | 1022  |                 | 359                             | 230   | 248  |       | 220 |     |      |     |   |
| <b>Signal Information</b>                        |  |                 |               |           |       |                 |                                 |       |      |       |     |     |      |     |   |
| Cycle, s   | 120.0                                  | Reference Phase | 2             |           |       |                 |                                 |       |      |       |     |     |      |     |   |
| Offset, s  | 0                                      | Reference Point | End           | Green     | 9.8   | 74.0            | 21.2                            | 0.0   | 0.0  | 0.0   | 0.0 | 0.0 | 0.0  | 0.0 |   |
| Uncoordinated                                    | No                                     | Simult. Gap E/W | On            | Yellow    | 3.5   | 3.5             | 3.5                             | 0.0   | 0.0  | 0.0   | 0.0 | 0.0 | 0.0  | 0.0 |   |
| Force Mode                                       | Fixed                                  | Simult. Gap N/S | On            | Red       | 1.5   | 1.5             | 1.5                             | 0.0   | 0.0  | 0.0   | 0.0 | 0.0 | 0.0  | 0.0 |   |
| <b>Timer Results</b>                             |  |                 |               | EBL       | EBT   | WBL             | WBT                             | NBL   | NBT  | SBL   | SBT |     |      |     |   |
| Assigned Phase                                   |  |                 |               | 5         | 2     |                 | 6                               |       | 8    |       |     |     |      |     |   |
| Case Number                                      |  |                 |               | 1.0       | 4.0   |                 | 7.3                             |       | 9.0  |       |     |     |      |     |   |
| Phase Duration, s                                |  |                 |               | 14.8      | 93.8  |                 | 79.0                            |       | 26.2 |       |     |     |      |     |   |
| Change Period, ( Y+R <sub>c</sub> ), s           |  |                 |               | 5.0       | 5.0   |                 | 5.0                             |       | 5.0  |       |     |     |      |     |   |
| Max Allow Headway ( MAH ), s                     |  |                 |               | 4.0       | 0.0   |                 | 0.0                             |       | 4.1  |       |     |     |      |     |   |
| Queue Clearance Time ( g <sub>s</sub> ), s       |  |                 |               | 8.8       |       |                 |                                 |       | 19.6 |       |     |     |      |     |   |
| Green Extension Time ( g <sub>e</sub> ), s       |  |                 |               | 1.1       | 0.0   |                 | 0.0                             |       | 1.6  |       |     |     |      |     |   |
| Phase Call Probability                           |  |                 |               | 1.00      |       |                 |                                 |       | 1.00 |       |     |     |      |     |   |
| Max Out Probability                              |  |                 |               | 0.00      |       |                 |                                 |       | 0.01 |       |     |     |      |     |   |
| <b>Movement Group Results</b>                    |  |                 |               | EB        |       |                 | WB                              |       |      | NB    |     | SB  |      |     |   |
| Approach Movement                                |  |                 |               | L         | T     | R               | L                               | T     | R    | L     | T   | R   | L    | T   | R |
| Assigned Movement                                |  |                 |               | 5         | 2     |                 |                                 | 6     | 16   | 3     |     | 18  |      |     |   |
| Adjusted Flow Rate ( v ), veh/h                  |  |                 |               | 302       | 1163  |                 |                                 | 378   | 242  | 261   |     | 232 |      |     |   |
| Adjusted Saturation Flow Rate ( s ), veh/h/ln    |  |                 |               | 1767      | 1839  |                 |                                 | 1756  |      | 1767  |     |     |      |     |   |
| Queue Service Time ( g <sub>s</sub> ), s         |  |                 |               | 6.8       | 22.4  |                 |                                 | 5.5   |      | 17.1  |     |     |      |     |   |
| Cycle Queue Clearance Time ( g <sub>c</sub> ), s |  |                 |               | 6.8       | 22.4  |                 |                                 | 5.5   |      | 17.1  |     |     |      |     |   |
| Green Ratio ( g/C )                              |  |                 |               | 0.72      | 0.74  |                 |                                 | 0.62  |      | 0.18  |     |     |      |     |   |
| Capacity ( c ), veh/h                            |  |                 |               | 773       | 2723  |                 |                                 | 2166  |      | 312   |     |     |      |     |   |
| Volume-to-Capacity Ratio ( X )                   |  |                 |               | 0.390     | 0.427 |                 |                                 | 0.174 |      | 0.837 |     |     |      |     |   |
| Back of Queue ( Q ), ft/ln ( 90 th percentile)   |  |                 |               | 103.3     | 332.4 |                 |                                 | 91.4  |      | 292.9 |     |     |      |     |   |
| Back of Queue ( Q ), veh/ln ( 90 th percentile)  |  |                 |               | 4.0       | 13.2  |                 |                                 | 3.6   |      | 11.4  |     |     |      |     |   |
| Queue Storage Ratio ( RQ ) ( 90 th percentile)   |  |                 |               | 0.52      | 0.47  |                 |                                 | 0.18  |      | 0.59  |     |     |      |     |   |
| Uniform Delay ( d <sub>1</sub> ), s/veh          |  |                 |               | 6.4       | 12.1  |                 |                                 | 9.9   |      | 47.8  |     |     |      |     |   |
| Incremental Delay ( d <sub>2</sub> ), s/veh      |  |                 |               | 0.3       | 0.4   |                 |                                 | 0.2   |      | 6.2   |     |     |      |     |   |
| Initial Queue Delay ( d <sub>3</sub> ), s/veh    |  |                 |               | 0.0       | 0.0   |                 |                                 | 0.0   |      | 0.0   |     |     |      |     |   |
| Control Delay ( d ), s/veh                       |  |                 |               | 6.6       | 12.5  |                 |                                 | 10.1  | 0.0  | 54.0  |     | 0.0 |      |     |   |
| Level of Service (LOS)                           |  |                 |               | A         | B     |                 |                                 | B     | A    | D     |     | A   |      |     |   |
| Approach Delay, s/veh / LOS                      |  |                 |               | 11.3      |       | B               | 6.1                             |       | A    | 28.6  |     | C   | 0.0  |     |   |
| Intersection Delay, s/veh / LOS                  |  |                 |               | 13.4      |       |                 |                                 | B     |      |       |     |     |      |     |   |
| <b>Multimodal Results</b>                        |  |                 |               | EB        |       |                 | WB                              |       |      | NB    |     | SB  |      |     |   |
| Pedestrian LOS Score / LOS                       |  |                 |               | 1.63      |       | B               | 1.37                            |       | A    | 2.33  |     | B   | 2.32 |     | B |
| Bicycle LOS Score / LOS                          |  |                 |               | 1.61      |       | B               | 1.00                            |       | A    |       |     | F   |      |     |   |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary     |  |                 |               |               |       |                 |                                 |      |       |      |     |     |   |   |   |
|--|--|-----------------|---------------|---------------|-------|-----------------|---------------------------------|------|-------|------|-----|-----|---|---|---|
| <b>General Information</b>                       |  |                 |               |               |       |                 | <b>Intersection Information</b> |      |       |      |     |     |   |   |   |
| Agency   | Diane B. Zimmerman Traffic Engineering |                 |               |               |       |                 | Duration, h                     | 0.25 |       |      |     |     |   |   |   |
| Analyst  | DBZ                                    | Analysis Date   | Mar 25, 2018  |               |       | Area Type       | Other                           |      |       |      |     |     |   |   |   |
| Jurisdiction                                     |  | Time Period     | PM Peak       |               |       | PHF             | 0.95                            |      |       |      |     |     |   |   |   |
| Urban Street                                     | Taylorsville Road                      |                 | Analysis Year | 2030 No Build |       | Analysis Period | 1> 4:00                         |      |       |      |     |     |   |   |   |
| Intersection                                     | I 265 NB Ramps                         |                 | File Name     | PM 30 NB.xus  |       |                 |                                 |      |       |      |     |     |   |   |   |
| Project Description                              | Covington by the Park                  |                 |               |               |       |                 |                                 |      |       |      |     |     |   |   |   |
| <b>Demand Information</b>                        |  |                 |               | EB            |       |                 | WB                              |      |       | NB   |     | SB  |   |   |   |
| Approach Movement                                |  |                 |               | L             | T     | R               | L                               | T    | R     | L    | T   | R   | L | T | R |
| Demand ( v ), veh/h                              |  |                 |               | 468           | 1365  |                 | 498                             | 292  |       | 387  |     | 349 |   |   |   |
| <b>Signal Information</b>                        |  |                 |               |               |       |                 |                                 |      |       |      |     |     |   |   |   |
| Cycle, s   | 120.0                                  | Reference Phase | 2             |               |       |                 |                                 |      |       |      |     |     |   |   |   |
| Offset, s  | 0                                      | Reference Point | End           | Green         | 19.4  | 54.7            | 30.9                            | 0.0  | 0.0   | 0.0  |     |     |   |   |   |
| Uncoordinated                                    | No                                     | Simult. Gap E/W | On            | Yellow        | 3.5   | 3.5             | 3.5                             | 0.0  | 0.0   | 0.0  |     |     |   |   |   |
| Force Mode                                       | Fixed                                  | Simult. Gap N/S | On            | Red           | 1.5   | 1.5             | 1.5                             | 0.0  | 0.0   | 0.0  |     |     |   |   |   |
| <b>Timer Results</b>                             |  |                 |               | EBL           | EBT   | WBL             | WBT                             | NBL  | NBT   | SBL  | SBT |     |   |   |   |
| Assigned Phase                                   |  |                 |               | 5             | 2     |                 | 6                               |      | 8     |      |     |     |   |   |   |
| Case Number                                      |  |                 |               | 1.0           | 4.0   |                 | 7.3                             |      | 9.0   |      |     |     |   |   |   |
| Phase Duration, s                                |  |                 |               | 24.4          | 84.1  |                 | 59.7                            |      | 35.9  |      |     |     |   |   |   |
| Change Period, ( Y+R <sub>c</sub> ), s           |  |                 |               | 5.0           | 5.0   |                 | 5.0                             |      | 5.0   |      |     |     |   |   |   |
| Max Allow Headway ( MAH ), s                     |  |                 |               | 4.0           | 0.0   |                 | 0.0                             |      | 4.1   |      |     |     |   |   |   |
| Queue Clearance Time ( g <sub>s</sub> ), s       |  |                 |               | 17.5          |       |                 |                                 |      | 29.2  |      |     |     |   |   |   |
| Green Extension Time ( g <sub>e</sub> ), s       |  |                 |               | 1.9           | 0.0   |                 | 0.0                             |      | 1.7   |      |     |     |   |   |   |
| Phase Call Probability                           |  |                 |               | 1.00          |       |                 |                                 |      | 1.00  |      |     |     |   |   |   |
| Max Out Probability                              |  |                 |               | 0.00          |       |                 |                                 |      | 0.66  |      |     |     |   |   |   |
| <b>Movement Group Results</b>                    |  |                 |               | EB            |       |                 | WB                              |      |       | NB   |     | SB  |   |   |   |
| Approach Movement                                |  |                 |               | L             | T     | R               | L                               | T    | R     | L    | T   | R   | L | T | R |
| Assigned Movement                                |  |                 |               | 5             | 2     |                 | 6                               | 16   |       | 3    |     | 18  |   |   |   |
| Adjusted Flow Rate ( v ), veh/h                  |  |                 |               | 508           | 1482  |                 | 524                             | 307  |       | 407  |     | 367 |   |   |   |
| Adjusted Saturation Flow Rate ( s ), veh/h/ln    |  |                 |               | 1767          | 1889  |                 | 1778                            |      | 1767  |      |     |     |   |   |   |
| Queue Service Time ( g <sub>s</sub> ), s         |  |                 |               | 15.5          | 37.4  |                 | 11.3                            |      | 26.4  |      |     |     |   |   |   |
| Cycle Queue Clearance Time ( g <sub>c</sub> ), s |  |                 |               | 15.5          | 37.4  |                 | 11.3                            |      | 26.4  |      |     |     |   |   |   |
| Green Ratio ( g/C )                              |  |                 |               | 0.63          | 0.66  |                 | 0.46                            |      | 0.27  |      |     |     |   |   |   |
| Capacity ( c ), veh/h                            |  |                 |               | 661           | 2491  |                 | 1621                            |      | 470   |      |     |     |   |   |   |
| Volume-to-Capacity Ratio ( X )                   |  |                 |               | 0.769         | 0.595 |                 | 0.323                           |      | 0.867 |      |     |     |   |   |   |
| Back of Queue ( Q ), ft/ln ( 90 th percentile)   |  |                 |               | 257.7         | 552.6 |                 | 186.5                           |      | 444   |      |     |     |   |   |   |
| Back of Queue ( Q ), veh/ln ( 90 th percentile)  |  |                 |               | 10.1          | 21.9  |                 | 7.3                             |      | 17.3  |      |     |     |   |   |   |
| Queue Storage Ratio ( RQ ) ( 90 th percentile)   |  |                 |               | 1.29          | 0.79  |                 | 0.37                            |      | 0.89  |      |     |     |   |   |   |
| Uniform Delay ( d <sub>1</sub> ), s/veh          |  |                 |               | 15.0          | 23.8  |                 | 20.8                            |      | 42.0  |      |     |     |   |   |   |
| Incremental Delay ( d <sub>2</sub> ), s/veh      |  |                 |               | 1.4           | 0.6   |                 | 0.5                             |      | 13.1  |      |     |     |   |   |   |
| Initial Queue Delay ( d <sub>3</sub> ), s/veh    |  |                 |               | 0.0           | 0.0   |                 | 0.0                             |      | 0.0   |      |     |     |   |   |   |
| Control Delay ( d ), s/veh                       |  |                 |               | 16.5          | 24.5  |                 | 21.4                            | 0.0  | 55.1  |      | 0.0 |     |   |   |   |
| Level of Service (LOS)                           |  |                 |               | B             | C     |                 | C                               | A    | E     |      | A   |     |   |   |   |
| Approach Delay, s/veh / LOS                      |  |                 |               | 22.4          | C     | 13.5            | B                               | 29.0 | C     | 0.0  |     |     |   |   |   |
| Intersection Delay, s/veh / LOS                  |  |                 |               | 21.8          |       |                 | C                               |      |       |      |     |     |   |   |   |
| <b>Multimodal Results</b>                        |  |                 |               | EB            |       |                 | WB                              |      |       | NB   |     | SB  |   |   |   |
| Pedestrian LOS Score / LOS                       |  |                 |               | 1.65          | B     | 1.40            | A                               | 2.33 | B     | 2.32 | B   |     |   |   |   |
| Bicycle LOS Score / LOS                          |  |                 |               | 2.08          | B     | 1.17            | A                               | F    |       |      |     |     |   |   |   |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary     |  |                 |               |             |       |                 |                                 |      |       |      |     |    |   |   |   |
|--|--|-----------------|---------------|-------------|-------|-----------------|---------------------------------|------|-------|------|-----|----|---|---|---|
| <b>General Information</b>                       |  |                 |               |             |       |                 | <b>Intersection Information</b> |      |       |      |     |    |   |   |   |
| Agency   | Diane B. Zimmerman Traffic Engineering |                 |               |             |       |                 | Duration, h                     | 0.25 |       |      |     |    |   |   |   |
| Analyst  | DBZ                                    | Analysis Date   | Mar 25, 2018  |             |       | Area Type       | Other                           |      |       |      |     |    |   |   |   |
| Jurisdiction                                     |  | Time Period     | PM Peak       |             |       | PHF             | 0.95                            |      |       |      |     |    |   |   |   |
| Urban Street                                     | Taylorsville Road                      |                 | Analysis Year | 2030 Build  |       | Analysis Period | 1> 4:00                         |      |       |      |     |    |   |   |   |
| Intersection                                     | I 265 NB Ramps                         |                 | File Name     | PM 30 B.xus |       |                 |                                 |      |       |      |     |    |   |   |   |
| Project Description                              | Covington by the Park                  |                 |               |             |       |                 |                                 |      |       |      |     |    |   |   |   |
| <b>Demand Information</b>                        |  |                 |               | EB          |       |                 | WB                              |      |       | NB   |     | SB |   |   |   |
| Approach Movement                                |  |                 |               | L           | T     | R               | L                               | T    | R     | L    | T   | R  | L | T | R |
| Demand ( v ), veh/h                              |  |                 |               | 468         | 1609  |                 | 587                             | 381  | 387   |      | 405 |    |   |   |   |
| <b>Signal Information</b>                        |  |                 |               |             |       |                 |                                 |      |       |      |     |    |   |   |   |
| Cycle, s   | 120.0                                  | Reference Phase | 2             |             |       |                 |                                 |      |       |      |     |    |   |   |   |
| Offset, s  | 0                                      | Reference Point | End           | Green       | 20.6  | 50.2            | 34.2                            | 0.0  | 0.0   | 0.0  |     |    |   |   |   |
| Uncoordinated                                    | No                                     | Simult. Gap E/W | On            | Yellow      | 3.5   | 3.5             | 3.5                             | 0.0  | 0.0   | 0.0  |     |    |   |   |   |
| Force Mode                                       | Fixed                                  | Simult. Gap N/S | On            | Red         | 1.5   | 1.5             | 1.5                             | 0.0  | 0.0   | 0.0  |     |    |   |   |   |
| <b>Timer Results</b>                             |  |                 |               | EBL         | EBT   | WBL             | WBT                             | NBL  | NBT   | SBL  | SBT |    |   |   |   |
| Assigned Phase                                   |  |                 |               | 5           | 2     |                 | 6                               |      | 8     |      |     |    |   |   |   |
| Case Number                                      |  |                 |               | 1.0         | 4.0   |                 | 7.3                             |      | 9.0   |      |     |    |   |   |   |
| Phase Duration, s                                |  |                 |               | 25.6        | 80.8  |                 | 55.2                            |      | 39.2  |      |     |    |   |   |   |
| Change Period, ( Y+R <sub>c</sub> ), s           |  |                 |               | 5.0         | 5.0   |                 | 5.0                             |      | 5.0   |      |     |    |   |   |   |
| Max Allow Headway ( MAH ), s                     |  |                 |               | 4.0         | 0.0   |                 | 0.0                             |      | 4.1   |      |     |    |   |   |   |
| Queue Clearance Time ( g <sub>s</sub> ), s       |  |                 |               | 18.8        |       |                 |                                 |      | 33.6  |      |     |    |   |   |   |
| Green Extension Time ( g <sub>e</sub> ), s       |  |                 |               | 1.7         | 0.0   |                 | 0.0                             |      | 0.6   |      |     |    |   |   |   |
| Phase Call Probability                           |  |                 |               | 1.00        |       |                 |                                 |      | 1.00  |      |     |    |   |   |   |
| Max Out Probability                              |  |                 |               | 0.01        |       |                 |                                 |      | 1.00  |      |     |    |   |   |   |
| <b>Movement Group Results</b>                    |  |                 |               | EB          |       |                 | WB                              |      |       | NB   |     | SB |   |   |   |
| Approach Movement                                |  |                 |               | L           | T     | R               | L                               | T    | R     | L    | T   | R  | L | T | R |
| Assigned Movement                                |  |                 |               | 5           | 2     |                 |                                 | 6    | 16    | 3    |     | 18 |   |   |   |
| Adjusted Flow Rate ( v ), veh/h                  |  |                 |               | 506         | 1738  |                 | 618                             | 401  | 407   |      | 426 |    |   |   |   |
| Adjusted Saturation Flow Rate ( s ), veh/h/ln    |  |                 |               | 1767        | 1931  |                 | 1769                            |      | 1767  |      |     |    |   |   |   |
| Queue Service Time ( g <sub>s</sub> ), s         |  |                 |               | 16.8        | 46.4  |                 | 14.8                            |      | 25.4  |      |     |    |   |   |   |
| Cycle Queue Clearance Time ( g <sub>c</sub> ), s |  |                 |               | 16.8        | 46.4  |                 | 14.8                            |      | 25.4  |      |     |    |   |   |   |
| Green Ratio ( g/C )                              |  |                 |               | 0.61        | 0.63  |                 | 0.42                            |      | 0.29  |      |     |    |   |   |   |
| Capacity ( c ), veh/h                            |  |                 |               | 599         | 2441  |                 | 1481                            |      | 518   |      |     |    |   |   |   |
| Volume-to-Capacity Ratio ( X )                   |  |                 |               | 0.844       | 0.712 |                 | 0.417                           |      | 0.786 |      |     |    |   |   |   |
| Back of Queue ( Q ), ft/ln ( 90 th percentile)   |  |                 |               | 265.4       | 668.7 |                 | 235.2                           |      | 410.9 |      |     |    |   |   |   |
| Back of Queue ( Q ), veh/ln ( 90 th percentile)  |  |                 |               | 10.4        | 26.5  |                 | 9.3                             |      | 16.1  |      |     |    |   |   |   |
| Queue Storage Ratio ( RQ ) ( 90 th percentile)   |  |                 |               | 1.33        | 0.96  |                 | 0.47                            |      | 0.82  |      |     |    |   |   |   |
| Uniform Delay ( d <sub>1</sub> ), s/veh          |  |                 |               | 19.3        | 28.9  |                 | 24.6                            |      | 39.0  |      |     |    |   |   |   |
| Incremental Delay ( d <sub>2</sub> ), s/veh      |  |                 |               | 2.4         | 0.7   |                 | 0.9                             |      | 7.6   |      |     |    |   |   |   |
| Initial Queue Delay ( d <sub>3</sub> ), s/veh    |  |                 |               | 0.0         | 0.0   |                 | 0.0                             |      | 0.0   |      |     |    |   |   |   |
| Control Delay ( d ), s/veh                       |  |                 |               | 21.7        | 29.6  |                 | 25.4                            | 0.0  | 46.5  |      | 0.0 |    |   |   |   |
| Level of Service (LOS)                           |  |                 |               | C           | C     |                 | C                               | A    | D     |      | A   |    |   |   |   |
| Approach Delay, s/veh / LOS                      |  |                 |               | 27.8        | C     | 15.4            | B                               | 22.7 | C     | 0.0  |     |    |   |   |   |
| Intersection Delay, s/veh / LOS                  |  |                 |               | 23.7        |       |                 | C                               |      |       |      |     |    |   |   |   |
| <b>Multimodal Results</b>                        |  |                 |               | EB          |       |                 | WB                              |      |       | NB   |     | SB |   |   |   |
| Pedestrian LOS Score / LOS                       |  |                 |               | 1.66        | B     | 1.40            | A                               | 2.33 | B     | 2.32 | B   |    |   |   |   |
| Bicycle LOS Score / LOS                          |  |                 |               | 2.29        | B     | 1.33            | A                               |      | F     |      |     |    |   |   |   |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Two-Way Stop-Control Report                           |                                       |      |     |     |           |      |      |                            |                           |      |      |      |            |      |      |      |
|--|---------------------------------------|------|-----|-----|-----------|------|------|----------------------------|---------------------------|------|------|------|------------|------|------|------|
| General Information  |                                       |      |     |     |           |      |      | Site Information           |                           |      |      |      |            |      |      |      |
| Analyst  | Diane Zimmerman                       |      |     |     |           |      |      | Intersection               | Taylorsville at S Pope Li |      |      |      |            |      |      |      |
| Agency/Co.   | Diane B Zimmerman Traffic Engineering |      |     |     |           |      |      | Jurisdiction               |                           |      |      |      |            |      |      |      |
| Date Performed   | 5/29/18                               |      |     |     |           |      |      | East/West Street           | Taylorsville Rd           |      |      |      |            |      |      |      |
| Analysis Year  | 2018                                  |      |     |     |           |      |      | North/South Street         | S Pope Lick Road          |      |      |      |            |      |      |      |
| Time Analyzed  | AM Peak                               |      |     |     |           |      |      | Peak Hour Factor           | 0.94                      |      |      |      |            |      |      |      |
| Intersection Orientation                                   | East-West                             |      |     |     |           |      |      | Analysis Time Period (hrs) | 0.25                      |      |      |      |            |      |      |      |
| Project Description  | Covington by the Park                 |      |     |     |           |      |      |                            |                           |      |      |      |            |      |      |      |
| Lanes  |                                       |      |     |     |           |      |      |                            |                           |      |      |      |            |      |      |      |
| <p style="text-align: center;">Major Street: East-West</p> |                                       |      |     |     |           |      |      |                            |                           |      |      |      |            |      |      |      |
| Vehicle Volumes and Adjustments                            |                                       |      |     |     |           |      |      |                            |                           |      |      |      |            |      |      |      |
| Approach   | Eastbound                             |      |     |     | Westbound |      |      |                            | Northbound                |      |      |      | Southbound |      |      |      |
| Movement   | U                                     | L    | T   | R   | U         | L    | T    | R                          | U                         | L    | T    | R    | U          | L    | T    | R    |
| Priority   | 1U                                    | 1    | 2   | 3   | 4U        | 4    | 5    | 6                          | 7                         | 8    | 9    |      | 10         | 11   | 12   |      |
| Number of Lanes  | 0                                     | 0    | 1   | 0   | 0         | 0    | 1    | 0                          | 0                         | 1    | 0    |      | 0          | 1    | 0    |      |
| Configuration  |                                       |      | LTR |     |           |      | LTR  |                            |                           |      | LTR  |      |            |      | LTR  |      |
| Volume (veh/h)   |                                       | 83   | 382 | 42  |           | 1    | 1158 | 242                        |                           | 3    | 1    | 6    |            | 6    | 0    | 34   |
| Percent Heavy Vehicles (%)                                 |                                       | 1    |     |     |           | 1    |      |                            |                           | 1    | 1    | 1    |            | 1    | 1    | 1    |
| Proportion Time Blocked                                    |                                       |      |     |     |           |      |      |                            |                           |      |      |      |            |      |      |      |
| Percent Grade (%)  |                                       |      |     |     |           |      |      |                            | 0                         |      |      |      | 0          |      |      |      |
| Right Turn Channelized                                     |                                       |      |     |     |           |      |      |                            |                           |      |      |      |            |      |      |      |
| Median Type   Storage                                      | Undivided                             |      |     |     |           |      |      |                            |                           |      |      |      |            |      |      |      |
| Critical and Follow-up Headways                            |                                       |      |     |     |           |      |      |                            |                           |      |      |      |            |      |      |      |
| Base Critical Headway (sec)                                |                                       | 4.1  |     |     |           | 4.1  |      |                            |                           | 7.1  | 6.5  | 6.2  |            | 7.1  | 6.5  | 6.2  |
| Critical Headway (sec)                                     |                                       | 4.11 |     |     |           | 4.11 |      |                            |                           | 7.11 | 6.51 | 6.21 |            | 7.11 | 6.51 | 6.21 |
| Base Follow-Up Headway (sec)                               |                                       | 2.2  |     |     |           | 2.2  |      |                            |                           | 3.5  | 4.0  | 3.3  |            | 3.5  | 4.0  | 3.3  |
| Follow-Up Headway (sec)                                    |                                       | 2.23 |     |     |           | 2.23 |      |                            |                           | 3.53 | 4.03 | 3.33 |            | 3.53 | 4.03 | 3.33 |
| Delay, Queue Length, and Level of Service                  |                                       |      |     |     |           |      |      |                            |                           |      |      |      |            |      |      |      |
| Flow Rate, v (veh/h)                                       |                                       | 88   |     |     |           | 1    |      |                            |                           | 11   |      |      |            | 43   |      |      |
| Capacity, c (veh/h)  |                                       | 451  |     |     |           | 1106 |      |                            |                           | 72   |      |      |            | 113  |      |      |
| v/c Ratio  |                                       | 0.20 |     |     |           | 0.00 |      |                            |                           | 0.15 |      |      |            | 0.38 |      |      |
| 95% Queue Length, Q <sub>95</sub> (veh)                    |                                       | 0.7  |     |     |           | 0.0  |      |                            |                           | 0.5  |      |      |            | 1.5  |      |      |
| Control Delay (s/veh)                                      |                                       | 14.9 |     | 3.9 |           | 8.3  |      | 0.1                        |                           | 63.4 |      |      |            | 54.8 |      |      |
| Level of Service (LOS)                                     |                                       | B    |     | A   |           | A    |      | A                          |                           | F    |      |      |            | F    |      |      |
| Approach Delay (s/veh)                                     | 5.7                                   |      |     |     | 0.1       |      |      |                            | 63.4                      |      |      |      | 54.8       |      |      |      |
| Approach LOS   |                                       |      |     |     |           |      |      |                            | F                         |      |      |      | F          |      |      |      |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

**HCS7 Signalized Intersection Results Summary**

| General Information                             |  |                 |                   | Intersection Information |         |       |       |       |      |       |       |     |    |  |  |
|---|--|-----------------|-------------------|--------------------------|---------|-------|-------|-------|------|-------|-------|-----|----|--|--|
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |                   | Duration, h              | 0.25    |       |       |       |      |       |       |     |    |  |  |
| Analyst   | DBZ                                    | Analysis Date   | May 29, 2018      | Area Type                | Other   |       |       |       |      |       |       |     |    |  |  |
| Jurisdiction                                    |  | Time Period     | AM Peak           | PHF                      | 0.92    |       |       |       |      |       |       |     |    |  |  |
| Urban Street                                    | Taylorsville Road                      | Analysis Year   | 2030 No Build     | Analysis Period          | 1> 7:00 |       |       |       |      |       |       |     |    |  |  |
| Intersection                                    | S Pope Lick Road                       | File Name       | AM Pope 30 NB.xus |                          |         |       |       |       |      |       |       |     |    |  |  |
| Project Description                             | Covington By the Park Single Family    |                 |                   |                          |         |       |       |       |      |       |       |     |    |  |  |
| Demand Information                              |  |                 |                   | EB                       |         |       | WB    |       |      | NB    |       |     | SB |  |  |
| Approach Movement                               | L                                      | T               | R                 | L                        | T       | R     | L     | T     | R    | L     | T     | R   |    |  |  |
| Demand (v), veh/h                               | 131                                    | 435             | 48                | 2                        | 1318    | 283   | 4     | 1     | 7    | 32    | 1     | 153 |    |  |  |
| Signal Information                              |  |                 |                   |                          |         |       |       |       |      |       |       |     |    |  |  |
| Cycle, s  | 150.0                                  | Reference Phase | 2                 |                          |         |       |       |       |      |       |       |     |    |  |  |
| Offset, s                                       | 0                                      | Reference Point | End               |                          |         |       |       |       |      |       |       |     |    |  |  |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On                | Green                    | 0.5     | 3.5   | 109.0 | 14.5  | 0.0  | 0.0   |       |     |    |  |  |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On                | Yellow                   | 4.0     | 4.0   | 4.0   | 4.0   | 0.0  | 0.0   |       |     |    |  |  |
|   |  |                 |                   | Red                      | 1.5     | 1.5   | 2.0   | 1.5   | 0.0  | 0.0   |       |     |    |  |  |
| Timer Results                                   |  |                 |                   | EBL                      | EBT     | WBL   | WBT   | NBL   | NBT  | SBL   | SBT   |     |    |  |  |
| Assigned Phase                                  |  |                 |                   | 5                        | 2       | 1     | 6     |       | 8    |       | 4     |     |    |  |  |
| Case Number                                     |  |                 |                   | 1.1                      | 4.0     | 2.0   | 3.0   |       | 6.0  |       | 6.0   |     |    |  |  |
| Phase Duration, s                               |  |                 |                   | 15.0                     | 124.0   | 6.0   | 115.0 |       | 20.0 |       | 20.0  |     |    |  |  |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |                   | 5.5                      | 6.0     | 5.5   | 6.0   |       | 5.5  |       | 5.5   |     |    |  |  |
| Max Allow Headway (MAH), s                      |  |                 |                   | 3.9                      | 0.0     | 3.9   | 0.0   |       | 4.1  |       | 4.1   |     |    |  |  |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |                   | 9.7                      |         | 2.2   |       |       | 16.5 |       | 16.5  |     |    |  |  |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |                   | 0.0                      | 0.0     | 0.0   | 0.0   |       | 0.0  |       | 0.0   |     |    |  |  |
| Phase Call Probability                          |  |                 |                   | 1.00                     |         | 0.09  |       |       | 1.00 |       | 1.00  |     |    |  |  |
| Max Out Probability                             |  |                 |                   | 1.00                     |         | 0.00  |       |       | 1.00 |       | 1.00  |     |    |  |  |
| Movement Group Results                          |  |                 |                   | EB                       |         |       | WB    |       |      | NB    |       |     | SB |  |  |
| Approach Movement                               | L                                      | T               | R                 | L                        | T       | R     | L     | T     | R    | L     | T     | R   |    |  |  |
| Assigned Movement                               | 5                                      | 2               | 12                | 1                        | 6       | 16    | 3     | 8     | 18   | 7     | 4     | 14  |    |  |  |
| Adjusted Flow Rate (v), veh/h                   | 142                                    | 525             |                   | 2                        | 1433    | 308   | 4     | 9     |      | 35    | 167   |     |    |  |  |
| Adjusted Saturation Flow Rate (s), veh/h/ln     | 1795                                   | 1808            |                   | 1795                     | 1841    | 1585  | 1228  | 1629  |      | 1418  | 1599  |     |    |  |  |
| Queue Service Time (g <sub>s</sub> ), s         | 7.7                                    | 13.1            |                   | 0.2                      | 110.0   | 9.9   | 0.0   | 0.7   |      | 3.4   | 14.5  |     |    |  |  |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s | 7.7                                    | 13.1            |                   | 0.2                      | 110.0   | 9.9   | 14.5  | 0.7   |      | 4.2   | 14.5  |     |    |  |  |
| Green Ratio (g/C)                               | 0.80                                   | 0.79            |                   | 0.00                     | 0.73    | 0.73  | 0.10  | 0.10  |      | 0.10  | 0.10  |     |    |  |  |
| Capacity (c), veh/h                             | 162                                    | 1422            |                   | 6                        | 1350    | 1152  | 48    | 157   |      | 178   | 165   |     |    |  |  |
| Volume-to-Capacity Ratio (X)                    | 0.881                                  | 0.369           |                   | 0.349                    | 1.061   | 0.267 | 0.091 | 0.055 |      | 0.195 | 1.013 |     |    |  |  |
| Back of Queue (Q), ft/ln (50 th percentile)     | 140.2                                  | 101.2           |                   | 3.4                      | 1340.3  | 76.2  | 4.4   | 7.6   |      | 31.1  | 228.8 |     |    |  |  |
| Back of Queue (Q), veh/ln (50 th percentile)    | 5.6                                    | 3.9             |                   | 0.1                      | 52.0    | 3.0   | 0.2   | 0.3   |      | 1.2   | 9.1   |     |    |  |  |
| Queue Storage Ratio (RQ) (50 th percentile)     | 0.70                                   | 0.10            |                   | 0.02                     | 1.68    | 0.38  | 0.04  | 0.03  |      | 0.16  | 0.38  |     |    |  |  |
| Uniform Delay (d <sub>1</sub> ), s/veh          | 58.2                                   | 4.8             |                   | 74.6                     | 20.0    | 7.0   | 75.0  | 61.5  |      | 63.4  | 67.3  |     |    |  |  |
| Incremental Delay (d <sub>2</sub> ), s/veh      | 38.7                                   | 0.7             |                   | 30.4                     | 42.6    | 0.6   | 0.8   | 0.1   |      | 0.5   | 73.4  |     |    |  |  |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    | 0.0                                    | 0.0             |                   | 0.0                      | 0.0     | 0.0   | 0.0   | 0.0   |      | 0.0   | 0.0   |     |    |  |  |
| Control Delay (d), s/veh                        | 96.9                                   | 5.6             |                   | 104.9                    | 62.6    | 7.5   | 75.8  | 61.7  |      | 63.9  | 140.7 |     |    |  |  |
| Level of Service (LOS)                          | F                                      | A               |                   | F                        | F       | A     | E     | E     |      | E     | F     |     |    |  |  |
| Approach Delay, s/veh / LOS                     | 25.0                                   |                 | C                 | 52.9                     |         | D     | 66.4  |       | E    | 127.5 |       | F   |    |  |  |
| Intersection Delay, s/veh / LOS                 | 51.6                                   |                 |                   |                          |         |       | D     |       |      |       |       |     |    |  |  |
| Multimodal Results                              |  |                 |                   | EB                       |         |       | WB    |       |      | NB    |       |     | SB |  |  |
| Pedestrian LOS Score / LOS                      | 1.85                                   |                 | B                 | 1.87                     |         | B     | 2.15  |       | B    | 1.96  |       | B   |    |  |  |
| Bicycle LOS Score / LOS                         | 1.59                                   |                 | B                 | 3.36                     |         | C     | 0.51  |       | A    | 0.82  |       | A   |    |  |  |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

**HCS7 Signalized Intersection Results Summary**

| General Information                             |  |                 |                  | Intersection Information |         |      |       |        |       |       |       |    |       |       |     |
|---|--|-----------------|------------------|--------------------------|---------|------|-------|--------|-------|-------|-------|----|-------|-------|-----|
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |                  | Duration, h              | 0.25    |      |       |        |       |       |       |    |       |       |     |
| Analyst   | DBZ                                    | Analysis Date   | May 29, 2018     | Area Type                | Other   |      |       |        |       |       |       |    |       |       |     |
| Jurisdiction                                    |  | Time Period     | AM Peak          | PHF                      | 0.92    |      |       |        |       |       |       |    |       |       |     |
| Urban Street                                    | Taylorsville Road                      | Analysis Year   | 2030             | Analysis Period          | 1> 7:00 |      |       |        |       |       |       |    |       |       |     |
| Intersection                                    | S Pope Lick Road                       | File Name       | AM Pope 30 B.xus |                          |         |      |       |        |       |       |       |    |       |       |     |
| Project Description                             | Covington By the Park Single Family    |                 |                  |                          |         |      |       |        |       |       |       |    |       |       |     |
| Demand Information                              |  |                 |                  | EB                       |         |      | WB    |        |       | NB    |       |    | SB    |       |     |
| Approach Movement                               |  |                 |                  | L                        | T       | R    | L     | T      | R     | L     | T     | R  | L     | T     | R   |
| Demand (v), veh/h                               |  |                 |                  | 131                      | 525     | 48   | 2     | 1590   | 300   | 4     | 1     | 7  | 38    | 1     | 153 |
| Signal Information                              |  |                 |                  |                          |         |      |       |        |       |       |       |    |       |       |     |
| Cycle, s  | 150.0                                  | Reference Phase | 2                |                          |         |      |       |        |       |       |       |    |       |       |     |
| Offset, s                                       | 0                                      | Reference Point | End              | Green                    | 0.5     | 3.5  | 109.0 | 14.5   | 0.0   | 0.0   |       |    |       |       |     |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On               | Yellow                   | 4.0     | 4.0  | 4.0   | 4.0    | 0.0   | 0.0   |       |    |       |       |     |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On               | Red                      | 1.5     | 1.5  | 2.0   | 1.5    | 0.0   | 0.0   |       |    |       |       |     |
| Timer Results                                   |  |                 |                  | EBL                      | EBT     | WBL  | WBT   | NBL    | NBT   | SBL   | SBT   |    |       |       |     |
| Assigned Phase                                  |  |                 |                  | 5                        | 2       | 1    | 6     |        | 8     |       | 4     |    |       |       |     |
| Case Number                                     |  |                 |                  | 1.1                      | 4.0     | 2.0  | 3.0   |        | 6.0   |       | 6.0   |    |       |       |     |
| Phase Duration, s                               |  |                 |                  | 15.0                     | 124.0   | 6.0  | 115.0 |        | 20.0  |       | 20.0  |    |       |       |     |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |                  | 5.5                      | 6.0     | 5.5  | 6.0   |        | 5.5   |       | 5.5   |    |       |       |     |
| Max Allow Headway (MAH), s                      |  |                 |                  | 3.9                      | 0.0     | 3.9  | 0.0   |        | 4.1   |       | 4.1   |    |       |       |     |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |                  | 9.7                      |         | 2.2  |       |        | 16.5  |       | 16.5  |    |       |       |     |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |                  | 0.0                      | 0.0     | 0.0  | 0.0   |        | 0.0   |       | 0.0   |    |       |       |     |
| Phase Call Probability                          |  |                 |                  | 1.00                     |         | 0.09 |       |        | 1.00  |       | 1.00  |    |       |       |     |
| Max Out Probability                             |  |                 |                  | 1.00                     |         | 0.00 |       |        | 1.00  |       | 1.00  |    |       |       |     |
| Movement Group Results                          |  |                 |                  | EB                       |         |      | WB    |        |       | NB    |       |    | SB    |       |     |
| Approach Movement                               |  |                 |                  | L                        | T       | R    | L     | T      | R     | L     | T     | R  | L     | T     | R   |
| Assigned Movement                               |  |                 |                  | 5                        | 2       | 12   | 1     | 6      | 16    | 3     | 8     | 18 | 7     | 4     | 14  |
| Adjusted Flow Rate (v), veh/h                   |  |                 |                  | 142                      | 623     |      | 2     | 1728   | 326   | 4     | 9     |    | 41    | 167   |     |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |                  | 1795                     | 1813    |      | 1795  | 1841   | 1585  | 1228  | 1629  |    | 1418  | 1599  |     |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |                  | 7.7                      | 16.8    |      | 0.2   | 110.0  | 10.6  | 0.0   | 0.7   |    | 4.1   | 14.5  |     |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |                  | 7.7                      | 16.8    |      | 0.2   | 110.0  | 10.6  | 14.5  | 0.7   |    | 4.8   | 14.5  |     |
| Green Ratio (g/C)                               |  |                 |                  | 0.80                     | 0.79    |      | 0.00  | 0.73   | 0.73  | 0.10  | 0.10  |    | 0.10  | 0.10  |     |
| Capacity (c), veh/h                             |  |                 |                  | 162                      | 1426    |      | 6     | 1350   | 1152  | 48    | 157   |    | 178   | 165   |     |
| Volume-to-Capacity Ratio (X)                    |  |                 |                  | 0.881                    | 0.437   |      | 0.349 | 1.280  | 0.283 | 0.091 | 0.055 |    | 0.232 | 1.013 |     |
| Back of Queue (Q), ft/ln (50 th percentile)     |  |                 |                  | 140.2                    | 130     |      | 3.4   | 2205.4 | 81.6  | 4.4   | 7.6   |    | 37.1  | 228.8 |     |
| Back of Queue (Q), veh/ln (50 th percentile)    |  |                 |                  | 5.6                      | 5.0     |      | 0.1   | 85.5   | 3.2   | 0.2   | 0.3   |    | 1.5   | 9.1   |     |
| Queue Storage Ratio (RQ) (50 th percentile)     |  |                 |                  | 0.70                     | 0.13    |      | 0.02  | 2.76   | 0.41  | 0.04  | 0.03  |    | 0.19  | 0.38  |     |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |                  | 58.2                     | 5.2     |      | 74.6  | 20.0   | 7.1   | 75.0  | 61.5  |    | 63.7  | 67.3  |     |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |                  | 38.7                     | 1.0     |      | 30.4  | 132.0  | 0.6   | 0.8   | 0.1   |    | 0.7   | 73.4  |     |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |                  | 0.0                      | 0.0     |      | 0.0   | 0.0    | 0.0   | 0.0   | 0.0   |    | 0.0   | 0.0   |     |
| Control Delay (d), s/veh                        |  |                 |                  | 96.9                     | 6.2     |      | 104.9 | 152.0  | 7.7   | 75.8  | 61.7  |    | 64.4  | 140.7 |     |
| Level of Service (LOS)                          |  |                 |                  | F                        | A       |      | F     | F      | A     | E     | E     |    | E     | F     |     |
| Approach Delay, s/veh / LOS                     |  |                 |                  | 23.1                     |         | C    | 129.0 |        | F     | 66.4  |       | E  | 125.6 |       | F   |
| Intersection Delay, s/veh / LOS                 |  |                 |                  | 101.9                    |         |      |       |        |       | F     |       |    |       |       |     |
| Multimodal Results                              |  |                 |                  | EB                       |         |      | WB    |        |       | NB    |       |    | SB    |       |     |
| Pedestrian LOS Score / LOS                      |  |                 |                  | 1.85                     |         | B    | 1.87  |        | B     | 2.15  |       | B  | 1.96  |       | B   |
| Bicycle LOS Score / LOS                         |  |                 |                  | 1.75                     |         | B    | 3.88  |        | D     | 0.51  |       | A  | 0.83  |       | A   |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Two-Way Stop-Control Report                           |                                       |      |      |     |           |      |           |                            |                           |       |      |      |            |       |      |      |  |
|--|---------------------------------------|------|------|-----|-----------|------|-----------|----------------------------|---------------------------|-------|------|------|------------|-------|------|------|--|
| General Information  |                                       |      |      |     |           |      |           | Site Information           |                           |       |      |      |            |       |      |      |  |
| Analyst  | Diane Zimmerman                       |      |      |     |           |      |           | Intersection               | Taylorsville at S Pope Li |       |      |      |            |       |      |      |  |
| Agency/Co.   | Diane B Zimmerman Traffic Engineering |      |      |     |           |      |           | Jurisdiction               |                           |       |      |      |            |       |      |      |  |
| Date Performed   | 5/29/18                               |      |      |     |           |      |           | East/West Street           | Taylorsville Rd           |       |      |      |            |       |      |      |  |
| Analysis Year  | 2018                                  |      |      |     |           |      |           | North/South Street         | S Pope Lick Road          |       |      |      |            |       |      |      |  |
| Time Analyzed  | PM Peak                               |      |      |     |           |      |           | Peak Hour Factor           | 0.96                      |       |      |      |            |       |      |      |  |
| Intersection Orientation                                   | East-West                             |      |      |     |           |      |           | Analysis Time Period (hrs) | 0.25                      |       |      |      |            |       |      |      |  |
| Project Description  | Covington by the Park                 |      |      |     |           |      |           |                            |                           |       |      |      |            |       |      |      |  |
| Lanes  |                                       |      |      |     |           |      |           |                            |                           |       |      |      |            |       |      |      |  |
| <p style="text-align: center;">Major Street: East-West</p> |                                       |      |      |     |           |      |           |                            |                           |       |      |      |            |       |      |      |  |
| Vehicle Volumes and Adjustments                            |                                       |      |      |     |           |      |           |                            |                           |       |      |      |            |       |      |      |  |
| Approach   | Eastbound                             |      |      |     | Westbound |      |           |                            | Northbound                |       |      |      | Southbound |       |      |      |  |
| Movement   | U                                     | L    | T    | R   | U         | L    | T         | R                          | U                         | L     | T    | R    | U          | L     | T    | R    |  |
| Priority   | 1U                                    | 1    | 2    | 3   | 4U        | 4    | 5         | 6                          |                           | 7     | 8    | 9    |            | 10    | 11   | 12   |  |
| Number of Lanes  | 0                                     | 0    | 1    | 0   | 0         | 0    | 1         | 0                          |                           | 0     | 1    | 0    |            | 0     | 1    | 0    |  |
| Configuration  |                                       |      | LTR  |     |           |      | LTR       |                            |                           |       | LTR  |      |            |       | LTR  |      |  |
| Volume (veh/h)   |                                       | 13   | 1171 | 119 |           | 4    | 653       | 35                         |                           | 19    | 2    | 7    |            | 36    | 3    | 39   |  |
| Percent Heavy Vehicles (%)                                 |                                       | 1    |      |     |           | 1    |           |                            |                           | 1     | 1    | 1    |            | 1     | 1    | 1    |  |
| Proportion Time Blocked                                    |                                       |      |      |     |           |      |           |                            |                           |       |      |      |            |       |      |      |  |
| Percent Grade (%)  |                                       |      |      |     |           |      |           |                            |                           | 0     |      |      |            | 0     |      |      |  |
| Right Turn Channelized                                     |                                       |      |      |     |           |      |           |                            |                           |       |      |      |            |       |      |      |  |
| Median Type   Storage                                      |                                       |      |      |     |           |      | Undivided |                            |                           |       |      |      |            |       |      |      |  |
| Critical and Follow-up Headways                            |                                       |      |      |     |           |      |           |                            |                           |       |      |      |            |       |      |      |  |
| Base Critical Headway (sec)                                |                                       | 4.1  |      |     |           | 4.1  |           |                            |                           | 7.1   | 6.5  | 6.2  |            | 7.1   | 6.5  | 6.2  |  |
| Critical Headway (sec)                                     |                                       | 4.11 |      |     |           | 4.11 |           |                            |                           | 7.11  | 6.51 | 6.21 |            | 7.11  | 6.51 | 6.21 |  |
| Base Follow-Up Headway (sec)                               |                                       | 2.2  |      |     |           | 2.2  |           |                            |                           | 3.5   | 4.0  | 3.3  |            | 3.5   | 4.0  | 3.3  |  |
| Follow-Up Headway (sec)                                    |                                       | 2.23 |      |     |           | 2.23 |           |                            |                           | 3.53  | 4.03 | 3.33 |            | 3.53  | 4.03 | 3.33 |  |
| Delay, Queue Length, and Level of Service                  |                                       |      |      |     |           |      |           |                            |                           |       |      |      |            |       |      |      |  |
| Flow Rate, v (veh/h)                                       |                                       | 14   |      |     |           | 4    |           |                            |                           | 29    |      |      |            | 81    |      |      |  |
| Capacity, c (veh/h)  |                                       | 882  |      |     |           | 513  |           |                            |                           | 45    |      |      |            | 71    |      |      |  |
| v/c Ratio  |                                       | 0.02 |      |     |           | 0.01 |           |                            |                           | 0.65  |      |      |            | 1.14  |      |      |  |
| 95% Queue Length, Q <sub>95</sub> (veh)                    |                                       | 0.0  |      |     |           | 0.0  |           |                            |                           | 2.5   |      |      |            | 6.2   |      |      |  |
| Control Delay (s/veh)                                      |                                       | 9.1  |      | 0.6 |           | 12.1 |           | 0.2                        |                           | 179.9 |      |      |            | 250.1 |      |      |  |
| Level of Service (LOS)                                     |                                       | A    |      | A   |           | B    |           | A                          |                           | F     |      |      |            | F     |      |      |  |
| Approach Delay (s/veh)                                     |                                       | 0.7  |      |     |           | 0.2  |           |                            |                           | 179.9 |      |      |            | 250.1 |      |      |  |
| Approach LOS   |                                       |      |      |     |           |      |           |                            |                           | F     |      |      |            | F     |      |      |  |



Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary     |  |                 |               |                   |        |                 |                                 |       |       |       |       |    |       |       |     |
|--|--|-----------------|---------------|-------------------|--------|-----------------|---------------------------------|-------|-------|-------|-------|----|-------|-------|-----|
| <b>General Information</b>                       |  |                 |               |                   |        |                 | <b>Intersection Information</b> |       |       |       |       |    |       |       |     |
| Agency   | Diane B. Zimmerman Traffic Engineering |                 |               |                   |        |                 | Duration, h                     | 0.25  |       |       |       |    |       |       |     |
| Analyst  | DBZ                                    | Analysis Date   | May 29, 2018  |                   |        | Area Type       | Other                           |       |       |       |       |    |       |       |     |
| Jurisdiction                                     |  | Time Period     | PM Peak       |                   |        | PHF             | 0.94                            |       |       |       |       |    |       |       |     |
| Urban Street                                     | Taylorsville Road                      |                 | Analysis Year | 2030 No Build     |        | Analysis Period | 1> 4:00                         |       |       |       |       |    |       |       |     |
| Intersection                                     | S Pope Lick Road                       |                 | File Name     | PM Pope 30 NB.xus |        |                 |                                 |       |       |       |       |    |       |       |     |
| Project Description                              | Covington By the Park Single Family    |                 |               |                   |        |                 |                                 |       |       |       |       |    |       |       |     |
| <b>Demand Information</b>                        |  |                 |               | EB                |        |                 | WB                              |       |       | NB    |       |    | SB    |       |     |
| Approach Movement                                |  |                 |               | L                 | T      | R               | L                               | T     | R     | L     | T     | R  | L     | T     | R   |
| Demand ( v ), veh/h                              |  |                 |               | 140               | 1333   | 135             | 5                               | 743   | 69    | 22    | 3     | 8  | 98    | 2     | 118 |
| <b>Signal Information</b>                        |  |                 |               |                   |        |                 |                                 |       |       |       |       |    |       |       |     |
| Cycle, s   | 150.0                                  | Reference Phase | 2             |                   |        |                 |                                 |       |       |       |       |    |       |       |     |
| Offset, s  | 0                                      | Reference Point | End           |                   |        |                 |                                 |       |       |       |       |    |       |       |     |
| Uncoordinated                                    | No                                     | Simult. Gap E/W | On            | Green             | 1.2    | 4.8             | 112.5                           | 14.5  | 0.0   | 0.0   |       |    |       |       |     |
| Force Mode                                       | Fixed                                  | Simult. Gap N/S | On            | Yellow            | 4.0    | 0.0             | 4.0                             | 4.0   | 0.0   | 0.0   |       |    |       |       |     |
|  |  |                 |               | Red               | 1.5    | 0.0             | 2.0                             | 1.5   | 0.0   | 0.0   |       |    |       |       |     |
| <b>Timer Results</b>                             |  |                 |               | EBL               | EBT    | WBL             | WBT                             | NBL   | NBT   | SBL   | SBT   |    |       |       |     |
| Assigned Phase                                   |  |                 |               | 5                 | 2      | 1               | 6                               |       | 8     |       | 4     |    |       |       |     |
| Case Number                                      |  |                 |               | 1.1               | 4.0    | 2.0             | 3.0                             |       | 6.0   |       | 6.0   |    |       |       |     |
| Phase Duration, s                                |  |                 |               | 11.5              | 123.3  | 6.7             | 118.5                           |       | 20.0  |       | 20.0  |    |       |       |     |
| Change Period, ( Y+R <sub>c</sub> ), s           |  |                 |               | 5.5               | 6.0    | 5.5             | 6.0                             |       | 5.5   |       | 5.5   |    |       |       |     |
| Max Allow Headway ( MAH ), s                     |  |                 |               | 3.9               | 0.0    | 3.9             | 0.0                             |       | 4.1   |       | 4.1   |    |       |       |     |
| Queue Clearance Time ( g <sub>s</sub> ), s       |  |                 |               | 4.7               |        | 2.4             |                                 |       | 16.5  |       | 13.8  |    |       |       |     |
| Green Extension Time ( g <sub>e</sub> ), s       |  |                 |               | 0.2               | 0.0    | 0.0             | 0.0                             |       | 0.0   |       | 0.1   |    |       |       |     |
| Phase Call Probability                           |  |                 |               | 1.00              |        | 0.20            |                                 |       | 1.00  |       | 1.00  |    |       |       |     |
| Max Out Probability                              |  |                 |               | 0.49              |        | 0.00            |                                 |       | 1.00  |       | 1.00  |    |       |       |     |
| <b>Movement Group Results</b>                    |  |                 |               | EB                |        |                 | WB                              |       |       | NB    |       |    | SB    |       |     |
| Approach Movement                                |  |                 |               | L                 | T      | R               | L                               | T     | R     | L     | T     | R  | L     | T     | R   |
| Assigned Movement                                |  |                 |               | 5                 | 2      | 12              | 1                               | 6     | 16    | 3     | 8     | 18 | 7     | 4     | 14  |
| Adjusted Flow Rate ( v ), veh/h                  |  |                 |               | 149               | 1562   |                 | 5                               | 790   | 73    | 23    | 12    |    | 104   | 128   |     |
| Adjusted Saturation Flow Rate ( s ), veh/h/ln    |  |                 |               | 1795              | 1811   |                 | 1795                            | 1841  | 1585  | 1273  | 1667  |    | 1414  | 1602  |     |
| Queue Service Time ( g <sub>s</sub> ), s         |  |                 |               | 2.7               | 118.3  |                 | 0.4                             | 28.2  | 1.8   | 2.8   | 1.0   |    | 10.9  | 11.7  |     |
| Cycle Queue Clearance Time ( g <sub>c</sub> ), s |  |                 |               | 2.7               | 118.3  |                 | 0.4                             | 28.2  | 1.8   | 14.5  | 1.0   |    | 11.8  | 11.7  |     |
| Green Ratio ( g/C )                              |  |                 |               | 0.80              | 0.79   |                 | 0.01                            | 0.75  | 0.75  | 0.10  | 0.10  |    | 0.10  | 0.10  |     |
| Capacity ( c ), veh/h                            |  |                 |               | 508               | 1416   |                 | 14                              | 1381  | 1189  | 71    | 161   |    | 176   | 155   |     |
| Volume-to-Capacity Ratio ( X )                   |  |                 |               | 0.293             | 1.103  |                 | 0.372                           | 0.572 | 0.062 | 0.328 | 0.073 |    | 0.594 | 0.824 |     |
| Back of Queue ( Q ), ft/ln ( 50 th percentile)   |  |                 |               | 21.1              | 1421.2 |                 | 6.6                             | 246   | 13.4  | 23.5  | 10.2  |    | 102.7 | 148.9 |     |
| Back of Queue ( Q ), veh/ln ( 50 th percentile)  |  |                 |               | 0.8               | 55.1   |                 | 0.3                             | 9.5   | 0.5   | 0.9   | 0.4   |    | 4.1   | 5.9   |     |
| Queue Storage Ratio ( RQ ) ( 50 th percentile)   |  |                 |               | 0.11              | 1.42   |                 | 0.03                            | 0.31  | 0.07  | 0.23  | 0.03  |    | 0.51  | 0.25  |     |
| Uniform Delay ( d <sub>1</sub> ), s/veh          |  |                 |               | 7.0               | 15.9   |                 | 74.0                            | 8.2   | 4.9   | 73.6  | 61.6  |    | 67.0  | 66.5  |     |
| Incremental Delay ( d <sub>2</sub> ), s/veh      |  |                 |               | 0.3               | 57.3   |                 | 15.3                            | 1.7   | 0.1   | 2.6   | 0.2   |    | 5.3   | 29.0  |     |
| Initial Queue Delay ( d <sub>3</sub> ), s/veh    |  |                 |               | 0.0               | 0.0    |                 | 0.0                             | 0.0   | 0.0   | 0.0   | 0.0   |    | 0.0   | 0.0   |     |
| Control Delay ( d ), s/veh                       |  |                 |               | 7.3               | 73.2   |                 | 89.4                            | 9.9   | 5.0   | 76.2  | 61.8  |    | 72.3  | 95.5  |     |
| Level of Service ( LOS )                         |  |                 |               | A                 | F      |                 | F                               | A     | A     | E     | E     |    | E     | F     |     |
| Approach Delay, s/veh / LOS                      |  |                 |               | 67.4              |        | E               | 10.0                            |       | B     | 71.4  |       | E  | 85.0  |       | F   |
| Intersection Delay, s/veh / LOS                  |  |                 |               | 51.4              |        |                 |                                 |       |       | D     |       |    |       |       |     |
| <b>Multimodal Results</b>                        |  |                 |               | EB                |        |                 | WB                              |       |       | NB    |       |    | SB    |       |     |
| Pedestrian LOS Score / LOS                       |  |                 |               | 1.85              |        | B               | 1.86                            |       | B     | 2.15  |       | B  | 1.96  |       | B   |
| Bicycle LOS Score / LOS                          |  |                 |               | 3.31              |        | C               | 1.92                            |       | B     | 0.55  |       | A  | 0.87  |       | A   |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

### HCS7 Signalized Intersection Results Summary

| General Information                             |  |                 |                  | Intersection Information |         |       |       |       |      |       |       |     |    |  |  |
|---|--|-----------------|------------------|--------------------------|---------|-------|-------|-------|------|-------|-------|-----|----|--|--|
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |                  | Duration, h              | 0.25    |       |       |       |      |       |       |     |    |  |  |
| Analyst   | DBZ                                    | Analysis Date   | May 29, 2018     | Area Type                | Other   |       |       |       |      |       |       |     |    |  |  |
| Jurisdiction                                    |  | Time Period     | PM Peak          | PHF                      | 0.94    |       |       |       |      |       |       |     |    |  |  |
| Urban Street                                    | Taylorsville Road                      | Analysis Year   | 2030             | Analysis Period          | 1> 4:00 |       |       |       |      |       |       |     |    |  |  |
| Intersection                                    | S Pope Lick Road                       | File Name       | PM Pope 30 B.xus |                          |         |       |       |       |      |       |       |     |    |  |  |
| Project Description                             | Covington By the Park Single Family    |                 |                  |                          |         |       |       |       |      |       |       |     |    |  |  |
| Demand Information                              |  |                 |                  | EB                       |         |       | WB    |       |      | NB    |       |     | SB |  |  |
| Approach Movement                               | L                                      | T               | R                | L                        | T       | R     | L     | T     | R    | L     | T     | R   |    |  |  |
| Demand (v), veh/h                               | 140                                    | 1633            | 135              | 5                        | 860     | 80    | 22    | 3     | 8    | 117   | 2     | 118 |    |  |  |
| Signal Information                              |  |                 |                  |                          |         |       |       |       |      |       |       |     |    |  |  |
| Cycle, s  | 150.0                                  | Reference Phase | 2                |                          |         |       |       |       |      |       |       |     |    |  |  |
| Offset, s                                       | 0                                      | Reference Point | End              |                          |         |       |       |       |      |       |       |     |    |  |  |
| Uncoordinated                                   | No                                     | Simult. Gap E/W | On               | Green                    | 1.2     | 4.8   | 112.5 | 14.5  | 0.0  | 0.0   |       |     |    |  |  |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On               | Yellow                   | 4.0     | 0.0   | 4.0   | 4.0   | 0.0  | 0.0   |       |     |    |  |  |
|   |  |                 |                  | Red                      | 1.5     | 0.0   | 2.0   | 1.5   | 0.0  | 0.0   |       |     |    |  |  |
| Timer Results                                   |  |                 |                  | EBL                      | EBT     | WBL   | WBT   | NBL   | NBT  | SBL   | SBT   |     |    |  |  |
| Assigned Phase                                  |  |                 |                  | 5                        | 2       | 1     | 6     |       | 8    |       | 4     |     |    |  |  |
| Case Number                                     |  |                 |                  | 1.1                      | 4.0     | 2.0   | 3.0   |       | 6.0  |       | 6.0   |     |    |  |  |
| Phase Duration, s                               |  |                 |                  | 11.5                     | 123.3   | 6.7   | 118.5 |       | 20.0 |       | 20.0  |     |    |  |  |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |                  | 5.5                      | 6.0     | 5.5   | 6.0   |       | 5.5  |       | 5.5   |     |    |  |  |
| Max Allow Headway (MAH), s                      |  |                 |                  | 3.9                      | 0.0     | 3.9   | 0.0   |       | 4.0  |       | 4.0   |     |    |  |  |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |                  | 4.7                      |         | 2.4   |       |       | 16.5 |       | 16.1  |     |    |  |  |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |                  | 0.2                      | 0.0     | 0.0   | 0.0   |       | 0.0  |       | 0.0   |     |    |  |  |
| Phase Call Probability                          |  |                 |                  | 1.00                     |         | 0.20  |       |       | 1.00 |       | 1.00  |     |    |  |  |
| Max Out Probability                             |  |                 |                  | 0.49                     |         | 0.00  |       |       | 1.00 |       | 1.00  |     |    |  |  |
| Movement Group Results                          |  |                 |                  | EB                       |         |       | WB    |       |      | NB    |       |     | SB |  |  |
| Approach Movement                               | L                                      | T               | R                | L                        | T       | R     | L     | T     | R    | L     | T     | R   |    |  |  |
| Assigned Movement                               | 5                                      | 2               | 12               | 1                        | 6       | 16    | 3     | 8     | 18   | 7     | 4     | 14  |    |  |  |
| Adjusted Flow Rate (v), veh/h                   | 149                                    | 1881            |                  | 5                        | 915     | 85    | 23    | 12    |      | 124   | 128   |     |    |  |  |
| Adjusted Saturation Flow Rate (s), veh/h/ln     | 1795                                   | 1816            |                  | 1795                     | 1841    | 1585  | 1273  | 1667  |      | 1414  | 1602  |     |    |  |  |
| Queue Service Time (g <sub>s</sub> ), s         | 2.7                                    | 118.3           |                  | 0.4                      | 37.0    | 2.1   | 2.8   | 1.0   |      | 13.2  | 11.7  |     |    |  |  |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s | 2.7                                    | 118.3           |                  | 0.4                      | 37.0    | 2.1   | 14.5  | 1.0   |      | 14.1  | 11.7  |     |    |  |  |
| Green Ratio (g/C)                               | 0.80                                   | 0.79            |                  | 0.01                     | 0.75    | 0.75  | 0.10  | 0.10  |      | 0.10  | 0.10  |     |    |  |  |
| Capacity (c), veh/h                             | 429                                    | 1420            |                  | 14                       | 1381    | 1189  | 71    | 161   |      | 176   | 155   |     |    |  |  |
| Volume-to-Capacity Ratio (X)                    | 0.347                                  | 1.325           |                  | 0.372                    | 0.663   | 0.072 | 0.328 | 0.073 |      | 0.709 | 0.824 |     |    |  |  |
| Back of Queue (Q), ft/ln (50 th percentile)     | 34.3                                   | 2379.2          |                  | 6.6                      | 325.2   | 15.6  | 23.5  | 10.2  |      | 131.7 | 148.9 |     |    |  |  |
| Back of Queue (Q), veh/ln (50 th percentile)    | 1.4                                    | 92.2            |                  | 0.3                      | 12.6    | 0.6   | 0.9   | 0.4   |      | 5.2   | 5.9   |     |    |  |  |
| Queue Storage Ratio (RQ) (50 th percentile)     | 0.17                                   | 2.38            |                  | 0.03                     | 0.41    | 0.08  | 0.23  | 0.03  |      | 0.66  | 0.25  |     |    |  |  |
| Uniform Delay (d <sub>1</sub> ), s/veh          | 9.8                                    | 15.9            |                  | 74.0                     | 9.3     | 5.0   | 73.6  | 61.6  |      | 68.1  | 66.5  |     |    |  |  |
| Incremental Delay (d <sub>2</sub> ), s/veh      | 0.5                                    | 151.0           |                  | 15.3                     | 2.5     | 0.1   | 2.6   | 0.2   |      | 12.4  | 29.0  |     |    |  |  |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    | 0.0                                    | 0.0             |                  | 0.0                      | 0.0     | 0.0   | 0.0   | 0.0   |      | 0.0   | 0.0   |     |    |  |  |
| Control Delay (d), s/veh                        | 10.3                                   | 166.9           |                  | 89.4                     | 11.8    | 5.1   | 76.2  | 61.8  |      | 80.4  | 95.5  |     |    |  |  |
| Level of Service (LOS)                          | B                                      | F               |                  | F                        | B       | A     | E     | E     |      | F     | F     |     |    |  |  |
| Approach Delay, s/veh / LOS                     | 155.4                                  |                 | F                | 11.7                     |         | B     | 71.4  |       | E    | 88.0  |       | F   |    |  |  |
| Intersection Delay, s/veh / LOS                 |  |                 |                  | 105.9                    |         |       |       |       |      | F     |       |     |    |  |  |
| Multimodal Results                              |  |                 |                  | EB                       |         |       | WB    |       |      | NB    |       |     | SB |  |  |
| Pedestrian LOS Score / LOS                      | 1.85                                   |                 | B                | 1.86                     |         | B     | 2.15  |       | B    | 1.96  |       | B   |    |  |  |
| Bicycle LOS Score / LOS                         | 3.84                                   |                 | D                | 2.15                     |         | B     | 0.55  |       | A    | 0.90  |       | A   |    |  |  |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |              |     |                 |                                 |      |       |      |       |       |       |       |     |
|---|--|-----------------|---------------|--------------|-----|-----------------|---------------------------------|------|-------|------|-------|-------|-------|-------|-----|
| <b>General Information</b>                      |  |                 |               |              |     |                 | <b>Intersection Information</b> |      |       |      |       |       |       |       |     |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |              |     |                 | Duration, h                     | 0.25 |       |      |       |       |       |       |     |
| Analyst   | DBZ                                    | Analysis Date   | 3/8/2018      |              |     | Area Type       | Other                           |      |       |      |       |       |       |       |     |
| Jurisdiction                                    |  | Time Period     |               |              |     | PHF             | 0.96                            |      |       |      |       |       |       |       |     |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2018         |     | Analysis Period | 1> 7:00                         |      |       |      |       |       |       |       |     |
| Intersection                                    | Taylorsville Lake Road                 |                 | File Name     | TL AM 18.xus |     |                 |                                 |      |       |      |       |       |       |       |     |
| Project Description                             | Covington by the Park                  |                 |               |              |     |                 |                                 |      |       |      |       |       |       |       |     |
| <b>Demand Information</b>                       |  |                 |               | EB           |     |                 | WB                              |      |       | NB   |       | SB    |       |       |     |
| Approach Movement                               |  |                 |               | L            | T   | R               | L                               | T    | R     | L    | T     | R     | L     | T     | R   |
| Demand (v), veh/h                               |  |                 |               |              |     |                 | 21                              |      | 230   |      |       | 1062  | 52    | 145   | 185 |
| <b>Signal Information</b>                       |  |                 |               |              |     |                 |                                 |      |       |      |       |       |       |       |     |
| Cycle, s  | 116.4                                  | Reference Phase | 2             |              |     |                 |                                 |      |       |      |       |       |       |       |     |
| Offset, s                                       | 0                                      | Reference Point | End           |              |     |                 |                                 |      |       |      |       |       |       |       |     |
| Uncoordinated                                   | Yes                                    | Simult. Gap E/W | On            | Green        | 6.0 | 71.6            | 20.0                            | 0.0  | 0.0   | 0.0  | 0.0   |       |       |       |     |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            | Yellow       | 3.5 | 5.0             | 3.5                             | 0.0  | 0.0   | 0.0  | 0.0   |       |       |       |     |
|   |  |                 |               | Red          | 2.5 | 1.3             | 3.0                             | 0.0  | 0.0   | 0.0  | 0.0   |       |       |       |     |
| <b>Timer Results</b>                            |  |                 |               | EBL          | EBT | WBL             | WBT                             | NBL  | NBT   | SBL  | SBT   |       |       |       |     |
| Assigned Phase                                  |  |                 |               |              |     |                 | 8                               |      | 2     | 1    | 6     |       |       |       |     |
| Case Number                                     |  |                 |               |              |     |                 | 9.0                             |      | 7.3   | 1.0  | 4.0   |       |       |       |     |
| Phase Duration, s                               |  |                 |               |              |     |                 | 26.5                            |      | 77.9  | 12.0 | 89.9  |       |       |       |     |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               |              |     |                 | 6.5                             |      | 6.3   | 6.0  | 6.3   |       |       |       |     |
| Max Allow Headway (MAH), s                      |  |                 |               |              |     |                 | 3.8                             |      | 3.4   | 3.5  | 3.4   |       |       |       |     |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               |              |     |                 | 19.1                            |      | 65.9  | 5.4  | 5.8   |       |       |       |     |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               |              |     |                 | 0.6                             |      | 5.0   | 0.3  | 5.3   |       |       |       |     |
| Phase Call Probability                          |  |                 |               |              |     |                 | 1.00                            |      | 1.00  | 0.99 | 1.00  |       |       |       |     |
| Max Out Probability                             |  |                 |               |              |     |                 | 0.00                            |      | 0.04  | 0.00 | 0.00  |       |       |       |     |
| <b>Movement Group Results</b>                   |  |                 |               | EB           |     |                 | WB                              |      |       | NB   |       | SB    |       |       |     |
| Approach Movement                               |  |                 |               | L            | T   | R               | L                               | T    | R     | L    | T     | R     | L     | T     | R   |
| Assigned Movement                               |  |                 |               |              |     |                 | 3                               |      | 18    |      | 2     | 12    | 1     | 6     |     |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               |              |     |                 | 22                              |      | 240   |      | 1106  | 54    | 151   | 193   |     |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               |              |     |                 | 1795                            |      | 1598  |      | 1885  | 1598  | 1795  | 1885  |     |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               |              |     |                 | 1.2                             |      | 17.1  |      | 63.9  | 1.6   | 3.4   | 3.8   |     |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               |              |     |                 | 1.2                             |      | 17.1  |      | 63.9  | 1.6   | 3.4   | 3.8   |     |
| Green Ratio (g/C)                               |  |                 |               |              |     |                 | 0.17                            |      | 0.17  |      | 0.62  | 0.62  | 0.69  | 0.72  |     |
| Capacity (c), veh/h                             |  |                 |               |              |     |                 | 309                             |      | 275   |      | 1161  | 984   | 189   | 1355  |     |
| Volume-to-Capacity Ratio (X)                    |  |                 |               |              |     |                 | 0.071                           |      | 0.871 |      | 0.952 | 0.055 | 0.801 | 0.142 |     |
| Back of Queue (Q), ft/ln (50 th percentile)     |  |                 |               |              |     |                 | 13                              |      | 176.4 |      | 673   | 12.1  | 71.4  | 28.1  |     |
| Back of Queue (Q), veh/ln (50 th percentile)    |  |                 |               |              |     |                 | 0.5                             |      | 7.0   |      | 26.7  | 0.5   | 2.8   | 1.1   |     |
| Queue Storage Ratio (RQ) (50 th percentile)     |  |                 |               |              |     |                 | 0.03                            |      | 0.44  |      | 1.68  | 0.03  | 0.16  | 0.06  |     |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               |              |     |                 | 40.7                            |      | 47.3  |      | 20.9  | 8.9   | 28.9  | 5.2   |     |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               |              |     |                 | 0.1                             |      | 7.0   |      | 12.1  | 0.0   | 6.2   | 0.0   |     |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               |              |     |                 | 0.0                             |      | 0.0   |      | 0.0   | 0.0   | 0.0   | 0.0   |     |
| Control Delay (d), s/veh                        |  |                 |               |              |     |                 | 40.8                            |      | 54.3  |      | 33.0  | 9.0   | 35.2  | 5.2   |     |
| Level of Service (LOS)                          |  |                 |               |              |     |                 | D                               |      | D     |      | C     | A     | D     | A     |     |
| Approach Delay, s/veh / LOS                     |  |                 |               | 0.0          |     |                 | 53.1                            | D    |       | 31.9 | C     |       | 18.4  | B     |     |
| Intersection Delay, s/veh / LOS                 |  |                 |               |              |     |                 | 32.4                            |      |       |      |       | C     |       |       |     |
| <b>Multimodal Results</b>                       |  |                 |               | EB           |     |                 | WB                              |      |       | NB   |       | SB    |       |       |     |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.96         | B   |                 | 1.97                            | B    |       | 1.88 | B     |       | 0.66  | A     |     |
| Bicycle LOS Score / LOS                         |  |                 |               |              |     |                 | F                               |      |       | 2.40 | B     |       | 1.05  | A     |     |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

**HCS7 Signalized Intersection Results Summary**

| General Information |  |  |               |               |                 |  |             |                 |         |  |  |  | Intersection Information |  |  |  |  |  |
|---------------------|--|--|---------------|---------------|-----------------|--|-------------|-----------------|---------|--|--|--|--------------------------|--|--|--|--|--|
| Agency              | Diane B. Zimmerman Traffic Engineering |  |               |               |                 |  | Duration, h | 0.25            |         |  |  |  |                          |  |  |  |  |  |
| Analyst             | DBZ                                    |  | Analysis Date | Apr 23, 2018  |                 |  | Area Type   | Other           |         |  |  |  |                          |  |  |  |  |  |
| Jurisdiction        |  |  |               |               |                 |  | PHF         | 0.96            |         |  |  |  |                          |  |  |  |  |  |
| Urban Street        | Taylorsville Road                      |  |               | Analysis Year | 2030 No Build   |  |             | Analysis Period | 1> 7:00 |  |  |  |                          |  |  |  |  |  |
| Intersection        | Taylorsville Lake Road                 |  |               | File Name     | TL AM 30 NB.xus |  |             |                 |         |  |  |  |                          |  |  |  |  |  |
| Project Description | Covington by the Park                  |  |               |               |                 |  |             |                 |         |  |  |  |                          |  |  |  |  |  |

| Demand Information  |  |    |   |   |    |   |     |    |      |    |     |     |   |
|---------------------|--|----|---|---|----|---|-----|----|------|----|-----|-----|---|
|                     |  | EB |   |   | WB |   |     | NB |      |    | SB  |     |   |
| Approach Movement   |  | L  | T | R | L  | T | R   | L  | T    | R  | L   | T   | R |
| Demand ( v ), veh/h |  |    |   |   | 24 |   | 259 |    | 1197 | 59 | 163 | 208 |   |

| Signal Information |       |                 |     |        |      |      |      |     |     |     |  |  |  |
|--------------------|-------|-----------------|-----|--------|------|------|------|-----|-----|-----|--|--|--|
| Cycle, s           | 144.5 | Reference Phase | 2   |        |      |      |      |     |     |     |  |  |  |
| Offset, s          | 0     | Reference Point | End | Green  | 11.6 | 90.0 | 24.2 | 0.0 | 0.0 | 0.0 |  |  |  |
| Uncoordinated      | Yes   | Simult. Gap E/W | On  | Yellow | 3.5  | 5.0  | 3.5  | 0.0 | 0.0 | 0.0 |  |  |  |
| Force Mode         | Fixed | Simult. Gap N/S | On  | Red    | 2.5  | 1.3  | 3.0  | 0.0 | 0.0 | 0.0 |  |  |  |

| Timer Results                              |  |     |  |  |     |  |  |      |  |  |      |  |      |       |
|--|--|-----|--|--|-----|--|--|------|--|--|------|--|------|-------|
|  |  | EBL |  |  | EBT |  |  | WBL  |  |  | WBT  |  |      |       |
| Assigned Phase                             |  |     |  |  |     |  |  | 8    |  |  | 2    |  | 1    | 6     |
| Case Number                                |  |     |  |  |     |  |  | 9.0  |  |  | 7.3  |  | 1.0  | 4.0   |
| Phase Duration, s                          |  |     |  |  |     |  |  | 30.7 |  |  | 96.3 |  | 17.6 | 113.9 |
| Change Period, ( Y+R <sub>c</sub> ), s     |  |     |  |  |     |  |  | 6.5  |  |  | 6.3  |  | 6.0  | 6.3   |
| Max Allow Headway ( MAH ), s               |  |     |  |  |     |  |  | 3.8  |  |  | 3.4  |  | 3.5  | 3.4   |
| Queue Clearance Time ( g <sub>s</sub> ), s |  |     |  |  |     |  |  | 23.7 |  |  | 93.0 |  | 11.5 | 6.7   |
| Green Extension Time ( g <sub>e</sub> ), s |  |     |  |  |     |  |  | 0.5  |  |  | 0.0  |  | 0.1  | 7.1   |
| Phase Call Probability                     |  |     |  |  |     |  |  | 1.00 |  |  | 1.00 |  | 1.00 | 1.00  |
| Max Out Probability                        |  |     |  |  |     |  |  | 0.20 |  |  | 1.00 |  | 0.99 | 0.00  |

| Movement Group Results                           |  |     |   |   |       |   |       |    |        |       |       |       |   |
|--|--|-----|---|---|-------|---|-------|----|--------|-------|-------|-------|---|
|  |  | EB  |   |   | WB    |   |       | NB |        |       | SB    |       |   |
| Approach Movement                                |  | L   | T | R | L     | T | R     | L  | T      | R     | L     | T     | R |
| Assigned Movement                                |  |     |   |   | 3     |   | 18    |    | 2      | 12    | 1     | 6     |   |
| Adjusted Flow Rate ( v ), veh/h                  |  |     |   |   | 25    |   | 270   |    | 1247   | 61    | 170   | 217   |   |
| Adjusted Saturation Flow Rate ( s ), veh/h/ln    |  |     |   |   | 1795  |   | 1598  |    | 1885   | 1598  | 1795  | 1885  |   |
| Queue Service Time ( g <sub>s</sub> ), s         |  |     |   |   | 1.7   |   | 21.7  |    | 91.0   | 2.2   | 9.5   | 4.7   |   |
| Cycle Queue Clearance Time ( g <sub>c</sub> ), s |  |     |   |   | 1.7   |   | 21.7  |    | 91.0   | 2.2   | 9.5   | 4.7   |   |
| Green Ratio ( g/C )                              |  |     |   |   | 0.17  |   | 0.25  |    | 0.63   | 0.63  | 0.72  | 0.75  |   |
| Capacity ( c ), veh/h                            |  |     |   |   | 300   |   | 417   |    | 1187   | 995   | 194   | 1416  |   |
| Volume-to-Capacity Ratio ( X )                   |  |     |   |   | 0.083 |   | 0.647 |    | 1.050  | 0.062 | 0.877 | 0.153 |   |
| Back of Queue ( Q ), ft/ln ( 50 th percentile)   |  |     |   |   | 19    |   | 216   |    | 1214.3 | 18.1  | 183.6 | 37.2  |   |
| Back of Queue ( Q ), veh/ln ( 50 th percentile)  |  |     |   |   | 0.8   |   | 8.6   |    | 48.2   | 0.7   | 7.3   | 1.5   |   |
| Queue Storage Ratio ( RQ ) ( 50 th percentile)   |  |     |   |   | 0.05  |   | 0.54  |    | 3.04   | 0.05  | 0.41  | 0.08  |   |
| Uniform Delay ( d <sub>1</sub> ), s/veh          |  |     |   |   | 50.8  |   | 47.5  |    | 26.8   | 10.7  | 52.1  | 5.2   |   |
| Incremental Delay ( d <sub>2</sub> ), s/veh      |  |     |   |   | 0.1   |   | 2.1   |    | 40.4   | 0.0   | 24.6  | 0.0   |   |
| Initial Queue Delay ( d <sub>3</sub> ), s/veh    |  |     |   |   | 0.0   |   | 0.0   |    | 0.0    | 0.0   | 0.0   | 0.0   |   |
| Control Delay ( d ), s/veh                       |  |     |   |   | 50.9  |   | 49.6  |    | 67.2   | 10.7  | 76.7  | 5.2   |   |
| Level of Service ( LOS )                         |  |     |   |   | D     |   | D     |    | F      | B     | E     | A     |   |
| Approach Delay, s/veh / LOS                      |  | 0.0 |   |   | 49.7  |   | D     |    | 64.6   | E     | 36.6  |       | D |
| Intersection Delay, s/veh / LOS                  |  |     |   |   | 56.9  |   |       |    |        | E     |       |       |   |

| Multimodal Results         |  |      |  |   |      |  |   |      |  |   |      |  |   |
|----------------------------|--|------|--|---|------|--|---|------|--|---|------|--|---|
|                            |  | EB   |  |   | WB   |  |   | NB   |  |   | SB   |  |   |
| Pedestrian LOS Score / LOS |  | 1.97 |  | B | 1.97 |  | B | 1.89 |  | B | 0.66 |  | A |
| Bicycle LOS Score / LOS    |  |      |  |   |      |  | F | 2.65 |  | C | 1.13 |  | A |

Covington by the Park  
4501 Taylorsville Lake Road  
Traffic Impact Study

### HCS7 Signalized Intersection Results Summary

| General Information |  |  |               |                |  |  |  |                 |             |      |  |  | Intersection Information |  |  |  |  |
|---------------------|--|--|---------------|----------------|--|--|--|-----------------|-------------|------|--|--|--------------------------|--|--|--|--|
| Agency              | Diane B. Zimmerman Traffic Engineering |  |               |                |  |  |  |                 | Duration, h | 0.25 |  |  |                          |  |  |  |  |
| Analyst             | DBZ                                    |  | Analysis Date | Apr 23, 2018   |  |  |  | Area Type       | Other       |      |  |  |                          |  |  |  |  |
| Jurisdiction        |  |  | Time Period   | AM Peak        |  |  |  | PHF             | 0.96        |      |  |  |                          |  |  |  |  |
| Urban Street        | Taylorsville Road                      |  | Analysis Year | 2030 Build     |  |  |  | Analysis Period | 1> 7:00     |      |  |  |                          |  |  |  |  |
| Intersection        | Taylorsville Lake Road                 |  | File Name     | TL AM 30 B.xus |  |  |  |                 |             |      |  |  |                          |  |  |  |  |
| Project Description | Covington by the Park Single Family    |  |               |                |  |  |  |                 |             |      |  |  |                          |  |  |  |  |

| Demand Information  |  |    |   |   |    |   |     |    |      |    |     |     |   |
|---------------------|--|----|---|---|----|---|-----|----|------|----|-----|-----|---|
|                     |  | EB |   |   | WB |   |     | NB |      |    | SB  |     |   |
| Approach Movement   |  | L  | T | R | L  | T | R   | L  | T    | R  | L   | T   | R |
| Demand ( v ), veh/h |  |    |   |   | 30 |   | 259 |    | 1486 | 76 | 163 | 304 |   |

| Signal Information |       |                 |     |        |      |      |      |     |     |     |  |  |  |
|--------------------|-------|-----------------|-----|--------|------|------|------|-----|-----|-----|--|--|--|
| Cycle, s           | 144.5 | Reference Phase | 2   |        |      |      |      |     |     |     |  |  |  |
| Offset, s          | 0     | Reference Point | End | Green  | 11.6 | 90.0 | 24.2 | 0.0 | 0.0 | 0.0 |  |  |  |
| Uncoordinated      | Yes   | Simult. Gap E/W | On  | Yellow | 3.5  | 5.0  | 3.5  | 0.0 | 0.0 | 0.0 |  |  |  |
| Force Mode         | Fixed | Simult. Gap N/S | On  | Red    | 2.5  | 1.3  | 3.0  | 0.0 | 0.0 | 0.0 |  |  |  |

| Timer Results                              |  |     |     |     |      |     |      |      |       |  |  |  |
|--|--|-----|-----|-----|------|-----|------|------|-------|--|--|--|
|  |  | EBL | EBT | WBL | WBT  | NBL | NBT  | SBL  | SBT   |  |  |  |
| Assigned Phase                             |  |     |     |     | 8    |     | 2    | 1    | 6     |  |  |  |
| Case Number                                |  |     |     |     | 9.0  |     | 7.3  | 1.0  | 4.0   |  |  |  |
| Phase Duration, s                          |  |     |     |     | 30.7 |     | 96.3 | 17.6 | 113.9 |  |  |  |
| Change Period, ( Y+R <sub>c</sub> ), s     |  |     |     |     | 6.5  |     | 6.3  | 6.0  | 6.3   |  |  |  |
| Max Allow Headway ( MAH ), s               |  |     |     |     | 3.8  |     | 3.4  | 3.5  | 3.4   |  |  |  |
| Queue Clearance Time ( g <sub>s</sub> ), s |  |     |     |     | 23.7 |     | 93.0 | 11.5 | 9.3   |  |  |  |
| Green Extension Time ( g <sub>e</sub> ), s |  |     |     |     | 0.5  |     | 0.0  | 0.1  | 15.0  |  |  |  |
| Phase Call Probability                     |  |     |     |     | 1.00 |     | 1.00 | 1.00 | 1.00  |  |  |  |
| Max Out Probability                        |  |     |     |     | 0.20 |     | 1.00 | 0.99 | 0.01  |  |  |  |

| Movement Group Results                           |  |       |   |   |       |   |       |    |        |       |       |       |   |
|--|--|-------|---|---|-------|---|-------|----|--------|-------|-------|-------|---|
|  |  | EB    |   |   | WB    |   |       | NB |        |       | SB    |       |   |
|  |  | L     | T | R | L     | T | R     | L  | T      | R     | L     | T     | R |
| Assigned Movement                                |  |       |   |   | 3     |   | 18    |    | 2      | 12    | 1     | 6     |   |
| Adjusted Flow Rate ( v ), veh/h                  |  |       |   |   | 31    |   | 270   |    | 1548   | 79    | 170   | 317   |   |
| Adjusted Saturation Flow Rate ( s ), veh/h/ln    |  |       |   |   | 1795  |   | 1598  |    | 1885   | 1598  | 1795  | 1885  |   |
| Queue Service Time ( g <sub>s</sub> ), s         |  |       |   |   | 2.1   |   | 21.7  |    | 91.0   | 2.8   | 9.5   | 7.3   |   |
| Cycle Queue Clearance Time ( g <sub>c</sub> ), s |  |       |   |   | 2.1   |   | 21.7  |    | 91.0   | 2.8   | 9.5   | 7.3   |   |
| Green Ratio ( g/C )                              |  |       |   |   | 0.17  |   | 0.25  |    | 0.63   | 0.63  | 0.72  | 0.75  |   |
| Capacity ( c ), veh/h                            |  |       |   |   | 300   |   | 417   |    | 1187   | 995   | 194   | 1416  |   |
| Volume-to-Capacity Ratio ( X )                   |  |       |   |   | 0.104 |   | 0.647 |    | 1.304  | 0.080 | 0.877 | 0.224 |   |
| Back of Queue ( Q ), ft/ln ( 50 th percentile)   |  |       |   |   | 23.8  |   | 216   |    | 2067.2 | 23.5  | 183.6 | 57.8  |   |
| Back of Queue ( Q ), veh/ln ( 50 th percentile)  |  |       |   |   | 0.9   |   | 8.6   |    | 82.0   | 0.9   | 7.3   | 2.3   |   |
| Queue Storage Ratio ( RQ ) ( 50 th percentile)   |  |       |   |   | 0.06  |   | 0.54  |    | 5.17   | 0.06  | 0.41  | 0.13  |   |
| Uniform Delay ( d <sub>1</sub> ), s/veh          |  |       |   |   | 51.0  |   | 47.5  |    | 26.8   | 10.8  | 52.1  | 5.5   |   |
| Incremental Delay ( d <sub>2</sub> ), s/veh      |  |       |   |   | 0.1   |   | 2.1   |    | 143.1  | 0.0   | 24.6  | 0.1   |   |
| Initial Queue Delay ( d <sub>3</sub> ), s/veh    |  |       |   |   | 0.0   |   | 0.0   |    | 0.0    | 0.0   | 0.0   | 0.0   |   |
| Control Delay ( d ), s/veh                       |  |       |   |   | 51.1  |   | 49.6  |    | 169.9  | 10.9  | 76.7  | 5.6   |   |
| Level of Service ( LOS )                         |  |       |   |   | D     |   | D     |    | F      | B     | E     | A     |   |
| Approach Delay, s/veh / LOS                      |  | 0.0   |   |   | 49.8  |   | D     |    | 162.2  | F     | 30.4  | C     |   |
| Intersection Delay, s/veh / LOS                  |  | 121.6 |   |   |       |   |       | F  |        |       |       |       |   |

| Multimodal Results         |  |      |  |   |      |  |   |      |  |   |      |  |   |
|----------------------------|--|------|--|---|------|--|---|------|--|---|------|--|---|
|                            |  | EB   |  |   | WB   |  |   | NB   |  |   | SB   |  |   |
| Pedestrian LOS Score / LOS |  | 1.97 |  | B | 1.97 |  | B | 1.89 |  | B | 0.66 |  | A |
| Bicycle LOS Score / LOS    |  |      |  |   |      |  | F | 3.17 |  | C | 1.29 |  | A |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |              |        |                 |                                 |      |       |       |       |       |       |   |   |
|---|--|-----------------|---------------|--------------|--------|-----------------|---------------------------------|------|-------|-------|-------|-------|-------|---|---|
| <b>General Information</b>                      |  |                 |               |              |        |                 | <b>Intersection Information</b> |      |       |       |       |       |       |   |   |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |              |        |                 | Duration, h                     | 0.25 |       |       |       |       |       |   |   |
| Analyst   | DBZ                                    | Analysis Date   | 3/8/2018      |              |        | Area Type       | Other                           |      |       |       |       |       |       |   |   |
| Jurisdiction                                    |  | Time Period     | PM Peak       |              |        | PHF             | 0.94                            |      |       |       |       |       |       |   |   |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2018         |        | Analysis Period | 1> 7:00                         |      |       |       |       |       |       |   |   |
| Intersection                                    | Taylorsville Lake Road                 |                 | File Name     | TL PM 18.xus |        |                 |                                 |      |       |       |       |       |       |   |   |
| Project Description                             | Covington by the Park                  |                 |               |              |        |                 |                                 |      |       |       |       |       |       |   |   |
| <b>Demand Information</b>                       |  |                 |               | EB           |        |                 | WB                              |      |       | NB    |       | SB    |       |   |   |
| Approach Movement                               |  |                 |               | L            | T      | R               | L                               | T    | R     | L     | T     | R     | L     | T | R |
| Demand (v), veh/h                               |  |                 |               |              |        |                 | 369                             |      | 263   | 443   | 31    | 215   | 1004  |   |   |
| <b>Signal Information</b>                       |  |                 |               |              |        |                 |                                 |      |       |       |       |       |       |   |   |
| Cycle, s  | 92.6                                   | Reference Phase | 2             |              |        |                 |                                 |      |       |       |       |       |       |   |   |
| Offset, s                                       | 0                                      | Reference Point | End           |              |        |                 |                                 |      |       |       |       |       |       |   |   |
| Uncoordinated                                   | Yes                                    | Simult. Gap E/W | On            |              | Green  | 8.5             | 41.8                            | 23.5 | 0.0   | 0.0   | 0.0   |       |       |   |   |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            |              | Yellow | 3.5             | 5.0                             | 3.5  | 0.0   | 0.0   | 0.0   |       |       |   |   |
|   |  |                 |               |              | Red    | 2.5             | 1.3                             | 3.0  | 0.0   | 0.0   | 0.0   |       |       |   |   |
| <b>Timer Results</b>                            |  |                 |               | EBL          | EBT    | WBL             | WBT                             | NBL  | NBT   | SBL   | SBT   |       |       |   |   |
| Assigned Phase                                  |  |                 |               |              |        |                 | 8                               |      | 2     | 1     | 6     |       |       |   |   |
| Case Number                                     |  |                 |               |              |        |                 | 9.0                             |      | 7.3   | 1.0   | 4.0   |       |       |   |   |
| Phase Duration, s                               |  |                 |               |              |        |                 | 30.0                            |      | 48.1  | 14.5  | 62.6  |       |       |   |   |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               |              |        |                 | 6.5                             |      | 6.3   | 6.0   | 6.3   |       |       |   |   |
| Max Allow Headway (MAH), s                      |  |                 |               |              |        |                 | 3.6                             |      | 3.4   | 3.5   | 3.4   |       |       |   |   |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               |              |        |                 | 21.5                            |      | 19.0  | 7.9   | 49.7  |       |       |   |   |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               |              |        |                 | 1.7                             |      | 6.1   | 0.5   | 6.0   |       |       |   |   |
| Phase Call Probability                          |  |                 |               |              |        |                 | 1.00                            |      | 1.00  | 1.00  | 1.00  |       |       |   |   |
| Max Out Probability                             |  |                 |               |              |        |                 | 0.03                            |      | 0.00  | 0.00  | 0.01  |       |       |   |   |
| <b>Movement Group Results</b>                   |  |                 |               | EB           |        |                 | WB                              |      |       | NB    |       | SB    |       |   |   |
| Approach Movement                               |  |                 |               | L            | T      | R               | L                               | T    | R     | L     | T     | R     | L     | T | R |
| Assigned Movement                               |  |                 |               |              |        |                 | 3                               |      | 18    | 2     | 12    | 1     | 6     |   |   |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               |              |        |                 | 393                             |      | 280   | 471   | 33    | 229   | 1068  |   |   |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               |              |        |                 | 1795                            |      | 1598  | 1885  | 1598  | 1795  | 1885  |   |   |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               |              |        |                 | 19.5                            |      | 14.8  | 17.0  | 1.1   | 5.9   | 47.7  |   |   |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               |              |        |                 | 19.5                            |      | 14.8  | 17.0  | 1.1   | 5.9   | 47.7  |   |   |
| Green Ratio (g/C)                               |  |                 |               |              |        |                 | 0.25                            |      | 0.25  | 0.45  | 0.45  | 0.57  | 0.61  |   |   |
| Capacity (c), veh/h                             |  |                 |               |              |        |                 | 456                             |      | 406   | 854   | 724   | 498   | 1148  |   |   |
| Volume-to-Capacity Ratio (X)                    |  |                 |               |              |        |                 | 0.861                           |      | 0.690 | 0.552 | 0.046 | 0.459 | 0.930 |   |   |
| Back of Queue (Q), ft/ln (50 th percentile)     |  |                 |               |              |        |                 | 215.9                           |      | 136   | 163.7 | 8.7   | 49.4  | 427.4 |   |   |
| Back of Queue (Q), veh/ln (50 th percentile)    |  |                 |               |              |        |                 | 8.6                             |      | 5.4   | 6.5   | 0.3   | 2.0   | 17.0  |   |   |
| Queue Storage Ratio (RQ) (50 th percentile)     |  |                 |               |              |        |                 | 0.54                            |      | 0.34  | 0.41  | 0.02  | 0.11  | 0.95  |   |   |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               |              |        |                 | 33.3                            |      | 31.5  | 18.6  | 14.3  | 12.5  | 16.5  |   |   |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               |              |        |                 | 6.9                             |      | 1.7   | 0.4   | 0.0   | 0.5   | 5.6   |   |   |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               |              |        |                 | 0.0                             |      | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |   |   |
| Control Delay (d), s/veh                        |  |                 |               |              |        |                 | 40.1                            |      | 33.2  | 19.1  | 14.3  | 13.0  | 22.1  |   |   |
| Level of Service (LOS)                          |  |                 |               |              |        |                 | D                               |      | C     | B     | B     | B     | C     |   |   |
| Approach Delay, s/veh / LOS                     |  |                 |               | 0.0          |        |                 | 37.3                            | D    | 18.8  | B     | 20.5  | C     |       |   |   |
| Intersection Delay, s/veh / LOS                 |  |                 |               | 24.7         |        |                 |                                 | C    |       |       |       |       |       |   |   |
| <b>Multimodal Results</b>                       |  |                 |               | EB           |        |                 | WB                              |      |       | NB    |       | SB    |       |   |   |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.96         | B      | 1.96            | B                               | 1.90 | B     | 0.68  | A     |       |       |   |   |
| Bicycle LOS Score / LOS                         |  |                 |               |              |        | F               | 1.32                            | A    | 2.63  | C     |       |       |       |   |   |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary     |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
|--|--|-----------------|---------------|-----------------|--------|-----------------|---------------------------------|------|-----|-----|-----|--|--|--|
| <b>General Information</b>                       |  |                 |               |                 |        |                 | <b>Intersection Information</b> |      |     |     |     |  |  |  |
| Agency   | Diane B. Zimmerman Traffic Engineering |                 |               |                 |        |                 | Duration, h                     | 0.25 |     |     |     |  |  |  |
| Analyst  | DBZ                                    | Analysis Date   | Apr 23, 2018  |                 |        | Area Type       | Other                           |      |     |     |     |  |  |  |
| Jurisdiction                                     |  | Time Period     | PM Peak       |                 |        | PHF             | 0.94                            |      |     |     |     |  |  |  |
| Urban Street                                     | Taylorsville Road                      |                 | Analysis Year | 2030 No Build   |        | Analysis Period | 1> 4:00                         |      |     |     |     |  |  |  |
| Intersection                                     | Taylorsville Lake Road                 |                 | File Name     | TL PM 30 NB.xus |        |                 |                                 |      |     |     |     |  |  |  |
| Project Description                              | Covington by the Park                  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| <b>Demand Information</b>                        |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Approach Movement                                |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Demand ( v ), veh/h                              |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| <b>Signal Information</b>                        |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Cycle, s   | 135.0                                  | Reference Phase | 2             |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Offset, s  | 0                                      | Reference Point | End           |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Uncoordinated                                    | Yes                                    | Simult. Gap E/W | On            |                 | Green  | 11.2            | 70.3                            | 34.7 | 0.0 | 0.0 | 0.0 |  |  |  |
| Force Mode                                       | Fixed                                  | Simult. Gap N/S | On            |                 | Yellow | 3.5             | 5.0                             | 3.5  | 0.0 | 0.0 | 0.0 |  |  |  |
|  |  |                 |               |                 | Red    | 2.5             | 1.3                             | 3.0  | 0.0 | 0.0 | 0.0 |  |  |  |
| <b>Timer Results</b>                             |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Assigned Phase                                   |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Case Number                                      |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Phase Duration, s                                |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Change Period, ( Y+R <sub>c</sub> ), s           |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Max Allow Headway ( MAH ), s                     |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Queue Clearance Time ( g <sub>s</sub> ), s       |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Green Extension Time ( g <sub>e</sub> ), s       |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Phase Call Probability                           |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Max Out Probability                              |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| <b>Movement Group Results</b>                    |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Approach Movement                                |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Assigned Movement                                |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Adjusted Flow Rate ( v ), veh/h                  |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Adjusted Saturation Flow Rate ( s ), veh/h/ln    |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Queue Service Time ( g <sub>s</sub> ), s         |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Cycle Queue Clearance Time ( g <sub>c</sub> ), s |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Green Ratio ( g/C )                              |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Capacity ( c ), veh/h                            |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Volume-to-Capacity Ratio ( X )                   |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Back of Queue ( Q ), ft/ln ( 50 th percentile)   |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Back of Queue ( Q ), veh/ln ( 50 th percentile)  |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Queue Storage Ratio ( RQ ) ( 50 th percentile)   |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Uniform Delay ( d <sub>1</sub> ), s/veh          |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Incremental Delay ( d <sub>2</sub> ), s/veh      |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Initial Queue Delay ( d <sub>3</sub> ), s/veh    |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Control Delay ( d ), s/veh                       |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Level of Service ( LOS)                          |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Approach Delay, s/veh / LOS                      |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Intersection Delay, s/veh / LOS                  |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| <b>Multimodal Results</b>                        |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Pedestrian LOS Score / LOS                       |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |
| Bicycle LOS Score / LOS                          |  |                 |               |                 |        |                 |                                 |      |     |     |     |  |  |  |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |                |      |                 |                                 |      |       |       |       |       |        |   |   |
|---|--|-----------------|---------------|----------------|------|-----------------|---------------------------------|------|-------|-------|-------|-------|--------|---|---|
| <b>General Information</b>                      |  |                 |               |                |      |                 | <b>Intersection Information</b> |      |       |       |       |       |        |   |   |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |                |      |                 | Duration, h                     | 0.25 |       |       |       |       |        |   |   |
| Analyst   | DBZ                                    | Analysis Date   | Apr 23, 2018  |                |      | Area Type       | Other                           |      |       |       |       |       |        |   |   |
| Jurisdiction                                    |  | Time Period     | PM Peak       |                |      | PHF             | 0.94                            |      |       |       |       |       |        |   |   |
| Urban Street                                    | Taylorsville Road                      |                 | Analysis Year | 2030 Build     |      | Analysis Period | 1> 4:00                         |      |       |       |       |       |        |   |   |
| Intersection                                    | Taylorsville Lake Road                 |                 | File Name     | TL PM 30 B.xus |      |                 |                                 |      |       |       |       |       |        |   |   |
| Project Description                             | Covington by the Park Single Family    |                 |               |                |      |                 |                                 |      |       |       |       |       |        |   |   |
| <b>Demand Information</b>                       |  |                 |               | EB             |      |                 | WB                              |      |       | NB    |       | SB    |        |   |   |
| Approach Movement                               |  |                 |               | L              | T    | R               | L                               | T    | R     | L     | T     | R     | L      | T | R |
| Demand (v), veh/h                               |  |                 |               |                |      |                 | 435                             |      | 296   | 687   | 46    | 242   | 1450   |   |   |
| <b>Signal Information</b>                       |  |                 |               |                |      |                 |                                 |      |       |       |       |       |        |   |   |
| Cycle, s  | 137.8                                  | Reference Phase | 2             |                |      |                 |                                 |      |       |       |       |       |        |   |   |
| Offset, s                                       | 0                                      | Reference Point | End           |                |      |                 |                                 |      |       |       |       |       |        |   |   |
| Uncoordinated                                   | Yes                                    | Simult. Gap E/W | On            | Green          | 10.9 | 73.1            | 35.0                            | 0.0  | 0.0   | 0.0   |       |       |        |   |   |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            | Yellow         | 3.5  | 5.0             | 3.5                             | 0.0  | 0.0   | 0.0   |       |       |        |   |   |
|   |  |                 |               | Red            | 2.5  | 1.3             | 3.0                             | 0.0  | 0.0   | 0.0   |       |       |        |   |   |
| <b>Timer Results</b>                            |  |                 |               | EBL            | EBT  | WBL             | WBT                             | NBL  | NBT   | SBL   | SBT   |       |        |   |   |
| Assigned Phase                                  |  |                 |               |                |      |                 | 8                               |      | 2     | 1     | 6     |       |        |   |   |
| Case Number                                     |  |                 |               |                |      |                 | 9.0                             |      | 7.3   | 1.0   | 4.0   |       |        |   |   |
| Phase Duration, s                               |  |                 |               |                |      |                 | 41.5                            |      | 79.4  | 16.9  | 96.3  |       |        |   |   |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |               |                |      |                 | 6.5                             |      | 6.3   | 6.0   | 6.3   |       |        |   |   |
| Max Allow Headway (MAH), s                      |  |                 |               |                |      |                 | 3.6                             |      | 3.4   | 3.5   | 3.4   |       |        |   |   |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |               |                |      |                 | 37.4                            |      | 43.0  | 10.3  | 93.0  |       |        |   |   |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |               |                |      |                 | 0.0                             |      | 17.1  | 0.6   | 0.0   |       |        |   |   |
| Phase Call Probability                          |  |                 |               |                |      |                 | 1.00                            |      | 1.00  | 1.00  | 1.00  |       |        |   |   |
| Max Out Probability                             |  |                 |               |                |      |                 | 1.00                            |      | 0.18  | 0.00  | 1.00  |       |        |   |   |
| <b>Movement Group Results</b>                   |  |                 |               | EB             |      |                 | WB                              |      |       | NB    |       | SB    |        |   |   |
| Approach Movement                               |  |                 |               | L              | T    | R               | L                               | T    | R     | L     | T     | R     | L      | T | R |
| Assigned Movement                               |  |                 |               |                |      |                 | 3                               |      | 18    | 2     | 12    | 1     | 6      |   |   |
| Adjusted Flow Rate (v), veh/h                   |  |                 |               |                |      |                 | 463                             |      | 315   | 731   | 49    | 257   | 1543   |   |   |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |               |                |      |                 | 1795                            |      | 1598  | 1885  | 1598  | 1795  | 1885   |   |   |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |               |                |      |                 | 35.4                            |      | 22.6  | 41.0  | 2.0   | 8.3   | 91.0   |   |   |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |               |                |      |                 | 35.4                            |      | 22.6  | 41.0  | 2.0   | 8.3   | 91.0   |   |   |
| Green Ratio (g/C)                               |  |                 |               |                |      |                 | 0.25                            |      | 0.33  | 0.53  | 0.53  | 0.64  | 0.66   |   |   |
| Capacity (c), veh/h                             |  |                 |               |                |      |                 | 469                             |      | 533   | 1000  | 847   | 383   | 1245   |   |   |
| Volume-to-Capacity Ratio (X)                    |  |                 |               |                |      |                 | 0.987                           |      | 0.591 | 0.731 | 0.058 | 0.672 | 1.239  |   |   |
| Back of Queue (Q), ft/ln (50 th percentile)     |  |                 |               |                |      |                 | 505.8                           |      | 218.5 | 431.6 | 17.9  | 84.1  | 1831.1 |   |   |
| Back of Queue (Q), veh/ln (50 th percentile)    |  |                 |               |                |      |                 | 20.1                            |      | 8.7   | 17.1  | 0.7   | 3.3   | 72.7   |   |   |
| Queue Storage Ratio (RQ) (50 th percentile)     |  |                 |               |                |      |                 | 1.26                            |      | 0.55  | 1.08  | 0.04  | 0.19  | 4.07   |   |   |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |               |                |      |                 | 50.7                            |      | 38.1  | 24.8  | 15.7  | 20.9  | 23.4   |   |   |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |               |                |      |                 | 37.9                            |      | 1.6   | 1.6   | 0.0   | 1.7   | 114.6  |   |   |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |               |                |      |                 | 0.0                             |      | 0.0   | 0.0   | 0.0   | 0.0   | 0.0    |   |   |
| Control Delay (d), s/veh                        |  |                 |               |                |      |                 | 88.6                            |      | 39.7  | 26.4  | 15.7  | 22.5  | 138.0  |   |   |
| Level of Service (LOS)                          |  |                 |               |                |      |                 | F                               |      | D     | C     | B     | C     | F      |   |   |
| Approach Delay, s/veh / LOS                     |  |                 |               | 0.0            |      |                 | 68.8                            | E    | 25.7  | C     | 121.5 | F     |        |   |   |
| Intersection Delay, s/veh / LOS                 |  |                 |               |                |      |                 | 87.1                            |      |       |       | F     |       |        |   |   |
| <b>Multimodal Results</b>                       |  |                 |               | EB             |      |                 | WB                              |      |       | NB    |       | SB    |        |   |   |
| Pedestrian LOS Score / LOS                      |  |                 |               | 1.97           | B    |                 | 1.97                            | B    |       | 1.91  | B     |       | 0.68   | A |   |
| Bicycle LOS Score / LOS                         |  |                 |               |                |      |                 | F                               |      |       | 1.77  | B     |       | 3.46   | C |   |



Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Two-Way Stop-Control Report                             |                                       |    |    |    |           |           |    |                            |                    |   |      |    |            |      |     |   |
|--|---------------------------------------|----|----|----|-----------|-----------|----|----------------------------|--------------------|---|------|----|------------|------|-----|---|
| General Information  |                                       |    |    |    |           |           |    | Site Information           |                    |   |      |    |            |      |     |   |
| Analyst  | Diane Zimmerman                       |    |    |    |           |           |    | Intersection               | KY 155 at Entrance |   |      |    |            |      |     |   |
| Agency/Co.   | Diane B Zimmerman Traffic Engineering |    |    |    |           |           |    | Jurisdiction               |                    |   |      |    |            |      |     |   |
| Date Performed   | 5/29/18                               |    |    |    |           |           |    | East/West Street           | Entrance           |   |      |    |            |      |     |   |
| Analysis Year  | 2030                                  |    |    |    |           |           |    | North/South Street         | KY 155             |   |      |    |            |      |     |   |
| Time Analyzed  | AM Peak                               |    |    |    |           |           |    | Peak Hour Factor           | 0.96               |   |      |    |            |      |     |   |
| Intersection Orientation                                     | North-South                           |    |    |    |           |           |    | Analysis Time Period (hrs) | 0.25               |   |      |    |            |      |     |   |
| Project Description  | Covington by the Park                 |    |    |    |           |           |    |                            |                    |   |      |    |            |      |     |   |
| Lanes  |                                       |    |    |    |           |           |    |                            |                    |   |      |    |            |      |     |   |
| <p style="text-align: center;">Major Street: North-South</p> |                                       |    |    |    |           |           |    |                            |                    |   |      |    |            |      |     |   |
| Vehicle Volumes and Adjustments                              |                                       |    |    |    |           |           |    |                            |                    |   |      |    |            |      |     |   |
| Approach   | Eastbound                             |    |    |    | Westbound |           |    |                            | Northbound         |   |      |    | Southbound |      |     |   |
| Movement   | U                                     | L  | T  | R  | U         | L         | T  | R                          | U                  | L | T    | R  | U          | L    | T   | R |
| Priority   |                                       | 10 | 11 | 12 |           | 7         | 8  | 9                          | 1U                 | 1 | 2    | 3  | 4U         | 4    | 5   | 6 |
| Number of Lanes  |                                       | 0  | 0  | 0  |           | 1         | 0  | 1                          | 0                  | 0 | 1    | 0  | 0          | 1    | 2   | 0 |
| Configuration  |                                       |    |    |    |           | L         |    | R                          |                    |   |      | TR |            | L    | T   |   |
| Volume (veh/h)   |                                       |    |    |    |           | 0         |    | 153                        |                    |   | 1409 | 0  |            | 51   | 283 |   |
| Percent Heavy Vehicles (%)                                   |                                       |    |    |    |           |           | 1  | 1                          |                    |   |      |    |            | 1    |     |   |
| Proportion Time Blocked                                      |                                       |    |    |    |           |           |    |                            |                    |   |      |    |            |      |     |   |
| Percent Grade (%)  |                                       |    |    |    |           |           | 0  |                            |                    |   |      |    |            |      |     |   |
| Right Turn Channelized                                       |                                       |    |    |    |           |           | No |                            |                    |   |      |    |            |      |     |   |
| Median Type   Storage  |                                       |    |    |    |           | Left Only |    |                            |                    |   |      |    | 1          |      |     |   |
| Critical and Follow-up Headways                              |                                       |    |    |    |           |           |    |                            |                    |   |      |    |            |      |     |   |
| Base Critical Headway (sec)                                  |                                       |    |    |    |           | 7.5       |    | 6.9                        |                    |   |      |    |            | 4.1  |     |   |
| Critical Headway (sec)                                       |                                       |    |    |    |           | 6.82      |    | 6.92                       |                    |   |      |    |            | 4.12 |     |   |
| Base Follow-Up Headway (sec)                                 |                                       |    |    |    |           | 3.5       |    | 3.3                        |                    |   |      |    |            | 2.2  |     |   |
| Follow-Up Headway (sec)                                      |                                       |    |    |    |           | 3.51      |    | 3.31                       |                    |   |      |    |            | 2.21 |     |   |
| Delay, Queue Length, and Level of Service                    |                                       |    |    |    |           |           |    |                            |                    |   |      |    |            |      |     |   |
| Flow Rate, v (veh/h)   |                                       |    |    |    |           | 0         |    | 159                        |                    |   |      |    |            | 53   |     |   |
| Capacity, c (veh/h)  |                                       |    |    |    |           | 150       |    | 118                        |                    |   |      |    |            | 461  |     |   |
| v/c Ratio  |                                       |    |    |    |           | 0.00      |    | 1.35                       |                    |   |      |    |            | 0.12 |     |   |
| 95% Queue Length, Q <sub>95</sub> (veh)                      |                                       |    |    |    |           | 0.0       |    | 10.7                       |                    |   |      |    |            | 0.4  |     |   |
| Control Delay (s/veh)  |                                       |    |    |    |           | 29.0      |    | 271.9                      |                    |   |      |    |            | 13.8 |     |   |
| Level of Service (LOS)                                       |                                       |    |    |    |           | D         |    | F                          |                    |   |      |    |            | B    |     |   |
| Approach Delay (s/veh)                                       |                                       |    |    |    |           | 271.9     |    |                            |                    |   |      |    | 2.1        |      |     |   |
| Approach LOS   |                                       |    |    |    |           | F         |    |                            |                    |   |      |    |            |      |     |   |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Two-Way Stop-Control Report                             |                                       |    |    |    |           |           |    |                            |                    |   |     |    |            |      |      |   |
|--|---------------------------------------|----|----|----|-----------|-----------|----|----------------------------|--------------------|---|-----|----|------------|------|------|---|
| General Information  |                                       |    |    |    |           |           |    | Site Information           |                    |   |     |    |            |      |      |   |
| Analyst  | Diane Zimmerman                       |    |    |    |           |           |    | Intersection               | KY 155 at Entrance |   |     |    |            |      |      |   |
| Agency/Co.   | Diane B Zimmerman Traffic Engineering |    |    |    |           |           |    | Jurisdiction               |                    |   |     |    |            |      |      |   |
| Date Performed   | 5/29/18                               |    |    |    |           |           |    | East/West Street           | Entrance           |   |     |    |            |      |      |   |
| Analysis Year  | 2030                                  |    |    |    |           |           |    | North/South Street         | KY 155             |   |     |    |            |      |      |   |
| Time Analyzed  | PM Peak                               |    |    |    |           |           |    | Peak Hour Factor           | 0.94               |   |     |    |            |      |      |   |
| Intersection Orientation                                     | North-South                           |    |    |    |           |           |    | Analysis Time Period (hrs) | 0.25               |   |     |    |            |      |      |   |
| Project Description  | Covington by the Park                 |    |    |    |           |           |    |                            |                    |   |     |    |            |      |      |   |
| Lanes  |                                       |    |    |    |           |           |    |                            |                    |   |     |    |            |      |      |   |
| <p style="text-align: center;">Major Street: North-South</p> |                                       |    |    |    |           |           |    |                            |                    |   |     |    |            |      |      |   |
| Vehicle Volumes and Adjustments                              |                                       |    |    |    |           |           |    |                            |                    |   |     |    |            |      |      |   |
| Approach   | Eastbound                             |    |    |    | Westbound |           |    |                            | Northbound         |   |     |    | Southbound |      |      |   |
| Movement   | U                                     | L  | T  | R  | U         | L         | T  | R                          | U                  | L | T   | R  | U          | L    | T    | R |
| Priority   |                                       | 10 | 11 | 12 |           | 7         | 8  | 9                          | 1U                 | 1 | 2   | 3  | 4U         | 4    | 5    | 6 |
| Number of Lanes  |                                       | 0  | 0  | 0  |           | 1         | 0  | 1                          | 0                  | 0 | 1   | 0  | 0          | 1    | 2    | 0 |
| Configuration  |                                       |    |    |    |           | L         |    | R                          |                    |   |     | TR |            | L    | T    |   |
| Volume (veh/h)   |                                       |    |    |    |           | 0         |    | 100                        |                    |   | 633 | 0  |            | 169  | 1716 |   |
| Percent Heavy Vehicles (%)                                   |                                       |    |    |    |           | 1         |    | 1                          |                    |   |     |    |            | 1    |      |   |
| Proportion Time Blocked                                      |                                       |    |    |    |           |           |    |                            |                    |   |     |    |            |      |      |   |
| Percent Grade (%)  |                                       |    |    |    |           |           | 0  |                            |                    |   |     |    |            |      |      |   |
| Right Turn Channelized                                       |                                       |    |    |    |           |           | No |                            |                    |   |     |    |            |      |      |   |
| Median Type   Storage  |                                       |    |    |    |           | Left Only |    |                            |                    |   |     |    |            | 1    |      |   |
| Critical and Follow-up Headways                              |                                       |    |    |    |           |           |    |                            |                    |   |     |    |            |      |      |   |
| Base Critical Headway (sec)                                  |                                       |    |    |    |           | 7.5       |    | 6.9                        |                    |   |     |    |            | 4.1  |      |   |
| Critical Headway (sec)                                       |                                       |    |    |    |           | 6.82      |    | 6.92                       |                    |   |     |    |            | 4.12 |      |   |
| Base Follow-Up Headway (sec)                                 |                                       |    |    |    |           | 3.5       |    | 3.3                        |                    |   |     |    |            | 2.2  |      |   |
| Follow-Up Headway (sec)                                      |                                       |    |    |    |           | 3.51      |    | 3.31                       |                    |   |     |    |            | 2.21 |      |   |
| Delay, Queue Length, and Level of Service                    |                                       |    |    |    |           |           |    |                            |                    |   |     |    |            |      |      |   |
| Flow Rate, v (veh/h)   |                                       |    |    |    |           | 0         |    | 106                        |                    |   |     |    |            | 180  |      |   |
| Capacity, c (veh/h)  |                                       |    |    |    |           | 137       |    | 400                        |                    |   |     |    |            | 920  |      |   |
| v/c Ratio  |                                       |    |    |    |           | 0.00      |    | 0.27                       |                    |   |     |    |            | 0.20 |      |   |
| 95% Queue Length, Q <sub>95</sub> (veh)                      |                                       |    |    |    |           | 0.0       |    | 1.1                        |                    |   |     |    |            | 0.7  |      |   |
| Control Delay (s/veh)  |                                       |    |    |    |           | 31.2      |    | 17.2                       |                    |   |     |    |            | 9.9  |      |   |
| Level of Service (LOS)                                       |                                       |    |    |    |           | D         |    | C                          |                    |   |     |    |            | A    |      |   |
| Approach Delay (s/veh)                                       |                                       |    |    |    |           | 17.2      |    |                            |                    |   |     |    |            | 0.9  |      |   |
| Approach LOS   |                                       |    |    |    |           | C         |    |                            |                    |   |     |    |            |      |      |   |



Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Two-Way Stop-Control Report                             |                                       |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
|--|---------------------------------------|-----------|----|------|-----------|---|----|----------------------------|-----------------------|------|-----|----|------------|---|-----|----|
| General Information  |                                       |           |    |      |           |   |    | Site Information           |                       |      |     |    |            |   |     |    |
| Analyst  | Diane Zimmerman                       |           |    |      |           |   |    | Intersection               | Taylorsville at Routt |      |     |    |            |   |     |    |
| Agency/Co.   | Diane B Zimmerman Traffic Engineering |           |    |      |           |   |    | Jurisdiction               |                       |      |     |    |            |   |     |    |
| Date Performed   | 3/25/2018                             |           |    |      |           |   |    | East/West Street           | Routt Road            |      |     |    |            |   |     |    |
| Analysis Year  | 2018                                  |           |    |      |           |   |    | North/South Street         | Taylorsville Lake     |      |     |    |            |   |     |    |
| Time Analyzed  | AM Peak                               |           |    |      |           |   |    | Peak Hour Factor           | 0.88                  |      |     |    |            |   |     |    |
| Intersection Orientation                                     | North-South                           |           |    |      |           |   |    | Analysis Time Period (hrs) | 0.25                  |      |     |    |            |   |     |    |
| Project Description  | Covington by the Park                 |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Lanes  |                                       |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| <p style="text-align: center;">Major Street: North-South</p> |                                       |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Vehicle Volumes and Adjustments                              |                                       |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Approach   | Eastbound                             |           |    |      | Westbound |   |    |                            | Northbound            |      |     |    | Southbound |   |     |    |
| Movement   | U                                     | L         | T  | R    | U         | L | T  | R                          | U                     | L    | T   | R  | U          | L | T   | R  |
| Priority   |                                       | 10        | 11 | 12   |           | 7 | 8  | 9                          | 1U                    | 1    | 2   | 3  | 4U         | 4 | 5   | 6  |
| Number of Lanes  |                                       | 1         | 0  | 1    |           | 0 | 0  | 0                          | 0                     | 0    | 1   | 0  | 0          | 0 | 1   | 1  |
| Configuration  |                                       | L         |    | R    |           |   |    |                            |                       | LT   |     |    |            |   | T   | R  |
| Volume, V (veh/h)  |                                       | 291       |    | 2    |           |   |    |                            |                       | 2    | 986 |    |            |   | 197 | 26 |
| Percent Heavy Vehicles (%)                                   |                                       | 1         |    | 1    |           |   |    |                            |                       | 1    |     |    |            |   |     |    |
| Proportion Time Blocked                                      |                                       |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Percent Grade (%)  |                                       | 0         |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Right Turn Channelized                                       |                                       | Yes       |    |      |           |   | No |                            |                       |      |     | No |            |   |     |    |
| Median Type/Storage  |                                       | Undivided |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Critical and Follow-up Headways                              |                                       |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Base Critical Headway (sec)                                  |                                       |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Critical Headway (sec)                                       |                                       |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Base Follow-Up Headway (sec)                                 |                                       |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Follow-Up Headway (sec)                                      |                                       |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Delay, Queue Length, and Level of Service                    |                                       |           |    |      |           |   |    |                            |                       |      |     |    |            |   |     |    |
| Flow Rate, v (veh/h)   |                                       | 331       |    | 2    |           |   |    |                            |                       | 2    |     |    |            |   |     |    |
| Capacity, c (veh/h)  |                                       | 167       |    | 168  |           |   |    |                            |                       | 1318 |     |    |            |   |     |    |
| v/c Ratio  |                                       | 1.98      |    | 0.01 |           |   |    |                            |                       | 0.00 |     |    |            |   |     |    |
| 95% Queue Length, Q <sub>95</sub> (veh)                      |                                       | 25.4      |    | 0.0  |           |   |    |                            |                       | 0.0  |     |    |            |   |     |    |
| Control Delay (s/veh)  |                                       | 509.2     |    | 26.7 |           |   |    |                            |                       | 7.7  |     |    |            |   |     |    |
| Level of Service, LOS  |                                       | F         |    | D    |           |   |    |                            |                       | A    |     |    |            |   |     |    |
| Approach Delay (s/veh)                                       |                                       | 505.9     |    |      |           |   |    |                            |                       | 0.1  |     |    |            |   |     |    |
| Approach LOS   |                                       | F         |    |      |           |   |    |                            |                       | A    |     |    |            |   |     |    |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Two-Way Stop-Control Report                             |                                       |           |    |      |           |   |   |                            |                       |      |      |   |            |    |     |    |  |
|--|---------------------------------------|-----------|----|------|-----------|---|---|----------------------------|-----------------------|------|------|---|------------|----|-----|----|--|
| General Information  |                                       |           |    |      |           |   |   | Site Information           |                       |      |      |   |            |    |     |    |  |
| Analyst  | Diane Zimmerman                       |           |    |      |           |   |   | Intersection               | Taylorsville at Routt |      |      |   |            |    |     |    |  |
| Agency/Co.   | Diane B Zimmerman Traffic Engineering |           |    |      |           |   |   | Jurisdiction               |                       |      |      |   |            |    |     |    |  |
| Date Performed   | 5/29/18                               |           |    |      |           |   |   | East/West Street           | Routt Road            |      |      |   |            |    |     |    |  |
| Analysis Year  | 2030                                  |           |    |      |           |   |   | North/South Street         | Taylorsville Lake     |      |      |   |            |    |     |    |  |
| Time Analyzed  | AM Peak No Build                      |           |    |      |           |   |   | Peak Hour Factor           | 0.88                  |      |      |   |            |    |     |    |  |
| Intersection Orientation                                     | North-South                           |           |    |      |           |   |   | Analysis Time Period (hrs) | 0.25                  |      |      |   |            |    |     |    |  |
| Project Description  | Covington by the Park                 |           |    |      |           |   |   |                            |                       |      |      |   |            |    |     |    |  |
| Lanes  |                                       |           |    |      |           |   |   |                            |                       |      |      |   |            |    |     |    |  |
| <p style="text-align: center;">Major Street: North-South</p> |                                       |           |    |      |           |   |   |                            |                       |      |      |   |            |    |     |    |  |
| Vehicle Volumes and Adjustments                              |                                       |           |    |      |           |   |   |                            |                       |      |      |   |            |    |     |    |  |
| Approach   | Eastbound                             |           |    |      | Westbound |   |   |                            | Northbound            |      |      |   | Southbound |    |     |    |  |
| Movement   | U                                     | L         | T  | R    | U         | L | T | R                          | U                     | L    | T    | R | U          | L  | T   | R  |  |
| Priority   |                                       | 10        | 11 | 12   |           | 7 | 8 | 9                          | 1U                    | 1    | 2    | 3 | 4U         | 4  | 5   | 6  |  |
| Number of Lanes  |                                       | 1         | 0  | 1    |           | 0 | 0 | 0                          | 0                     | 0    | 1    | 0 | 0          | 0  | 1   | 1  |  |
| Configuration  |                                       | L         |    | R    |           |   |   |                            |                       | LT   |      |   |            |    | T   | R  |  |
| Volume (veh/h)   |                                       | 328       |    | 3    |           |   |   |                            |                       | 3    | 1111 |   |            |    | 222 | 29 |  |
| Percent Heavy Vehicles (%)                                   |                                       | 1         |    | 1    |           |   |   |                            |                       | 1    |      |   |            |    |     |    |  |
| Proportion Time Blocked                                      |                                       |           |    |      |           |   |   |                            |                       |      |      |   |            |    |     |    |  |
| Percent Grade (%)  |                                       | 0         |    |      |           |   |   |                            |                       |      |      |   |            |    |     |    |  |
| Right Turn Channelized                                       |                                       | Yes       |    |      |           |   |   |                            |                       |      |      |   |            | No |     |    |  |
| Median Type   Storage  |                                       | Undivided |    |      |           |   |   |                            |                       |      |      |   |            |    |     |    |  |
| Critical and Follow-up Headways                              |                                       |           |    |      |           |   |   |                            |                       |      |      |   |            |    |     |    |  |
| Base Critical Headway (sec)                                  |                                       | 7.1       |    | 6.2  |           |   |   |                            |                       | 4.1  |      |   |            |    |     |    |  |
| Critical Headway (sec)                                       |                                       | 6.41      |    | 6.21 |           |   |   |                            |                       | 4.11 |      |   |            |    |     |    |  |
| Base Follow-Up Headway (sec)                                 |                                       | 3.5       |    | 3.3  |           |   |   |                            |                       | 2.2  |      |   |            |    |     |    |  |
| Follow-Up Headway (sec)                                      |                                       | 3.51      |    | 3.31 |           |   |   |                            |                       | 2.21 |      |   |            |    |     |    |  |
| Delay, Queue Length, and Level of Service                    |                                       |           |    |      |           |   |   |                            |                       |      |      |   |            |    |     |    |  |
| Flow Rate, v (veh/h)   |                                       | 373       |    | 3    |           |   |   |                            |                       | 3    |      |   |            |    |     |    |  |
| Capacity, c (veh/h)  |                                       | 131       |    | 789  |           |   |   |                            |                       | 1282 |      |   |            |    |     |    |  |
| v/c Ratio  |                                       | 2.85      |    | 0.00 |           |   |   |                            |                       | 0.00 |      |   |            |    |     |    |  |
| 95% Queue Length, Q <sub>95</sub> (veh)                      |                                       | 34.3      |    | 0.0  |           |   |   |                            |                       | 0.0  |      |   |            |    |     |    |  |
| Control Delay (s/veh)  |                                       | 906.4     |    | 9.6  |           |   |   |                            |                       | 7.8  |      |   |            |    |     |    |  |
| Level of Service (LOS)                                       |                                       | F         |    | A    |           |   |   |                            |                       | A    |      |   |            |    |     |    |  |
| Approach Delay (s/veh)                                       |                                       | 898.3     |    |      |           |   |   |                            |                       | 0.1  |      |   |            |    |     |    |  |
| Approach LOS   |                                       | F         |    |      |           |   |   |                            |                       | A    |      |   |            |    |     |    |  |

### HCS7 Signalized Intersection Results Summary

| General Information                             |  |                 |                      | Intersection Information   |         |      |       |  |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
|---|--|-----------------|----------------------|--|---------|------|-------|---|-------|-------|--------|-------|-------|-------|-------|-----|--|--|-----|--|--|-----|--|--|-----|--|--|
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |                      | Duration, h  | 0.25    |      |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Analyst   | DBZ                                    | Analysis Date   | Apr 23, 2018         | Area Type  | Other   |      |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Jurisdiction                                    |  | Time Period     | AM Peak              | PHF  | 0.92    |      |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Urban Street                                    | KY 155                                 | Analysis Year   | 2030                 | Analysis Period  | 1> 7:00 |      |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Intersection                                    | Rouff Road                             | File Name       | AM Rouff 30 B SF.xus |  |         |      |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Project Description                             | Covington by the Park Single family    |                 |                      |  |         |      |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Demand Information                              |  |                 |                      | EB   |         |      | WB    |   |       | NB    |        |       | SB    |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Approach Movement                               |  |                 |                      | L  | T       | R    | L     | T   | R     | L     | T      | R     | L     | T     | R     |     |  |  |     |  |  |     |  |  |     |  |  |
| Demand (v), veh/h                               |  |                 |                      | 328  | 67      | 3    | 17    | 17  | 153   | 3     | 1111   | 6     | 51    | 222   | 29    |     |  |  |     |  |  |     |  |  |     |  |  |
| Signal Information                              |  |                 |                      |  |         |      |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Cycle, s  | 138.5                                  | Reference Phase | 2                    |  |         |      |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Offset, s                                       | 0                                      | Reference Point | End                  |  |         |      |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Uncoordinated                                   | Yes                                    | Simult. Gap E/W | On                   |  |         |      |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On                   |  |         |      |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Green   | 0.7                                    | 4.6             | 75.0                 | 3.1  | 8.9     | 16.2 |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Yellow  | 4.0                                    | 0.0             | 4.0                  | 4.0  | 4.0     | 4.0  |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Red   | 2.0                                    | 0.0             | 2.0                  | 2.0  | 2.0     | 2.0  |       |   |       |       |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Timer Results                                   |  |                 |                      | EBL  |         |      | EBT   |   |       | WBL   |        |       | WBT   |       |       | NBL |  |  | NBT |  |  | SBL |  |  | SBT |  |  |
| Assigned Phase                                  |  |                 |                      | 7  | 4       | 3    | 8     | 5   | 2     | 1     | 6      |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Case Number                                     |  |                 |                      | 1.1  | 4.0     | 1.1  | 3.0   | 1.1   | 3.0   | 1.1   | 3.0    |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Phase Duration, s                               |  |                 |                      | 24.0   | 37.1    | 9.1  | 22.2  | 6.7   | 81.0  | 11.3  | 85.6   |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Change Period, (Y+R <sub>c</sub> ), s           |  |                 |                      | 6.0  | 6.0     | 6.0  | 6.0   | 6.0   | 6.0   | 6.0   | 6.0    |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Max Allow Headway (MAH), s                      |  |                 |                      | 3.9  | 4.1     | 3.9  | 4.1   | 3.9   | 3.8   | 3.9   | 3.8    |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Queue Clearance Time (g <sub>s</sub> ), s       |  |                 |                      | 20.0   | 6.5     | 3.2  | 16.0  | 2.1   | 78.0  | 3.8   | 10.6   |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Green Extension Time (g <sub>e</sub> ), s       |  |                 |                      | 0.0  | 0.7     | 0.0  | 0.2   | 0.0   | 0.0   | 0.1   | 9.2    |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Phase Call Probability                          |  |                 |                      | 1.00   | 1.00    | 0.51 | 1.00  | 0.12  | 1.00  | 0.88  | 1.00   |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Max Out Probability                             |  |                 |                      | 1.00   | 0.00    | 0.00 | 1.00  | 0.00  | 1.00  | 0.00  | 0.00   |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Movement Group Results                          |  |                 |                      | EB   |         |      | WB    |   |       | NB    |        |       | SB    |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Approach Movement                               |  |                 |                      | L  | T       | R    | L     | T   | R     | L     | T      | R     | L     | T     | R     |     |  |  |     |  |  |     |  |  |     |  |  |
| Assigned Movement                               |  |                 |                      | 7  | 4       | 14   | 3     | 8   | 18    | 5     | 2      | 12    | 1     | 6     | 16    |     |  |  |     |  |  |     |  |  |     |  |  |
| Adjusted Flow Rate (v), veh/h                   |  |                 |                      | 357  | 76      |      | 18    | 18  | 166   | 3     | 1208   | 7     | 55    | 241   | 32    |     |  |  |     |  |  |     |  |  |     |  |  |
| Adjusted Saturation Flow Rate (s), veh/h/ln     |  |                 |                      | 1810   | 1885    |      | 1810  | 1900  | 1610  | 1810  | 1900   | 1610  | 1810  | 1900  | 1610  |     |  |  |     |  |  |     |  |  |     |  |  |
| Queue Service Time (g <sub>s</sub> ), s         |  |                 |                      | 18.0   | 4.5     |      | 1.2   | 1.2   | 14.0  | 0.1   | 76.0   | 0.3   | 1.8   | 8.6   | 1.2   |     |  |  |     |  |  |     |  |  |     |  |  |
| Cycle Queue Clearance Time (g <sub>c</sub> ), s |  |                 |                      | 18.0   | 4.5     |      | 1.2   | 1.2   | 14.0  | 0.1   | 76.0   | 0.3   | 1.8   | 8.6   | 1.2   |     |  |  |     |  |  |     |  |  |     |  |  |
| Green Ratio (g/C)                               |  |                 |                      | 0.26   | 0.22    |      | 0.14  | 0.12  | 0.12  | 0.55  | 0.55   | 0.55  | 0.58  | 0.57  | 0.57  |     |  |  |     |  |  |     |  |  |     |  |  |
| Capacity (c), veh/h                             |  |                 |                      | 441  | 424     |      | 249   | 222   | 200   | 638   | 1043   | 872   | 121   | 1092  | 925   |     |  |  |     |  |  |     |  |  |     |  |  |
| Volume-to-Capacity Ratio (X)                    |  |                 |                      | 0.809  | 0.179   |      | 0.074 | 0.083   | 0.832 | 0.005 | 1.158  | 0.007 | 0.458 | 0.221 | 0.034 |     |  |  |     |  |  |     |  |  |     |  |  |
| Back of Queue (Q), ft/ln (50 th percentile)     |  |                 |                      | 91.5   | 51.8    |      | 13.8  | 14.2  | 162.6 | 1.1   | 1366.5 | 2.2   | 25.8  | 86.2  | 10    |     |  |  |     |  |  |     |  |  |     |  |  |
| Back of Queue (Q), veh/ln (50 th percentile)    |  |                 |                      | 3.7  | 2.1     |      | 0.6   | 0.6   | 6.5   | 0.0   | 54.7   | 0.1   | 1.0   | 3.4   | 0.4   |     |  |  |     |  |  |     |  |  |     |  |  |
| Queue Storage Ratio (RQ) (50 th percentile)     |  |                 |                      | 0.00   | 0.00    |      | 0.00  | 0.00  | 0.00  | 0.00  | 0.00   | 0.00  | 0.00  | 0.00  | 0.00  |     |  |  |     |  |  |     |  |  |     |  |  |
| Uniform Delay (d <sub>1</sub> ), s/veh          |  |                 |                      | 48.3   | 43.4    |      | 51.9  | 54.5  | 59.2  | 14.4  | 31.2   | 14.6  | 33.0  | 14.4  | 12.8  |     |  |  |     |  |  |     |  |  |     |  |  |
| Incremental Delay (d <sub>2</sub> ), s/veh      |  |                 |                      | 10.8   | 0.2     |      | 0.1   | 0.2   | 18.0  | 0.0   | 82.1   | 0.0   | 2.7   | 0.1   | 0.0   |     |  |  |     |  |  |     |  |  |     |  |  |
| Initial Queue Delay (d <sub>3</sub> ), s/veh    |  |                 |                      | 0.0  | 0.0     |      | 0.0   | 0.0   | 0.0   | 0.0   | 0.0    | 0.0   | 0.0   | 0.0   | 0.0   |     |  |  |     |  |  |     |  |  |     |  |  |
| Control Delay (d), s/veh                        |  |                 |                      | 59.0   | 43.6    |      | 52.0  | 54.7  | 77.2  | 14.4  | 113.4  | 14.6  | 35.7  | 14.5  | 12.8  |     |  |  |     |  |  |     |  |  |     |  |  |
| Level of Service (LOS)                          |  |                 |                      | E  | D       |      | D     | D   | E     | B     | F      | B     | D     | B     | B     |     |  |  |     |  |  |     |  |  |     |  |  |
| Approach Delay, s/veh / LOS                     |  |                 |                      | 56.3   | E       |      | 72.9  | E   |       | 112.6 | F      |       | 17.9  | B     |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Intersection Delay, s/veh / LOS                 |  |                 |                      | 83.5   |         |      |       |   |       | F     |        |       |       |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Multimodal Results                              |  |                 |                      | EB   |         |      | WB    |   |       | NB    |        |       | SB    |       |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Pedestrian LOS Score / LOS                      |  |                 |                      | 2.14   | B       |      | 2.15  | B   |       | 2.10  | B      |       | 1.90  | B     |       |     |  |  |     |  |  |     |  |  |     |  |  |
| Bicycle LOS Score / LOS                         |  |                 |                      | 1.20   | A       |      | 0.82  | A   |       | 2.50  | B      |       | 1.03  | A     |       |     |  |  |     |  |  |     |  |  |     |  |  |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Two-Way Stop-Control Report          |                                       |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
|---|---------------------------------------|-----------|----|------|-----------|----|---|----------------------------|-----------------------|------|-----|---|------------|----|-----|-----|--|
| General Information                       |                                       |           |    |      |           |    |   | Site Information           |                       |      |     |   |            |    |     |     |  |
| Analyst                                   | Diane Zimmerman                       |           |    |      |           |    |   | Intersection               | Taylorsville at Routt |      |     |   |            |    |     |     |  |
| Agency/Co.                                | Diane B Zimmerman Traffic Engineering |           |    |      |           |    |   | Jurisdiction               |                       |      |     |   |            |    |     |     |  |
| Date Performed                            | 3/25/2018                             |           |    |      |           |    |   | East/West Street           | Routt Road            |      |     |   |            |    |     |     |  |
| Analysis Year                             | 2018                                  |           |    |      |           |    |   | North/South Street         | Taylorsville Lake     |      |     |   |            |    |     |     |  |
| Time Analyzed                             | PM Peak                               |           |    |      |           |    |   | Peak Hour Factor           | 0.88                  |      |     |   |            |    |     |     |  |
| Intersection Orientation                  | North-South                           |           |    |      |           |    |   | Analysis Time Period (hrs) | 0.25                  |      |     |   |            |    |     |     |  |
| Project Description                       | Covington by the Park                 |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Lanes                                     |                                       |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| <p>Major Street: North-South</p>          |                                       |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Vehicle Volumes and Adjustments           |                                       |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Approach                                  | Eastbound                             |           |    |      | Westbound |    |   |                            | Northbound            |      |     |   | Southbound |    |     |     |  |
| Movement                                  | U                                     | L         | T  | R    | U         | L  | T | R                          | U                     | L    | T   | R | U          | L  | T   | R   |  |
| Priority                                  |                                       | 10        | 11 | 12   |           | 7  | 8 | 9                          | 1U                    | 1    | 2   | 3 | 4U         | 4  | 5   | 6   |  |
| Number of Lanes                           |                                       | 1         | 0  | 1    |           | 0  | 0 | 0                          | 0                     | 0    | 1   | 0 | 0          | 0  | 1   | 1   |  |
| Configuration                             |                                       | L         |    | R    |           |    |   |                            |                       | LT   |     |   |            |    | T   | R   |  |
| Volume, V (veh/h)                         |                                       | 98        |    | 2    |           |    |   |                            |                       | 2    | 365 |   |            |    | 999 | 264 |  |
| Percent Heavy Vehicles (%)                |                                       | 1         |    | 1    |           |    |   |                            |                       | 1    |     |   |            |    |     |     |  |
| Proportion Time Blocked                   |                                       |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Percent Grade (%)                         |                                       | 0         |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Right Turn Channelized                    |                                       | Yes       |    |      |           | No |   |                            |                       | No   |     |   |            | No |     |     |  |
| Median Type/Storage                       |                                       | Undivided |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Critical and Follow-up Headways           |                                       |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Base Critical Headway (sec)               |                                       |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Critical Headway (sec)                    |                                       |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Base Follow-Up Headway (sec)              |                                       |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Follow-Up Headway (sec)                   |                                       |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Delay, Queue Length, and Level of Service |                                       |           |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |
| Flow Rate, v (veh/h)                      |                                       | 111       |    | 2    |           |    |   |                            |                       | 2    |     |   |            |    |     |     |  |
| Capacity, c (veh/h)                       |                                       | 124       |    | 127  |           |    |   |                            |                       | 476  |     |   |            |    |     |     |  |
| v/c Ratio                                 |                                       | 0.89      |    | 0.02 |           |    |   |                            |                       | 0.00 |     |   |            |    |     |     |  |
| 95% Queue Length, Q <sub>95</sub> (veh)   |                                       | 5.7       |    | 0.1  |           |    |   |                            |                       | 0.0  |     |   |            |    |     |     |  |
| Control Delay (s/veh)                     |                                       | 120.8     |    | 33.9 |           |    |   |                            |                       | 12.6 |     |   |            |    |     |     |  |
| Level of Service, LOS                     |                                       | F         |    | D    |           |    |   |                            |                       | B    |     |   |            |    |     |     |  |
| Approach Delay (s/veh)                    |                                       | 119.0     |    |      |           |    |   |                            |                       | 0.1  |     |   |            |    |     |     |  |
| Approach LOS                              |                                       | F         |    |      |           |    |   |                            |                       |      |     |   |            |    |     |     |  |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Two-Way Stop-Control Report          |                                       |           |    |      |           |   |   |                            |                       |      |     |   |            |    |      |     |  |
|---|---------------------------------------|-----------|----|------|-----------|---|---|----------------------------|-----------------------|------|-----|---|------------|----|------|-----|--|
| General Information                       |                                       |           |    |      |           |   |   | Site Information           |                       |      |     |   |            |    |      |     |  |
| Analyst                                   | Diane Zimmerman                       |           |    |      |           |   |   | Intersection               | Taylorsville at Routt |      |     |   |            |    |      |     |  |
| Agency/Co.                                | Diane B Zimmerman Traffic Engineering |           |    |      |           |   |   | Jurisdiction               |                       |      |     |   |            |    |      |     |  |
| Date Performed                            | 5/29/2018                             |           |    |      |           |   |   | East/West Street           | Routt Road            |      |     |   |            |    |      |     |  |
| Analysis Year                             | 2030                                  |           |    |      |           |   |   | North/South Street         | Taylorsville Lake     |      |     |   |            |    |      |     |  |
| Time Analyzed                             | PM Peak No Build                      |           |    |      |           |   |   | Peak Hour Factor           | 0.88                  |      |     |   |            |    |      |     |  |
| Intersection Orientation                  | North-South                           |           |    |      |           |   |   | Analysis Time Period (hrs) | 0.25                  |      |     |   |            |    |      |     |  |
| Project Description                       | Covington by the Park                 |           |    |      |           |   |   |                            |                       |      |     |   |            |    |      |     |  |
| Lanes                                     |                                       |           |    |      |           |   |   |                            |                       |      |     |   |            |    |      |     |  |
|   |                                       |           |    |      |           |   |   |                            |                       |      |     |   |            |    |      |     |  |
| Vehicle Volumes and Adjustments           |                                       |           |    |      |           |   |   |                            |                       |      |     |   |            |    |      |     |  |
| Approach                                  | Eastbound                             |           |    |      | Westbound |   |   |                            | Northbound            |      |     |   | Southbound |    |      |     |  |
| Movement                                  | U                                     | L         | T  | R    | U         | L | T | R                          | U                     | L    | T   | R | U          | L  | T    | R   |  |
| Priority                                  |                                       | 10        | 11 | 12   |           | 7 | 8 | 9                          | 1U                    | 1    | 2   | 3 | 4U         | 4  | 5    | 6   |  |
| Number of Lanes                           |                                       | 1         | 0  | 1    |           | 0 | 0 | 0                          | 0                     | 0    | 1   | 0 | 0          | 0  | 1    | 1   |  |
| Configuration                             |                                       | L         |    | R    |           |   |   |                            |                       | LT   |     |   |            |    | T    | R   |  |
| Volume (veh/h)                            |                                       | 110       |    | 3    |           |   |   |                            |                       | 3    | 411 |   |            |    | 1126 | 297 |  |
| Percent Heavy Vehicles (%)                |                                       | 1         |    | 1    |           |   |   |                            |                       | 1    |     |   |            |    |      |     |  |
| Proportion Time Blocked                   |                                       |           |    |      |           |   |   |                            |                       |      |     |   |            |    |      |     |  |
| Percent Grade (%)                         |                                       | 0         |    |      |           |   |   |                            |                       |      |     |   |            |    |      |     |  |
| Right Turn Channelized                    |                                       | Yes       |    |      |           |   |   |                            |                       |      |     |   |            | No |      |     |  |
| Median Type   Storage                     |                                       | Undivided |    |      |           |   |   |                            |                       |      |     |   |            |    |      |     |  |
| Critical and Follow-up Headways           |                                       |           |    |      |           |   |   |                            |                       |      |     |   |            |    |      |     |  |
| Base Critical Headway (sec)               |                                       | 7.1       |    | 6.2  |           |   |   |                            |                       | 4.1  |     |   |            |    |      |     |  |
| Critical Headway (sec)                    |                                       | 6.41      |    | 6.21 |           |   |   |                            |                       | 4.11 |     |   |            |    |      |     |  |
| Base Follow-Up Headway (sec)              |                                       | 3.5       |    | 3.3  |           |   |   |                            |                       | 2.2  |     |   |            |    |      |     |  |
| Follow-Up Headway (sec)                   |                                       | 3.51      |    | 3.31 |           |   |   |                            |                       | 2.21 |     |   |            |    |      |     |  |
| Delay, Queue Length, and Level of Service |                                       |           |    |      |           |   |   |                            |                       |      |     |   |            |    |      |     |  |
| Flow Rate, v (veh/h)                      |                                       | 125       |    | 3    |           |   |   |                            |                       | 3    |     |   |            |    |      |     |  |
| Capacity, c (veh/h)                       |                                       | 94        |    | 204  |           |   |   |                            |                       | 406  |     |   |            |    |      |     |  |
| v/c Ratio                                 |                                       | 1.34      |    | 0.02 |           |   |   |                            |                       | 0.01 |     |   |            |    |      |     |  |
| 95% Queue Length, Q <sub>95</sub> (veh)   |                                       | 9.1       |    | 0.1  |           |   |   |                            |                       | 0.0  |     |   |            |    |      |     |  |
| Control Delay (s/veh)                     |                                       | 289.0     |    | 23.0 |           |   |   |                            |                       | 14.0 |     |   |            |    |      |     |  |
| Level of Service (LOS)                    |                                       | F         |    | C    |           |   |   |                            |                       | B    |     |   |            |    |      |     |  |
| Approach Delay (s/veh)                    |                                       | 282.0     |    |      |           |   |   |                            |                       | 0.3  |     |   |            |    |      |     |  |
| Approach LOS                              |                                       | F         |    |      |           |   |   |                            |                       | B    |     |   |            |    |      |     |  |

Covington by the Park  
 4501 Taylorsville Lake Road  
 Traffic Impact Study

| HCS7 Signalized Intersection Results Summary    |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
|---|--|-----------------|---------------|----------------------|--------|---------------------------------|---------|------|-----|-----|-----|--|--|--|
| <b>General Information</b>                      |  |                 |               |                      |        | <b>Intersection Information</b> |         |      |     |     |     |  |  |  |
| Agency  | Diane B. Zimmerman Traffic Engineering |                 |               |                      |        | Duration, h                     | 0.25    |      |     |     |     |  |  |  |
| Analyst   | DBZ                                    | Analysis Date   | Apr 23, 2018  |                      |        | Area Type                       | Other   |      |     |     |     |  |  |  |
| Jurisdiction                                    |  | Time Period     | PM Peak       |                      |        | PHF                             | 0.92    |      |     |     |     |  |  |  |
| Urban Street                                    | KY 155                                 |                 | Analysis Year | 2030                 |        | Analysis Period                 | 1> 4:30 |      |     |     |     |  |  |  |
| Intersection                                    | Routt Road                             |                 | File Name     | PM Routt 30 B SF.xus |        |                                 |         |      |     |     |     |  |  |  |
| Project Description                             | Covington by the Park Single Family    |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| <b>Demand Information</b>                       |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Approach Movement                               |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Demand ( v ), veh/h                             |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| <b>Signal Information</b>                       |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Cycle, s  | 112.9                                  | Reference Phase | 2             |                      |        |                                 |         |      |     |     |     |  |  |  |
| Offset, s                                       | 0                                      | Reference Point | End           |                      | Green  | 0.6                             | 0.4     | 63.6 | 1.9 | 0.7 | 9.7 |  |  |  |
| Uncoordinated                                   | Yes                                    | Simult. Gap E/W | On            |                      | Yellow | 4.0                             | 4.0     | 4.0  | 4.0 | 4.0 | 4.0 |  |  |  |
| Force Mode                                      | Fixed                                  | Simult. Gap N/S | On            |                      | Red    | 2.0                             | 2.0     | 2.0  | 2.0 | 2.0 | 2.0 |  |  |  |
| <b>Timer Results</b>                            |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Assigned Phase                                  |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Case Number                                     |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Phase Duration, s                               |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Change Period, ( Y+R c ), s                     |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Max Allow Headway ( MAH ), s                    |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Queue Clearance Time ( g s ), s                 |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Green Extension Time ( g e ), s                 |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Phase Call Probability                          |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Max Out Probability                             |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| <b>Movement Group Results</b>                   |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Approach Movement                               |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Assigned Movement                               |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Adjusted Flow Rate ( v ), veh/h                 |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Adjusted Saturation Flow Rate ( s ), veh/h/ln   |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Queue Service Time ( g s ), s                   |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Cycle Queue Clearance Time ( g c ), s           |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Green Ratio ( g/C )                             |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Capacity ( c ), veh/h                           |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Volume-to-Capacity Ratio ( X )                  |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Back of Queue ( Q ), ft/ln ( 50 th percentile)  |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Back of Queue ( Q ), veh/ln ( 50 th percentile) |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Queue Storage Ratio ( RQ ) ( 50 th percentile)  |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Uniform Delay ( d 1 ), s/veh                    |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Incremental Delay ( d 2 ), s/veh                |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Initial Queue Delay ( d 3 ), s/veh              |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Control Delay ( d ), s/veh                      |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Level of Service (LOS)                          |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Approach Delay, s/veh / LOS                     |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Intersection Delay, s/veh / LOS                 |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| <b>Multimodal Results</b>                       |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Pedestrian LOS Score / LOS                      |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |
| Bicycle LOS Score / LOS                         |  |                 |               |                      |        |                                 |         |      |     |     |     |  |  |  |