

**PLANNING & DESIGN** 

SERVICES

TYPICAL PARKING DETAIL

2.74 ACRES VACANT

#### SITE LANDSCAPE REQUIREMENT

7.5% LANDSCAPE REQUIREMENT INTERIOR LANDSCAPE AREA PROVIDED

# 4,634 SQ.FT.

12,365 SQ.FT. (10.4%) EX. TREE CANOPY TO BE PRESERVED 3,909 SQ.FT. (3.3%) 41,774 SQ.FT. (35%) ADDITIONAL TREE CANOPY REQUIRED 37,865 SQ.FT. (31.7%) ADDITIONAL TREE CANOPY PROVIDED 38,400 SQ.FT. (35.2%) 32 TYPE 'A' TREES @ 1,200 SQ.FT. EACH 42,309 SQ.FT. (35.4%

### **GENERAL NOTES:**

- 1. BOUNDARY AND TOPOGRAPHIC INFORMATION PROVIDED BY SURVEY BY BOWMAN
- AN ENCROACHMENT PERMIT AND BOND WILL BE REQUIRED FOR ALL WORK DONE IN THE RIGHT-OF-WAY. 3. NO INCREASE IN VELOCITY AT POINT OF DISCHARGE AT PROPERTY LINE.
- STREET TREES SHALL BE PLANTED IN A MANNER THAT DOES NOT EFFECT PUBLIC SAFETY OR HAMPER SIGHT DISTANCE. FINAL LOCATION WILL BE DETERMINED DURING CONSTRUCTION APPROVAL PROCESS.
- 5. THE DEVELOPER WILL BE RESPONSIBLE FOR ANY UTILITY RELOCATION ON THE
- 6. VERIFY CAPACITY OF EXISTING 48" PIPE IN COBBLESTONE DEVELOPMENT.
- 7. IWD APPROVAL REQUIRED.
- MITIGATION MEASURES FOR DUST CONTROL SHALL BE IN PLACE DURING DEMOLITION AND CONSTRUCTION ACTIVITIES TO PREVENT FUGITIVE PARTICULATE EMISSIONS FROM REACHING EXISTING ROADS AND NEIGHBORING PROPERTIES.
- OFF-STREET LOADING AND REFUSE COLLECTION AREAS SHALL LOCATED AND SCREENED PER LDC CHAPTER 10 REQUIREMENTS SO AS NOT TO BE VISIBLE FROM ADJACENT PUBLIC STREETS AND RESIDENTIAL USES.
- 10. SHORT TERM BICYCLE PARKING DEVICE SHALL BE A DURABLE, SECURELY ANCHORED DEVICE THAT SUPPORTS THE FRAME OF THE BICYCLE, IS ABLE TO ACCOMMODATE A HIGH SECURITY LOCK AND IS DIMENSIONED AS REQUIRED BY THE LDC.
- ACCESSORY STRUCTURES SHALL BE IN COMPLIANCE WITH SECTIONS 5.5.5 AND 10.2.6 OF THE L.D.C.
- ALL NEW AND EXISTING SIDEWALKS SHALL BE EITHER BROUGHT UP TO OR BUILT TO ADA CURRENT STANDARDS. 13. A CROSS-ACCESS AGREEMENT WILL BE RECORDED PRIOR TO CONSTRUCTION PLAN APPROVAL FOR LOTS 1-3 AND CONNECTION TO ABUTTING PROPERTY TO THE WEST. A CROSS-ACCESS AGREEMENT FOR ABUTTING PROPERTY TO THE EAST WILL BE RECORDED IF REQUIRED IN CONNECTION WITH THE REDEVELOPMENT OF THAT
- 14. TYPE C\* BUFFER YARD WITH 1.5 TIMES PLANTING DENSITY AND SCREENING WILL BE INSTALLED ALONG THE REAR PROPERTY LINE OF LOTS 1,2, AND 3. \*TYPE C-4 PER TABLE 10.2.3 AND 10.2.4.
- COMPATIBLE UTILITY LINES (ELECTRIC, TELEPHONE, CABLE) SHALL BE PLACED IN A COMMON TRENCH UNLESS OTHERWISE REQUIRED BY THE APPROPRIATE AGENCIES.

#### **MSD NOTES**

- . CONSTRUCTION PLANS AND DOCUMENTS SHALL COMPLY WITH LOUISVILLE AND JEFFERSON COUNTY METROPOLITAN SEWER DISTRICT'S DESIGN MANUAL AND STANDARD SPECIFICATIONS
- DRAINAGE PATTERN DEPICTED BY ARROWS IS FOR CONCEPT PURPOSES ONLY. FINAL CONFIGURATION AND DESIGN OF DRAINAGE PIPES AND CHANNELS SHALL BE DETERMINED D THE CONSTRUCTION PLAN DESIGN PROCESS. DRAINAGE FACILITIES SHALL CONFORM TO MS 3. AN APPROVED EROSION PREVENTION AND SEDIMENT CONTROL (EPSC) PLAN SHALL BE IMPLEMENTED PRIOR TO ANY LAND DISTURBING ACTIVITY ON THE CONSTRUCTION SITE. ANY
- PRIVATE DEVELOPMENT REVIEW OFFICE. EPSC BMP'S SHALL BE INSTALLED PER THE PLAN AND MSD STANDARDS.
- ACTIONS MUST BE TAKEN TO MINIMIZE THE TRACKING OF MUD AND SOIL FROM CONSTRUCTION AREAS ONTO PUBLIC ROADWAYS. SOIL TRACKED ONTO THE ROADWAY SHALL BE REMOVED DAILY. SOIL STOCKPILES SHALL BE LOCATED AWAY FROM STREAMS, PONDS, SWALES AND CATCH BASINS. STOCKPILES SHALL BE SEEDED, MULCHED, AND ADEQUATELY CONTAINED THROUGH THE USE OF SILT FENCE.
- WHERE CONSTRUCTION OR LAND DISTURBANCE ACTIVITY WILL OR HAS TEMPORARILY CEASED ON ANY PORTION OF THE SITE, TEMPORARY SITE STABILIZATION MEASURES SHALL BE REQUIRED AS SOON AS PRACTICAL, BUT NO LATER THAN 14 CALENDAR DAYS AFTER THE ACTIVITY HAS
- SANITARY SEWER SERVICE PROVIDED BY L.E., SUBJECT TO FEES AND ANY APPLICABLE CHARGES.
- THE FINAL DESIGN OF THIS PROJECT MUST MEET ALL MS4 WATER QUALITY REGULATIONS ESTABLISHED BY MSD. SITE LAYOUT MAY CHANGE AT THE DESIGN PHASE DUE TO PROPER SIZING OF GREEN BEST MANAGEMENT PRACTICES.
- . KENTUCKY DIVISION OF WATER APPROVAL REQUIRED PRIOR TO MSD CONSTRUCTION PLAN
- ALL RETAIL SHOPS MUST HAVE INDIVIDUAL CONNECTIONS PER MSD'S FATS, OIL AND
- 12. ONSITE DETENTION WILL BE PROVIDED. POST-DEVELOPED PEAK FLOWS WILL BE LIMITED TO PRE-DEVELOPED PEAK FLOWS FOR THE 2, 10, 25 AND 100-YEAR STORMS OR TO THE CAPACITY OF THE DOWNSTREAM SYSTEM, WHICHEVER IS MORE RESTRICTIVE.

### **HEALTH DEPT. NOTES**

- OWNER MUST PROVIDE DOCUMENTATION OF CONNECT TO SANITARY SEWER, PSC, WITH A MINIMUM SIX-INCH SANITARY SEWER.
- 2. SANITARY SEWER SERVICE TO BE APPROVED BY MSD.
- 3. ALL CONSTRUCTION AND SALES TRAILERS MUST BE PERMITTED BY THE DEPARTMENT OF PUBLIC HEALTH AND WELLNESS IN ACCORDANCE WITH CHAPTER 115 OF LOUISVILLE
- MOSQUITO CONTROL IN ACCORDANCE WITH CHAPTER 96 OF LOUISVILLE JEFFERSON COUNTY METRO ORDINANCES.
- ALL FOOD SERVICE ESTABLISHMENTS MUST BE IN ACCORDANCE WITH 902 KAR 45:005 REGULATIONS.
- MUST COMPLY WITH 902 KAR TATTOOING REGULATIONS FOR ANY FUTURE MICROBLADING OR PERMANENT MAKEUP.
- 7. PLANS MUST BE SUBMITTED TO THE HEALTH DEPARTMENT PRIOR TO CONSTRUCTION

## **KYTC NOTES:**

REQUIRED 10' SETBACK ALONG BOTH SIDES OF AN ACCESS ESM'T

- 1. KENTUCKY DEPARTMENT OF TRANSPORTATION APPROVAL REQUIRED. 2. THERE SHALL BE NO INCREASE IN DRAINAGE RUN-OFF TO THE RIGHT-OF-WAY.
- THERE SHALL BE NO COMMERCIAL SIGNS ON THE RIGHT-OF-WAY NOR ANY SIGNAGE ATTACHED TO THE RIGHT-OF-WAY FENCE..
- THERE SHOULD BE NO LANDSCAPING IN THE RIGHT-OF-WAY WITHOUT AN ENCROACHMENT PERMIT. TREE SPECIES PLANTED IN THE RIGHT-OF-WAY MUST CONFORM WITH DISTRICT 5 LIST OF APPROVED TREES. 5. NO INCREASE IN VELOCITY AT POINT OF DISCHARGE AT PROPERTY LINE. 6. ALL DRAINAGE STRUCTURES WITHIN STATE R.O.W. SHALL BE OF STATE DESIGN.
- ALL NEW AND EXISTING SIDEWALKS SHALL BE EITHER BROUGHT UP TO OR BUILT TO ADA CURRENT STANDARDS.
- 9. CALCULATIONS WILL BE REQUIRED FOR ANY RUNOFF DEEMED NECESSARY TO BE TAKEN TO THE STATE RIGHT-OF-WAY. PROPOSALS TO ALTER OR SIGNIFICANTLY INCREASE A DRAINAGE AREA OR RUNOFF FACTORS OR TO CHANGE IN ANY WAY THE PERFORMANCE OF ANY EXISTING DRAINAGE STRUCTURE SHALL BE ACCOMPANIED BY A COMPLETE DRAINAGE SURVEY AND HYDROLOGIC ANALYSIS CUMPANIED BY A COMPLETE DRAINAGE SURVET AND HIDROLOGIC ANALTSIS (UPSTREAM AND DOWNSTREAM) BASED ON 25-YEAR AND 100-YEAR STORMS. THIS ANALYSIS SHALL INCLUDE A COMPARISON OF EXISTING AND PROPOSED CONDITIONS. REQUESTS TO ALTER ON A RIGHT-OF-WAY SHALL RESULT IN CONDITIONS THAT ARE EQUAL TO OR BETTER THAN THE EXISTING FACILITIES.
- THERE SHALL BE NO PARKING NOR ANY PORTION OF ANY PARKING LOT ON STATE RIGHT-OF-WAY.

# **LOT 1 INFORMATION**

1.20 ACRES (52,430.20 SQ.FT.) PROPOSED USE RESTAURANT BUILDING AREA 4,600 SQ. FT. PARKING CALCULATIONS: MIN. REQUIRED: 9 SPACES 1 SPACE/500 S.F. MAX. ALLOWED: 46 SPACES 1 SPACE/100 S.F. PARKING PROVIDED 35 SPACES (INCLUDES 2 ACCESSIBLE SPACES)

# **LOT 2 INFORMATION**

3 SPACES OR 10% OF MIN. PARKING REQ.

BIKE PARKING

LOT AREA 1.04 ACRES (45,508.57 SQ.FT.) PROPOSED USE MEDICAL/DENTAL/ OFFICE/RETAIL BUILDING AREA 8,200 SQ.FT. DENTAL OFFICE 4,200 S.F. 4,000 S.F. PARKING CALCULATIONS: OFFICE (4,200 SQ.FT. MIN. REQUIRED 11 SPACES 1 SPACE/400 S.F. MAX. ALLOWED 28 SPACES 1 SPACE/150 S.F. RETAIL (4,000 S.F.) MIN. REQUIRED 8 SPACES 1 SPACE/500 S.F. MAX. ALLOWED 20 SPACES 1 SPACE/200 S.F.

3 SPACES

19 SPACES

48 SPACES

48 SPACES

3 SPACES

# **LOT 3 INFORMATION**

(INC. 2 ACCESSIBLE SPACES)

3 SPACES OR 10% OF MIN. PARKING REQ.

TOTAL MIN. REQUIRED

TOTAL MAX. ALLOWED

PARKING PROVIDED

BIKE PARKING

LOT AREA 0.49 ACRES (21,455.01 SQ.FT.) PROPOSE USE RESTAURANT BUILDING AREA 1,400 SQ.FT. PARKING CALCULATIONS: MIN. REQUIRED 3 SPACES 1 SPACE/500 S.F. MAX. ALLOWED 14 SPACES 1 SPACE/100 S.F. 7 SPACES PARKING PROVIDED (INC. 1 ACCESSIBLE SPACE) BIKE PARKING 3 SPACES

3 SPACES OR 10% OF MIN. PARKING REQ.

LEGEND OVERHEAD UTILITIES --- G --- GAS LINE TELEPHONE LINE ----- W ----- DOMESTIC WATER LINE FO FIBER OPTIC LINE UTILITY POLE TELEPHONE MANHOLE

ELECTRIC MANHOLE SANITARY SEWER MANHOLE POLYVINYL CHLORIDE PIPE


PVC FIRE HYDRANT WATER VALVE GAS VALVE

**GUY WIRE** TELEPHONE PEDESTAL

#### BENCH MARK EXISTING CONTOUR LINE

M.H.#10394 EXISTING SANITARY SEWER PROP. STORM LINE

EX. STORM LINE DRAINAGE FLOW



010 BIKE RACK EX. ASPHALT PAVEMENT

EX. CONCRETE PAVEMENT/ SIDEWALK

PROP. CONCRETE SIDEWALK

**CASE NO. 22-DDP-0097 MSD WM #172** 

RELATED CASES: CASE NO. 8394 DOCKET # 09-064-01 **17DEVPLAN1019** 

FOR

240505 - RDDP16

DRAWING

0

ETAILED DE ROWNSB( SITE INFORMATI 9903 Brownsboro

 $\Box$   $\Box$ 

REVISED 9903

PLAN STATUS REV.PER AGENCY COM RESUBMITTAL RESUBMITTAL RESUBMITTAL 2023/01/26 DATE DESCRIPTION DHS DHS CRB

DESIGN DRAWN CHKD SCALE H: 1"=30" V: N/A JOB No. **240505-01-001** 

DATE : DATE