

## Paint Design Guidelines Analysis

| Current Standard Guidelines   | Nore' Winter's Draft                                | Staff Suggestions                             |
|---|---|---|
| <p>P1 Painting masonry or stucco that has never been painted is not recommended. Paint is difficult to remove, accumulated layers will obscure decorative detail, and paint coatings (even "breathable" paints) will affect the wall's vapor transmission performance. The presence of a lead oxide wash does not constitute a precedent for painting a building.</p> | <p>**Incorporated into Masonry Guideline M.11**</p> | <p>See Masonry Design Guidelines Analysis</p> |
| <p>P2 When removing paint from previously-painted masonry, use gentle treatments that have been previously tested in an inconspicuous location. Do not sandblast or use acid-based cleaners.</p>  | <p>**Incorporated into Masonry Guideline M.14**</p> | <p>See Masonry Design Guidelines Analysis</p> |
| <p>P3 Use a "breathable" masonry paint that is compatible with and can create a strong bond with existing paint, only on previously-painted masonry.</p>  | <p>**Incorporated into Masonry Guideline M.13**</p> | <p>See Masonry Design Guidelines Analysis</p> |
| <p>P4 If painting previously-painted masonry, select a color that matches the existing color, approximates a natural masonry color as approved, or is recommended by the staff. Staff is available to consult with you on appropriate colors.</p>   | <p>**Incorporated into Masonry Guideline M.12**</p> | <p>See Masonry Design Guidelines Analysis</p> |
| <p>P5 Have paint samples analyzed when possible. Paint seriation studies can determine historic pigments and appropriate colors for repainting, by analyzing a paint sample under special lighting conditions to ascertain specific color, hue, and value of paint layers.</p>  | <p>**Not incorporated**</p>                         | <p>Staff recommends leaving this out</p>      |
| <p>P6 Do not expose metal types that require protection from the elements or apply paint or other coatings to metals that were historically meant to be exposed, such as copper, bronze, or stainless steel.</p>  | <p>**Incorporated into Metal Guideline M.6**</p>    | <p>See Metal Design Guidelines Analysis</p>   |

| Current Standard Guidelines   | Nore' Winter's Draft                                    | Staff Suggestions                           |
|---|---|---|
| <p>P7 Paint replacement gutters, downspouts, metal frame screen and storm windows, roof-vent assemblies, and fire escapes to match wall, trim, cornice, or roof color of the house, whichever is most effective in reducing the visibility of these elements.</p> | <p><b>**Incorporated into Metal Guideline M.5**</b></p> | <p>See Metal Design Guidelines Analysis</p> |
| <p>P8 Be aware that historic structures often contain hazardous substances, such as lead paint and asbestos. Contact the Board of Health regarding proper methods of removal and disposal.</p>  | <p><b>**Not incorporated**</b></p>                      | <p>Staff recommends leaving this out</p>    |